



724-283-4681

SALES.BWIEAGLE@CATTRON.COM

PRODUCT GUIDE

RECEIVERS

Click on the links to view detailed product information.



SINGLE RELAY

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-20100-AC	441-20100-AC	-
9-36VDC	38-20100-DC	441-20100-DC	-
Responds to user-selectable button on transmitter	100-250VAC	38-20100-X-AC	441-20100-X-AC
	9-36VDC	38-20100-X-DC	441-20100-X-DC



THREE RELAYS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	-	-	461-5000-AC
9-36VDC	-	-	461-5000-DC



FOUR RELAYS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-2000-AC	441-8000-AC	461-8000-AC
9-36VDC	38-2000-DC	441-8000-DC	461-8000-DC
Sends confirmation of relay activation to transmitter	100-250VAC	38-2000-VBR-AC	441-8000-VBR-AC
	9-36VDC	38-2000-VBR-DC	441-8000-VBR-DC

Learn more about BWI Eagle solutions at bwieagle.com.



RECEIVERS

Click on the links to view detailed product information.



EIGHT RELAYS			
	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-20800-AC	441-20800-AC	461-20800-AC
9-36VDC	38-20800-DC	441-20800-DC	461-20800-DC



SIXTEEN RELAYS			
	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-21600-AC	441-21600-AC	461-21600-AC
9-36VDC	38-21600-DC	441-21600-DC	461-21600-DC



SPECIALTY			
	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38HC-2000	441HC-8000	-
9-36VDC	38HC-2000-DC	38HC-2000-DC	-

Three High Current
Relay, Momentary or
Toggle

Learn more about BWI Eagle solutions at bwieagle.com

