



724-283-4681

SALES.BWIEAGLE@CATTRON.COM

PRODUCT GUIDE

RECEIVERS

Click on the links to view detailed product information.



Responds to user-selectable button on transmitter

SINGLE RELAY

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-20100-AC	441-20100-AC	-
9-36VDC	38-20100-DC	441-20100-DC	-
100-250VAC	38-20100-X-AC	441-20100-X-AC	-
9-36VDC	38-20100-X-DC	441-20100-X-DC	-



THREE RELAYS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	-	-	461-5000-AC
9-36VDC	-	-	461-5000-DC



Sends confirmation of relay activation to transmitter

FOUR RELAYS

	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-2000-AC	441-8000-AC	461-8000-AC
9-36VDC	38-2000-DC	441-8000-DC	461-8000-DC
100-250VAC	38-2000-VBR-AC	441-8000-VBR-AC	461-8000-VBR-AC
9-36VDC	38-2000-VBR-DC	441-8000-VBR-DC	461-8000-VBR-DC

Learn more about BWI Eagle solutions at bwieagle.com.



RECEIVERS

Click on the links to view detailed product information.



EIGHT RELAYS			
	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-20800-AC	441-20800-AC	461-20800-AC
9-36VDC	38-20800-DC	441-20800-DC	461-20800-DC



SIXTEEN RELAYS			
	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38-21600-AC	441-21600-AC	461-21600-AC
9-36VDC	38-21600-DC	441-21600-DC	461-21600-DC



SPECIALTY			
	600 foot range 2.4 GHz	2500 foot range 900 MHz	5000 foot range 900 MHz
100-250VAC	38HC-2000	441HC-8000	-
9-36VDC	38HC-2000-DC	38HC-2000-DC	-

Three High Current
Relay, Momentary or
Toggle

Learn more about BW EAGLE solutions at bwieagle.com

