DBOX 55

Quick Start Guide

PACKAGE CONTENTS



> 1x Haptic Bridge



> 1x USB A to USB B Cable



> 1x Power Supply



Mounting Screws (4 per actuator)



> 1 to 4 Haptic Actuator(s)



> 1 to 5 IEC Plug-Lock Insert(s)



Power Cables & "Y" Splitters



	12501	2x Power Cables
	2250i	2x Power Cables + 1x "Y" Splitters
	3250i	3x Power Cables + 1x "Y" Splitters
	4250i	3x Power Cables + 2x "Y" Splitters

OPTIONAL COMPONENTS (SELECTED AT ORDER)



Endings (captive or non captive)



Brackets ("L" or "U" shape)



Pivot Delrin

OVERVIEW

Thank you for purchasing your G5 haptic system! Please make sure to follow each step one by one to make your system operational.

- Unboxing
- Inventory
- Voltage Selection
- Haptic Actuator Endings
- Brackets Installation
- System Connection
- D-BOX Connect Account Creation
- D-BOX Motion Core Installation
- System Configuration
- Test & Play

Complete G5 User Guide is available here

1 UNBOXING

- 1 Unpack the product from the box.
- 2 Visually inspect the product for damage.
- 3 If any part appears to be broken, contact the D-BOX Support Team*.

2 INVENTORY

Ensure that you have all the components necessary to assemble your system. Refer to the "Package Contents" section if needed.

3 VOLTAGE SELECTION

Set all haptic actuators to meet your region power voltage by using the switch selector located underneath the casing:



4 HAPTIC ACTUATOR ENDINGS

NON-CAPTIVE ENDINGS

G5 haptic actuators come native with non-captive endings. Once the actuators are installed on your platform, simply drop the actuators into the provided metal cups:







4 HAPTIC ACTUATOR ENDINGS (CONTINUED)


CAPTIVE ENDINGS (optional)

Please refer to the G5 User Guide for detailed instructions. Never operate the haptic actuator(s) without the ending installed. This may lead to irreparable damages to the actuator:




5 BRACKETS INSTALLATION

Attach your haptic actuators to your platform using either the brackets provided by D-BOX or your reseller. "U" brackets should be mounted first on your platform:



Reseller brackets could be attached in a different way depending on the model. Please refer to the reseller instructions.





6 SYSTEM CONNECTION (CONTINUED)

2 Connect the Haptic Bridge to your PC using the USB cable provided with your haptic system. Connect the power supply to the Haptic Bridge as well as to a power outlet:



Do not connect your Haptic Bridge to a USB hub.

3 Connect all actuator power cables to a power outlet. Use the "Y" splitter(s) to simplify the connection.

Install an IEC Plug-Lock insert to each IEC female connector and make sure that all power cables are firmly inserted:



7 D-BOX CONNECT ACCOUNT CREATION

Create your D-BOX account here.

This is mandatory to to install haptic codes for games (D-BOX Coded Gaming mode) and to have access to D-BOX Coded Video mode.

You will be prompted later to log in when opening the D-BOX Game Center or the HaptiSync app.

D-BOX MOTION CORE INSTALLATION

- 1 Download D-BOX Motion Core here.
- 2 Extract & install Motion Core on the computer (PC) that will be connected to your haptic system.

D-BOX Motion Core includes system drivers in addition to a complete software suite including the following software and utilities:

- D-BOX Control Panel
- D-BOX Game Center
- D-BOX Adaptive Gaming Configurator
- D-BOX HaptiSync App
- D-BOX System Monitor
- D-BOX Stimuli Presenter


Take note that this software cannot be used until you complete your system configuration at step 9.




9 SYSTEM CONFIGURATION

Your Haptic Bridge comes with a blank configuration. You need to configure your Haptic Bridge to match your haptic system configuration using the D-BOX System Configurator.

- 1 Download D-BOX System Configurator here
- 2 Extract the compressed file and run the installer. Take note that the User Guide is located into the Windows Start menu/D-BOX folder.
- 3 Firmware update:
- a) Make sure your haptic system is powered on.
- b) Open the D-BOX System Configurator from the Windows Start menu/D-BOX folder. From the Firmware Update tab, click Refresh Firmware Status.
- c) If the system shows "Outdated (Update firmware)", click Update **Firmware** and follow the on-screen instructions:



- 4 Configuration update:
- a) Select the Configuration Update tab. Click Refresh Information. Make sure the Actuator Count matches with your system. If not, make sure that all power cables and RJ45 are firmly connected.
- b) Enter the configuration number matching your system (see section 6) or select the axes you want for your system. Click Apply Configuration:



Close the System Configurator when completed.




10 TEST & PLAY

1 Testing your system: From the Windows Start menu, open the D-BOX Game Center application and enter your D-BOX Connect account credentials. Make sure your HaptiSync Mode is set to **D-BOX Coded Gaming**. Click on the **Global Settings** tab then click on the **Control Panel** button:



From the Device Priority List, select your Haptic Bridge then click the **Test** button. Your haptic system should start moving and vibrate following a factory haptic pattern:



Click the **Test** button again to stop the test.

- 2 D-BOX Game Center: It's now the time to enjoy your new haptic system with your favorite game or movie! Make sure to select the appropriate HaptiSync Mode from the Game Center drop down menu:
 - D-BOX Coded Gaming: Premium haptic experiences for D-BOX coded apps, simulators & games. Use the Adaptive Gaming mode if your title is not in the list. Click here for more details.
 - D-BOX Coded Video: Premium haptic experiences for D-BOX coded movies, TV shows, using audio synchronization. Click here for more details.
 - Adaptive Gaming: Haptic experiences using real-time events from game controller or keyboard. Click here for detailed instructions on how to use this feature.
 - Adaptive Audio: Automated haptic experiences for any movie, music, TV show and games using audio processing. Click here for more details.