


Operating Guide


VFM 2 DN 65-250 PN 16 & PN 25




MAINTENANCE
FREE





VFM 2
(DN 65-250)





VFM 2 (DN 150-250) +
AMV(E) 85, 86






VFM 2 (DN 65-250) +
AMV(E) 65x







IP 54
AMV(E) 65x




IP 54
AMV(E) 85, 86




V.B.045.2/02




P_{max} (bar) EN-GJL-250 (GG-25)



P [bar] EN-GJS-400-18



VFM 2




–10°C / 2°C

Adapter

Adapter

DN	Actuators
65-125	AMV(E) 65X + adapter
150-250	AMV(E) 65X

DN	Actuators
150-250	AMV(E) 85/86



Type	DN	PN 16							PN 25							PN 16 & PN 25		
		L	L1	H	k	d2	n	Weight (kg)	L	L1	H	k	d2	n	Weight (kg)	H1	H2	H3
		mm							mm							mm		
VFM 2	65	290	185	336	145	19	4	25	290	185	336	145	19	8	23.5	114	493.5	-
	80	310	200	336	160	19	8	33	310	200	336	160	19	8	27	114	494.5	-
	100	350	242	414	180	19	8	48	350	242	414	190	23	8	46	148	528.5	-
	125	400	250	416	210	19	8	57	400	270	416	220	28	8	56	149	529.5	-
	150	480	310	516	240	22	8	101	480	320	516	250	28	8	102	182.5	628.5	639
	200	600	385	669	295	23	12	208	600	385	669	310	28	12	197	245	686	685
	250	730	500	728	355	26	12	348	730	500	728	370	31	12	334	267	732	732