



Package Contents



Round Panel Light ×1



Telescopic Column ×1




Base ×1



Remote ×1




Phone Holder with
Super Clamp ×1



Power Adapter
×1

Product Illustration



Product Illustration

① Screen

② Color Temperature Dial:

1. Turn clockwise to increase color temperature until it reaches its upper limit.
Turn counterclockwise to decrease color temperature until it reaches lower limit.
2. Short press to cycle through preset values: 3000K-3500K-4400K-5600-6500K-3000K.

③ Power Input:


④ Angle Adjustment Knob:

⑤ Power Button/Brightness Dial:

1. Short press: power on/off
2. Turn clockwise to increase brightness until reaches upper limit.
Turn counterclockwise to decrease brightness until reaches lower limit.

⑥ Panel Light Locking Knob

Remote



① Brightness “+” Button:

Short press to increase brightness; long press for quick adjustment to 100%.

② Color Temperature “-” Button:

Short press to decrease color temperature; long press for quick adjustment to the minimum.

③ M Button:

Short press to cycle through pre-set values: 3000K-3500K-4400K-5600-6500K-3000K.

④ Quick Brightness Adjustment Button:

Short press to cycle through preset values: 20%-40%-60%-80%-100%-20%.

⑤ Power Button:

Short press to turn the light on and off.


⑥ Color Temperature “+” Button:

Short press to increase color temperature; long press for quick adjustment to the maximum.


⑦ Brightness “-” Button:

Short press to decrease brightness; long press for quick adjustment to 1%.

Assembly Guide



- ① Turn the threaded piece of the center column into the base until secured.
- ② Attach the phone holder to the center column, then place the phone inside the phone holder.



- ③ Mount the panel light on the top screw of the center column, then secure it with the locking knob.



- ④ Loosen the angle adjustment knob and set the light to a required angle, then tighten the knob.

Safety Precautions

1. Do not drop the product or expose it to strong impacts.
2. Avoid direct eye contact with the light to prevent eyesight damage.
3. Keep away from flammable and explosive materials.
4. Do not use in rainy or humid environments.
5. Turn off the power when not in use.
6. If not used for an extended period, store the product in a well-ventilated, dry place away from heat sources and magnetic fields.

Specifications

Model	BR13
Power	24W
Input voltage	DC 24V/1.5A
Color rendering index (CRI)	95
Color temperature	3000K-6500K
Maximum illuminance	1600lux/0.5m
Weight (accessories included)	7lb/3.24kg
Size (accessories included)	ø12"x79.5"/ø30.5x202cm