POWERDETECT" Clean & Empty Cordless Vacuum

OWNER'S GUIDE



contrain contlets so an easin funds on content represents to a second receiver, explaint all ghost field, good fine, paint as the mile text, month pooling, at last according to mile of the particular and the second common of the set.

amon the security between union is a

eaning mainmosites, or sexualished ing

DONOT out or shape other than the finance of the same of the broadenship.

 $\mathbf{AG}_{\mathrm{s}} \propto \cos(\mathbf{a})^{2} \, |\mathbf{b}_{\mathrm{s}}| \, \cos \mathbf{a} \, \mathbf{n} \, \mathbf{d} \, \cos \mathbf{n} \, \mathbf{p} \, \cos \mathbf{b} \, \mathbf{b} \, \mathrm{doro}$

27. DO NOT modify or although to repair the

ne ke og i otte var med transvert og int ner transverske i forderer i det

would'n ordina ballery you be file cooptiat nd cated in this manual, BO NOT use the terrory or years in file ray beyonded flories

carrages. Larraged or modified carrolled may be in it on modified by the model of

e, an emiliar espíritary.

connecting or disconnecting motor sec

record exacts emove as no considerations. Conductive dand to exact

51. For IFECCO Serva, use only onerging dock.

33. Any first large way beam to stake journal of present large way beam to stake journal of the present large and property the maked proceedings.

53. Johannia St. Committee of the com

contont seven sorts reciped note: 54. Cartely should not be stoned at temperatures below 250, 27.41°F or space 10.19°F, 40°C) to

maintain ong-nome came of the TO NOT many in the value of the relationship of kine his (400%) in more 10400 (1 41%).

Chaminin ensetate or at temperatures subject of the second distance has damage

the bollery and increase the next inc.

16. Standard spot and income. BO NOT includes your hipping 20, (27, 159). Thus is

10 to 10.

a prilanti e a manutem era ce

DO NOT an occur the patterny to the or personnel residuous 2007 (19070) to minery

es, se sopicale". Laggeria per una aire a colligada

59. Disconnect the bottery back from the

AR. Far IP CCC and IP30 Volkados Arty Let

fine changing conditions of does not fit fully
into the outer reviews that plug II first 1 does
tent it contacts quelfied a company BD.

HOT lense are purious or more more by reflex

perfoliant form of record and remove the

a resided the mikelish because a nine rake.

perjance eveneent Respicare away from

satury pushaba 1840, 9

an unit official be environed unit.

dd, no ent on the extension on an

43. Uppling the potent care from a uler when the line is a section of careforing.

the ontriacolite standard to confi

45. Turn off a licentrob before unplugging 46. US NOT pull in constitution (), a constitution of the constitu

marigue of hitters are as the of organic

Liegnoras may me bili caractiquiza-

Appliance before making any adjustments, onenging eccessories, or ettoring expliance. Such present so unterly make the receives the associate into the eccessories of electronics.

To provide informational are single about a provide arm is powered off ballots skelling.

ora i naisath a colo DC HST ... y e paisteasi lanc'nye coth

ADCI-1750CC, To 17°CCC Serves, only use cattery charges 180CA-503100 (Full or MLIKE -7305)CC.

28. A wark turn all this appliance being

rouge or figure tool.

anamin'ny matrix ao fivons

BATTEBYPACK

25. Durant deuten nicht eiter, meinzer ande

raggang in with anyon. Tal^{ag} pharasan na padara with as neombore.

unglugging the chargest 24. Think^M (Chargest)

IMPORTANT SAFETY INSTRUCTIONS

FOR HOUSEHOLD USE ONLY

▲ WARNING

When using an electrical appliance, to reduce the risk of fire, a actific shock, injury, or processy country, basic resolutions strough aways so followed, including the laterators:

READ ALL INSTRUCTIONS DEFORE USING THIS VACUUM:

- has income object there a leaving necessary bearing a pure breaker is assume that, precises for necessary in some that some the forest making the country the floor needs when contains the country of the countr a wethical contractions.
- Note that the control of the co
- Jie only kent of replacement parts
- datasetti, micanna ne no se, klobalt o cerro. Language and with the the many 1. DO HOT use the bacular like any consess.
- ather than a operate writed in this manual. . With the expect on of their berdend dust. tup, DO NOT report and temporation was uno to water or the like like.
- assessment the more of the control of the concharlings, DO NOT also the covered w so cased by shilteren i DO HOT allow to be used as a tox.
- Dove super-pion a nacessary when used near ship ren SEMESSE JAE
- Isotopolicine cambo used by servers and reduced viscoul conserv, or many popular is an object experience and chooledge if they have been given supervision or not righted concerning use of e agli me in la de versant i ma e tan le la ma esale de la dina qui a la ce
- nomes in exercit or to make a cord of Africant, more the vacuum before connecting and sconnecting any current cerrying makes, motor secundaries orangers, berrollos, or enter abornization
- 10. no entre este ou que se con vic-
- Astronomy. II. DO NOT use → thous ductions. IESA and
- Pre-mote if her and solt inlier in place During the North Medical and telephone is seen, bother in an exact sort in a warren by 13. DO NOT put any oblects into nazyla or
- ecceptor y openings DO NOT use with any opening a coston; keep find of our , i in, he n and engining that they led use a riles.
- '4. US NOT not for exercise to vary all forces on the first of the control of the veguum off. Remove will obstructions before
- source of the increase.

 In proceed with the countries of the boundary of the second state. krowle with . 15. BO hOT use!" western a not working as b
- erou di orines baen d'oppes, demagas, le'il Americans, and opposition water.

 Accept that we read thought or
- 18. BO NOT wave the cooper protected
- while powered on.

 18. When present domain path is according CONTRACTOR OF THE PROPERTY OF THE PARTY OF T
- Linear control of a great 20. BO NOT place vacuum on untrapia
- e. Now our according or backet 21. Control of a park up
- c: Ligada
- a) La golacidade
- Fancia de la principa de la lava marca. cosa e no como A
- d) Large quantiles of out (including hyperi il replace solt, chemberoli Dá NGT i za svienistrach hardita poka
- See John on the managers of the contract.
- en are to saula en matches).

 1) If an macia an opmoust ble materia a (lighter fluid, gave the or herosene.
- p has no need to need use anneed to be reduced by 25. BERGT to the close of carried Lybody (a
- ng Western in presidents d) Speces that are and pead and may

- 42. The area to the power is polynomials also be bethe or great in i dyn gwdi i caesatri e yn marchaeth ha tha as

ODOR NEUTRALIZER TECHNOLOGY

- Change the following section is a first as a in Ciden No. Galletin earn order, earliene a) BO NOT attempt to obsesse note the
- austrick u. hij Assa come no totar de bage one ne to be esto q
- BO NOT creedly into all for the contridge.
- tj. ke ar zayî ni rek nen maja t of Keep away can could stark and secon
- f) BO NOT present all est our light. DOMESTIC DAY SIPST AIR
- a). A-projective; or upmay and impred

.44. The length of the power rupoly colo

DI Economiae. Remession factionses processing the rest control of the second of

- elter renoling Piloteries or est develops such a discussion / Lagran
- dt. Impla, on Province on a freshan I Вем им ехропология влу-варисску аутобити. Гаутобити enals, saek medica (sovice/strent on
- a) Ingertkin BO NOT Indicate with ring, we concluded a decayle in their

HOUSE BEHIND OF CORREST OF CUE FAC ACREST CARROLL BEING CONTROLL OF CONTROLS OF THE CORREST CARROLL OF CONTROLS OF CORREST OF A SECTION OF

SAVE THESE INSTRUCTIONS

Accessory type and quantit

may vary depending on the

िक स्वर्थ के 196€

Data: New Follows

Contractors

ODOR NEUTRALIZER TECHNOLOGY

ADJUSTING THE ODOR INTENSITY

lip up the dial handle and rotate the odor dia

to adjust Odor Neutralizer Technology intent N

insertion/Removal: Rotate the odor dial to e.gn the Lea

rrows. Remove the dial to access the odc

ntensity to the lowest level when the vac. 11- 5

recommended setting for optimal performance.

Low: Rotate the dial toward the Low position to decrease the

High: Rotate the dial toward the High position for the High-

intensity level when the vacuum is in use. "It stock from is the

or to unlock the dial for cartridge access.

kremiere Flavge

AUTO-EMPTY ASSEMBLY (IP3000)

- Slide the Wand onto the neck of the Floor Negzie until it clicks into place
- 2. Align the Hand Vacuum nozzle opening with the top of the wand and slide it on until it clicks into place.
- Make sure the Dock is facing upright. Slide the Charging Post into the slot on front of dock until it clicks.
- 4. Place the dock on the floor near a wall outlet. Plug the Power Cord into the outlet
- 5. Store the crevice tool accessory on the mount on the dock.
- 6. Refer for Odor Installation and Replacement instructions.

ius: 🛊

(Dias : 🖡

For proper operation, ensure all components are completely connected and clicked into place.

Mailler FX

HOOP A to the diagraphs of shallers, in difference of

NON-AUTO-EMPTY ASSEMBLY (IPIOCO)

- A life the Wand crop the rock affect Floor Nozzle a franciska moglete i
- 2. A $\eta_{\rm s}$ title. Find Vacuum inschaloper who the cap of the wand and sind than method a laboratory
- -th process counciliantly sold of to less to be one plantify connected and shaked the base.

naktie 🗸

The images shown in this

manual are for illustrative

subject to change.

urnoses only and may hi

Floor Mass



AUTO-EMPTY DOCK Align the teal arrow on the dial cover with the arrow on the auto-empty dock, then reinsert the dial into the auto-empty dock. Rotate the dial counterclockwise until it clicks into an intensity setting to engage. Rotate further to change the intensity setting.

5. USED CARTRIDGE

BAC STRAD WEN LIATENI.

TAIDIAL

Allegate vallega i dwaret

steet the cargo rewit the

selice arrow on the ade of

the distoryer than ment the

the statution, classes as to know

ODOR NEUTRALIZER TECHNOLOGY TIPS

st Particle poor paritridge from diel F_{2} ou don't werninge behan two time 0oor betriel ste.

The mainstead are deep Ne, to be an to the constytion and in average much over the control of the province of the control of the

HAVELS - IN COORDE INSCRETO DE NICERO DOMENTE. ANTOCIANDO ARROCANDO CRIPA A OFICIA A CUARTE PAGA COORDE COMPANIO. A COMPANIO COMPANIO A COMPANI

DOOR CARTRIDGE REPLACEMENT

2 HERRICA GLD D CASTR DGE

Chap again a din noga as recommendad undar Oper Cartridge Rapticamen

knowledding. De low replacement instructions to ensure comitted performence.

Odor Dial Yest be installed for Vacuum to Function Properly

If well both messes and disanced up intorquishly disantific vacuum.

diear of 1 ters agree of menerous and artifical norm ters.

En ety ineidas, expire artista ng year wysatim.

Elpiudica concluente intata i Batateleta contide gel

Halmiene roe Raguired

E-agrance Strongth Core Time

I. VAMOVA COOR JIAL FROM THE AUTO-EMPTY BOCK


Disposars a moderatories by decaring threater track

MOTE Only on the Ego of the Color of the Silver of the Color of the Color of Color of the Color

Prior to first use, charge the hattery completely LED BATTERY POWER AND

CHARGING INDICATORS

4. INSTALL DIAL IN THE



Charging

- LED on the battery pack will pulse yellow when reaching 0-75% charge
- LED on the battery pack will pulse green from 75% 100% charge.
- ☐ White LED the battery pack is fully charged.


LEDs turn off once the battery is fully charged. 2. Unit will not power on when charger is connected


BATTERY CHARGING INFORMATION -Half Charge Low Charge No Charge Full Charge

authorized recycling center or to the retailer for recycling. Contact your local recycling center

CHARSING


CHARGING WHILE IN STORAGE NODE





chamata y and worse in Tenthe docs Mas. sure the contacts on the world are digned, with the contacts on the charging pro-When can area is contribute and you need active the circle are after off the cost.

To detuce the find value in from the wene, press the front flott relative button on the hand we where II meets the wand, then I make the hand which has hand. sallium to de word afor the land a color atentities agent the topic in relevand and stice to ar full holder mappeds.



expressions an expression of 15% Author 55% in charger pugnific the port both with the idial on the hencie diversion. COTT index that share well-as the large partial state of the

all high process that day yet sating a

The state of the s

BATTERY RENOVAL

HENCYING THE BALLERS




To remove the partery from the paid socium plassitioner east tall bit including lead of a see call the battery in remainly since the partery into the compartment in the centile. red it allows late place.

USING YOUR VACUUM


CONTROLS AND CLEANING HODES



Press the @ justion on the for turn on bower. To turn off plower, presi the button again. To taggle between ECO DETECT, and 9009T modes, gress the mide selection trapper



When spiright, the nozzie will lock to allow for freetanding storage when the hand vac is dietaclised. To began cleaning with the floor nozzle, disengage the lock by stepping on the nozze and fitting the hand vac down.



When the LED indicator light is willite, this meams no heavy stebris is detected and suction power is normal. When the escure senses newy debrix, the light will turn deep purple and suction will increase for more cleaning ower When the indicator light turns light simple, debris to being remo reaming with the indicator turns white again

PRINTED IN MEXICO



ien an edge is defected, the headights will thurningto on the olds where the edge detected, to fiscus on largeted determ

A description of Year Jeddening
 A description

814100378 Elbrd: J.M. / SC: 02-21-2025 OBPN: IP1000_IP3000Series_IB_REV_Mv1_241009 SHDML: IP1250_B / ADD: IP1251

RECYCLING THE LI-ION BATTERY

When the Shark' Li-ion battery needs to be replaced, dispose of it or recycle it in accordance with local ordinances or regulations. In some areas, it is illegal to place spent lithium-ion batteries in the trash or in a municipal solid waste stream. Return spent batteries to an

tree Committee House in the artist of Country

AGES. The Sind halong the Hill ideas have discharged by Landau and Ages and Specification the 1996.





an fernace of wield advised to see that are

ABOVE-FLOOR CLEANING



Describitional disaction to stem groups from areas Press the root but in elected but on on the hand see where it receives a weed than Pi off the hand see turn. To write him because is to the non-division of about 16 the deeping in the model of premove, pressore the right label release purpose one regulates where a meets the ware, and slide in the processes at


To detect the file acressed from the word, stap on the indulation the pressing the backet is easy to that of the backets of realward. If the want to remove in to realsaft, what dust in the decided of the floor cone after aloa for until the crokents, years.

ABOVE-PLOGE WITH WARD

MULTIFLEX' WAND



Pryontived up mode for Love the Milhfel EX-webbigour capacity at the application of a and a furniture and mischer hard to read cross lines. the lauthor the back of the wend to adjust the engle. To return to the original engle, streighted the wand until th de les myeres est



 $\ell_{\rm obs}$, in later on the back of the ward in eight 0.4 . When it is down into storage book on en Bieladas, bitospostawil a citar surface for more success.

MAINTAINING YOUR VACUUM

EMPTYING THE BOCK DUST BIN



Emply the dock you, bin when the Bust Bin Lutinuszalor light comes on. To remove the library little in by the benefit



plants, yither arrived it over the heath and t preceivé release outron on the cide. The noticem will open to release the deer's

EMPTYING THE HANDHELD VACUUM DOST COP



To precity the bondhold values (P1000): Sured distribution in of the bower and need the range was over the boart. Freed the referee burton and the dust due lid will drop open

USING YOUR VACUUM

USING THE AUTO-EMPTY DOCK




Place the vacuum on the dock in a downward motion. Once properly attached, the automatic evacuation process will begin. The



Once execution is complete, the -accum will confirms charging on title a removed from the cook.

USING THE AUTO-EMPTY DOCK



Use Quiet mode to dock and charge the secular mode to dock and charge the secular without automatic execuation. To activate Quiet mode, move the slider to the right. To deactivate quiet mode, move the slider to the left. Do not use Quiet mode while the vacuum is evacuating.




The Dust Bin Full indicator will illuminate when the dust bin is full of debris and needs to be emplied. To reset the indicator, remove the dust bin and empty it.

Note: Do not remove the vacuum while the execuation cycle is taking place.

MAINTAINING YOUR VACUUM

CLEANING THE REPAIRTLER (171000 SERIES).

NOTE: In sertic, LPA it is a least once in nor this maintain suction bows. More treatment of an inguine processory with heavy user is clear the little, these tile in while they and glow it to a years party for upon 15 hours before triavaling. Tablet income an income tween weekers when preced-



していっとつの 月三つの 引かる 直がし pression dust exploringly in out on a scenifier on.

Then processes out
a processy pullbaged

zice i le disticupietti ho




substitute yorky pull the ILPA Herbotto the A After the file has were n ecolone in doud completely aide Londo moine baco veguin.




4. Ph. 10. 100 37 decided in the first release out, and debris into the trian, but the lower on the potton of the durant in and the bottom

CLEANING THE HEPA FILTER (IP3000 SERIES)



 blackers and LPA litter cressing Dust Cub Empty butten to open the curv ana. Uramai see Urang su e culton and alice the dust cup on the hand yet.



and and 5. Alian the Therthologian ringed and eindried name cooks sind if each




te release destrainé como lete thancase, ou lete lever pointe potrait et tra day, can em. Corbottem Teller Loosen


IMCORTAND FOR MOTH remorphisms therefore a fine of the vertices by the entire of some and the entire of a continuous section and in the entire of the entire

CLEANING THE AUTO-EMPTY DOCK FILTER.

moth, a dividuant




olescess the treatment experimentation. thereby the same settle in the south of the body then tilt the cooked. If till off, Sengve the filter from the cook called the ter has page in modernal or educar washing sy reinserting it, into the dock and rectacing i the Birer open.




Sixissess Jim Auto-Empty Exhaunt Foam Ther, make the dust bid. Before removing to ok a stiffner filter, vectours off any fire cery, her the surface. Left the filter but of the cock, their mass it with water prey for help as tough Allow the filter to all dry compactly before satisfacing it.

As a loss of collectivity the discount materials in the collection of the first section of the collection of the collect

NOZZLE MAINTENANCE




to looke the across to the invoke.



- 4. Or country eveniency the substitute from Una record (gray)
- 2. Presidite notate release button to detroit the recode from the world (Fig. 1) When rendering the oriental, make some the morre conswitted by the wide or 3. Durance possible with and they are now here.

CLEANING THE SENSORS



Make sure to diennine. Detact survey conduity as held and officer debats. mis pardada e tu sap as thanget in emi-開動: Mina sa spenaly obstructor DETECT rook will not expend the

To clean the sensors :

cos bon /1 o. 35

. Turn off power and remove the floor nozzle.

- 2. Locate the Dirt Detect sensor in the nozzle of the hand yet (Fig. 1), the | ohr Detect" sorror. on the top of the nozzle (Fig. 2), and the Edge Detect sensor on the side of the nozzle (Fig. 2). Gently wipe the sensors with a microfiber cloth and remove all hair and remove.
- 4. Reattach the floor nozzle to the rest of the unit and turn on power. Verify th: unit
- is continuous normally

CLEANING THE HAND VACUUM DUST CUP (IPSCOO)



one nove the bushque on your If \$000.


nanc vacuum, press the release but on and a life the cust cup off the hand year



2. Haza thy Boat Call amony outlan to open ля сис. съртка / гу 25.

CHECKING FOR BLOCKAGES IN THE VACUUM

I yet han over a randler sharp object or nessed in rose than jo white suctaining it hack for allockeds or objects caught in the provincial



the Ward:

Bornsyntre band van um file.

any even a en blockagus.

Checking for Blockares in

Greeking for Stockanes in the land Veguum: 1. Iu - 2" th. 2. cu. m

A. Check et intelle populates to the destruction districts

tempina excusiva

for alcakamas and availa-4. Cicar sway arry dobits of Justian S

2. Set of the early specific and 2. Jet of the early from the year punishing the second A charakthach and sight rewords. A. Prossithe a Jacket Lindone

Congress of the

1. June off the vectors

ficer novemen

m proces.

Floor Mozzies

Checking for Blockinges in the

Latter and slide the breampt but of the mass wi


ata religio los madas

incothe condensioning everything is lined uplane.

4. Cleanany biobleges and ... clease any ophils from the

5. Shoulth, prestro fibres.

CHECKING FOR BLOCKAGES IN THE AUTO-EMPTY DOCK



Checking for Blockages in the Charging Post:


1. Unplug the dock.

2. Remove the vacuum from the dock. 3. Press the latch on the back

of the charging post and lift the post away from the dock.

4. Check the end of the charging post and top of the dock for any door's or

Writinger 2005 and



Checking for Blockage. In the Dock:

2. Remove the vacuum "The the dock.

the dock.

and openings.

1. Unplug the dock.

3. Remove the dust bin from

Remove any debris : blockages from all rich.



TECHNICAL SPECIFICATIONS GOOD NEUTRALIZED SPECIFICATIONS

1. Product Saron Orbit Leithaltan Sandage 2. Martinecturer Obert Anja 3. Martinecturer (1986)

4 Ingressor At 854 d 854 ce moda te polynier CCF + frag mood SE 272235

THOUSEESHOOTING

▲ WARNING: To reduce the nak of shock and unintended operation, turn off power and remove the battery before servicing.

Vacuum is not picking up depris. No suction or light suction. Third indicator light on hand vacuum is sail diyellow. (Refer to Checking to-Blockeget weet on for more information.)

Business may be full amony destrois.
 Check floor new eithrichtingsgeginger op obleges ill required.
 Roman any strong carbon floor partial may may be wipper a mondifie a usbroit.
 Check to may be recomberet accumulation. To block a experience of the entire recomber.
 Check to an observational degree of the entire of the mondifier of the entire of the original of the original degree of the entire of the entire of the original o

Oramon the area sings.

1. Huberthe your only on a net COst index that, the wholl-december the area of the particle of the control of the cost of the

The brusheal is the Boot nozzle dozen't spin.

Hill mean they for the five and the leave are breaks explaints that in a district count back to a Hake sure the far threath is a that district in a count for the fraction for the region with interest. If the door not the resolution and the case not included the control to door the far threather that a count for which, and we say they are strictly a count of the far the far the far that the far t

Vacuum tu-ns off oir balawn.

vector in turns on a rick ewe. There are seen to possible interest faithful to have in politically two interesting block again. watery switched devented together together the sale of switch position the relieving stees.

It turned the weed mande steek the category theodoright on the national care of the version of the category make sure was our life version of the category make sure was our power is all and place that the category disks.

2. Empty dust cup and clean filters (See the Maintaining Your Vacuum section above.)

Check wand, accessories, and inlet openings and remove any blockages.Allow unit and battery to cool for at least 45 minutes, until they return to room temperature. Press the On/Off switch to restart the vacuum.

Error message Codes					
Kulturction	Component	Error leans phase 1		Error icons phase 2	UED loons
Nextle Clog-or Stalling	Nocole	LED Ring is Risshing Purple		No 180s	LED DETECT
Motor Failure During Startup	Hand Taroum	EID, DETEXT, BOOST 1804 cm	-	BOT, DETECT LEDs on	- Lin
Over-Temperature Protection	Hand Racum	810, DETECT, BOOST LEDs on	-	BOOST, DETECT USEs on	lon long
Over Current protection	Hand Racoum	80,0ETB3T,80067 LBDs on	\leftrightarrow	No ISIs	$X = \emptyset - X$
Short Protection	Hand Taroum	EID, DETECT LEDs on	•	No 180s	
Overspeed Protection	Hand Nacum	DETECT LEDs on	60	801; 8005TLEBs on	(0)
Communication Failure	Hand Rassum	EID, DETECT LEDs on	↔	DETECT, BOOST USEs on	
Over-Temperature Protection	Niczle	E10, 9000\$7 LEDs:	↔	No ISS	D 'x
Short Protection	Nocole	DETECT, BOOST LEDts on	60	No 180s	· ·
Debris Detection Failure	Hand Rassum	F0 150-6 150 Ring on	0-0	No 180s	D Ion
Profession	l/e-	.IDen Efficient hell, tillhen	• •	44102	FXT+F in ious will blink for 8.5 seconds

HCTS the solution in the charge $\rho_{\rm s}$, by equally under the solution of the





К©

Promote compared with the compared to promote the promote compared to the comp

This product uses all thium-lon rechargescle and reprosible batters. When the battery no forcer notice a annigo, michaela ha remevad noro the encuan and cayo educio Hall, none inclor componente causay.

When you like the reclaim is access to be expressed the passed from the whole have so clause securious. proximate virtuals, and in sendin as it. In tions wickle agent, this is for an arise in the trade of its medical action for mentions as it is easier from open corresponding actions to explicate easier for easi and a specifical enging account of a silon at went marginistic sport and up-

or APA Table and a 44-bit real Province Commuter (see an Bardinger range) buy, edited a see that posts to lacycle the castery at the end of its seek! He re-eleiredly seen beind by Sherk 4 ris. In one areas Tis legal op at soort florreson alteremette har var soon ookstasse heer antitree-ka loog on need a consumentary meaning at the legal of

2000 consequent serve the following contribution is a respect to be a server to the framework of the consequences. Ciscar and Canada to feel into the pollector of spant i thiury-for batteries III do protect our andronment. and conserve which a resource by returning the specific filtration conserves at winds that \$10 filter according to the contract of the contrac

SHARK QUICK START GUIDE

Contents for the Shark' PowerDetect" Clean & Empty System

