



Aibo Standard Technology (Shenzhen) Co., Ltd.

101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +(86) 0755 85250797

E-mail: Aibonorm@aibonorm.com

Website: www.Aibonorm.com

FCC TEST REPORT

Report No.....: AB25060094CW02

FCC ID.....: **2AC59-0E926**

IC ID.....: **32474-0E926**

Applicant.....: SHENZHEN LOFREE CULTURE CO., LTD

Address.....: 201-F4,F518 Idea Land,1065 Bao Yuan Road, Shenzhen

Manufacturer.....: SHENZHEN LOFREE CULTURE CO., LTD

Address.....: 201-F4,F518 Idea Land,1065 Bao Yuan Road, Shenzhen

Product Name.....: FLOW 2-68 Triple Mode Low-Profile Mechanical Keyboard

Trade Mark.....: **lofree**

Test Model.....: OE926

Additional Model(s).....: N/A

Standard.....: FCC 47 CFR §1.1310
FCC 47 CFR §2.1093
KDB 447498 D01 General RF Exposure Guidance v06

Date of Receipt.....: 2025.07.03

Date of Issue.....: 2025.07.19

Test Result.....: Pass

Compiled by:
(Printed Name + Signature)

Huaijie Li

Huaijie Li

Supervised by:
(Printed Name + Signature)

Jay Liu

Jay Liu

Approved by:
(Printed Name + Signature)

Mic Cheng

Mic Cheng

Testing Laboratory Name.....: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address.....: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by Aibo. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to Aibo within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

FCC TEST REPORT

Test Report No.: AB25060094FW02	<u>2025.07.19</u> Date of issue
--	------------------------------------

EUT.....	: FLOW 2-68 Triple Mode Low-Profile Mechanical Keyboard
Test Model.....	: OE926
Applicant	: SHENZHEN LOFREE CULTURE CO., LTD
Address.....	: 201-F4,F518 Idea Land,1065 Bao Yuan Road, Shenzhen
Telephone.....	: /
Fax.....	: /
Manufacturer	: SHENZHEN LOFREE CULTURE CO., LTD
Address.....	: 201-F4,F518 Idea Land,1065 Bao Yuan Road, Shenzhen
Telephone.....	: /
Fax.....	: /
Factory	: SHENZHEN LOFREE CULTURE CO., LTD
Address.....	: 201-F4,F518 Idea Land,1065 Bao Yuan Road, Shenzhen
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

REPORT VERSION

Version No.	Issue Date	Description
01	2025.07.19	Initial Issue

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. GENERAL DESCRIPTION OF EUT	5
1.2. DESCRIPTION OF SUPPORT EQUIPMENT	6
1.3. DESCRIPTION OF EXTERNAL I/O	6
1.4. GENERAL DESCRIPTION OF APPLIED STANDARDS	7
1.5. DESCRIPTION OF TEST FACILITY	7
2. RF EXPOSURE EVALUATION	8
2.1 LIMIT	8
2.2 EVALUATION RESULT	9
2.3 CONCLUSION	9

1. GENERAL INFORMATION

1.1. GENERAL DESCRIPTION OF EUT

Product Name:	FLOW 2-68 Triple Mode Low-Profile Mechanical Keyboard	
Trade Mark:	lofree	
Test Model:	OE926	
Additional Model(s):	/	
Model Difference:	/	
Hardware Version:	OE926-VIA-V1	
Software Version:	1	
Power Supply:	DC 3.7V by battery(2000mAh) or DC 5V 1A from AC/DC adapter	
EUT Supports Function: (Provided by the customer)	2.4GHz ISM Bands:	Bluetooth V5. 1
Test Sample(s) Number:	AB25060094-01 (Engineer Sample) AB25060094-02 (Normal Sample)	
Radio Specification Subject to this Report		
Bluetooth Version:	Bluetooth LE	
Frequency Range:	2402MHz~2480MHz	
Modulation Type:	GFSK	
Channel Spacing:	2MHz	
Channel Number(s):	40	
Antenna Type:	PIFA Antenna	
Antenna Gain:	-0.58dBi(Max.)	

1.2. DESCRIPTION OF SUPPORT EQUIPMENT

Description	Manufacturer	Model	Serial Number	Supplied by
AC/DC Adapter	Xiaomi	MDY-11-EX	SA62212LA04358J	Applicant

1.3. DESCRIPTION OF EXTERNAL I/O

I/O Port Description	Quantity	Cable
N/A	N/A	N/A

1.4. GENERAL DESCRIPTION OF APPLIED STANDARDS

The tests were performed according to following standards:

[FCC CFR 47 part1 1.1310](#) - Radio frequency radiation exposure limits.

[FCC CFR 47 part2 2.1093](#) -Radio frequency radiation exposure evaluation: portable devices

[FCC KDB 447498 D01 General RF Exposure Guidance v06](#)-Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

1.5. DESCRIPTION OF TEST FACILITY

Test Lab: Aibo Standard Technology (Shenzhen) Co., Ltd.

Address: 101, Building B, Tuori New Energy Industrial Park, High-tech Park, Tianliao Community, Yutang Street, Guangming District, Shenzhen City, Guangdong Province, China

Tel.: +(86) 0755 85250797

E-mail: Aibonorm@aibonorm.com

Website: www.Aibonorm.com

The test facility is recognized, certified, or accredited by the following organizations:

A2LA-Lab Certificate No.: 7514.01

Aibo Standard Technology (Shenzhen) Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC Accredited Lab.

Designation Number: CN1411

Test Firm Registration Number: 567066

ISED Wireless Device Testing Laboratories

CAB identifier: CN0185

2. RF EXPOSURE EVALUATION

2.1 Limit

According to KDB447498 D01 General RF Exposure Guidance v06 Section 4.3.1 Standalone SAR test exclusion considerations: “Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Test Exclusion Threshold condition, listed below, is satisfied. These test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.²² The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander (see 5) of section 4.1). To qualify for SAR test exclusion, the test separation distances applied must be fully explained and justified by the operating configurations and exposure conditions of the transmitter and applicable host platform requirements, typically in the SAR measurement or SAR analysis report, according to the required published RF exposure KDB procedures. When no other RF exposure testing or reporting is required, a statement of justification and compliance must be included in the equipment approval, in lieu of the SAR report, to qualify for the SAR test exclusion. When required, the device specific conditions described in the other published RF exposure KDB procedures must be satisfied before applying these SAR test exclusion provisions; for example, handheld PTT two-way radios, handsets, laptops & tablets etc.²³ “

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f} \text{ (GHz)}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- f (GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2.2 Evaluation Result

Band/ Mode	f (GHz)	Evaluation Distance (mm)	RF Output Power (dBm)	Tolerance (dBm)	Max Tune-up Power(dBm)	Max. Tune-up Power(mW)	Calc. thresholds	SAR Test Exclusion Threshold
BLE	2440	5	3.04	3(±1)	4	2.51	0.7847384	3.0

Mode	Frequency (MHz)	Power (dBuV/m)	Power (dBm)	Power (mW)	Calc. thresholds	SAR Test Exclusion Threshold
2.4G	2438	85.91	-9.29	0.117760597	0.0367745	3.0

Notes: 86.91dBuV/m-95.2=-9.29dBm

2.3 Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01 v06. No SAR test is required.

*****THE END*****