



 213026
OTM05-10PS-T3
Retroreflective diffuse sensor

- Extremely small design
- Red light
- Scanning range preset
- Stainless steel housing
- Can be installed countersunk
- Large temperature range



BK: black

BN: brown

BU: blue

Function



Technical data (typ.)

+20°C, 24 V DC

Service voltage	10 ... 30 V DC
No-load current (max.)	15 mA
Inverse polarity protection	Yes
Thread	M5 x 0,5
Housing material	Stainless steel (V2A)
Material	Plastic (Window / optics)
Weight	4 g
Protection class	III, operation on protective low voltage
Operating principle	Retroreflective diffuse sensor
Evaluation	digital
Design	Thread
Switching output	pnp, 100 mA, NO
Voltage drop (max.)	2 V
Light source	LED
Color	red
Wavelength	630 nm
Light spot size	5 x 6 mm (at distance of 10 mm)
Scanning range	10 mm
Standardized measuring plate	200 x 200 mm (white)
Sensitivity adjustment	no setting elements

**213026****OTM05-10PS-T3****Retroreflective diffuse sensor****Technical data (typ.)****+20°C, 24 V DC**

Display

LED yellow - Switching output

Switching frequency

1.000 Hz

Ambient temperature during operation

-25 ... +65 °C

Protection type

IP 67

Connection

Connector, M8, 3-pin

More information / accessories<https://www.di-soric.com/213026>