

UBX-M10050-KB

u-blox M10 standard precision GNSS chip

Ultra-low power GNSS receiver for high-performance asset tracking applications

- Less than 15 mW power consumption without compromising GNSS performance
- Maximum position availability with concurrent reception of 4 GNSS
- Proven excellent performance, even with small antennas
- Advanced spoofing and jamming detection



Standard



Professional



Automotive

Small QFN28 package
4.0 x 4.0 x 0.55 mm



Product description

The UBX-M10050-KB chip, which is part of the u-blox M10 standard precision GNSS platform, provides exceptional sensitivity and acquisition times for all L1 GNSS systems.

The extremely low power consumption of <15 mW in continuous tracking mode allows great power autonomy for all battery operated devices, such as asset trackers, without compromising on GNSS performance.

UBX-M10050-KB supports concurrent reception of four GNSS (GPS, GLONASS, Galileo, and BeiDou). The high number of visible satellites enables the receiver to select the best signals. This maximizes the position availability, in particular under challenging conditions such as in deep urban canyons.

u-blox Super-S (Super-Signal) technology offers great RF sensitivity and can improve the dynamic position accuracy by up to 25% with small antennas or in a non-line-of-sight scenario.

UBX-M10050-KB detects jamming and spoofing events and reports them to the host, so that the system can react to such events. Advanced filtering algorithms mitigate the impact of RF interference and jamming, thus enabling the product to operate as intended.

UBX-M10050-KB chips are qualified according to AEC-Q100, manufactured in IATF 16949 certified sites, and are fully tested on a system level.

UBX-M10050-KB

Grade	
Automotive	
Professional	•
Standard	
GNSS	
GPS + QZSS/SBAS	•
GLONASS	•
Galileo	•
BeiDou	•
Number of concurrent GNSS	4
Interfaces	
UART	1
SPI	1
DDC (I2C compliant)	1
Features	
RTC crystal	S
Oscillator	C/T
Antenna supervisor	S
Timepulse	1

S = supported, may require ext. components
C/T = Crystal and TCXO supported

Product performance

Receiver type	u-blox M10 engine GPS L1 C/A, QZSS L1 C/A/S, GLONASS L10F, BeiDou B1I/B1C, Galileo E1B/C, SBAS L1 C/A: WAAS, EGNOS, MSAS, GAGAN	
Nav. update rate	Up to 10 Hz (4 concurrent GNSS)	
Horizontal position accuracy ¹	1.5 m CEP	
Acquisition ¹	Cold start	24 s
	Aided start	2 s
	Hot start	1 s
Sensitivity ¹	Tracking & Nav.	-167 dBm
	Reacquisition	-161 dBm
	Cold start	-148 dBm
	Hot start	-159 dBm

1 = For default mode: GPS/BDS/GAL+SBAS/QZSS

External components

Oscillator	Crystal or TCXO
RTC input (optional)	32.768 kHz
Antenna supply & supervisor	External circuit required for short and open circuit detection
Flash memory (optional)	SPI interface (cannot be used to upgrade firmware)

Tracking features

u-blox Super-S	Improved accuracy with small antennas
Data batching	Autonomous tracking up to 10 min at 1 Hz
Odometer	Measure traveled distance with support for different user profiles

Security features

Signal integrity	RF interference & jamming detection and reporting Active GNSS in-band filtering Spoofing detection and reporting
Device integrity	Receiver configuration lock by command
Secure interface	Signed UBX messages (SHA-256) JTAG debug interface disabled by default

Package

28 pin QFN: 4.0 x 4.0 x 0.55 mm

Environmental data, quality & reliability

Operating temp.	-40°C to +85°C
Storage temp.	-40 °C to +125 °C
MSL	1
Environmental grade	2015/863/EU RoHS-3, Green, IEC-61249-2-21 halogen-free
Environmental testing	AEC-Q100
Quality management	Manufactured and fully tested in IATF 16949 certified production sites

Electrical data

Supply voltage	1.0 V to 1.8 V
Digital I/O voltage	1.8 V or 3.3 V
Power consumption ²	3 GNSS: 13 mW
	4 GNSS: 18 mW
Backup supply	1.65 V to 3.6 V

2 = Supply voltage 1.0 V, digital I/O voltage 1.8 V

Interfaces

Serial interfaces	1 UART 1 DDC (I2C compliant) 1 SPI
Digital I/O	1 configurable time pulse 1 EXTINT interrupt input
Raw data output	Code phase data
Memory	SPI interface for optional Flash
Protocols	NMEA 4.10, UBX binary

Services

Assisted GNSS	AssistNow GNSS Online: Data valid 2-4 hours AssistNow GNSS Offline: Data valid up to 35 days AssistNow Autonomous: Data valid up to 6 days
---------------	--

Support products

EVK-M101	u-blox M10 GNSS evaluation kit with UBX-M10050 chip and I/O interface
u-center	Highly interactive and easy-to-use GNSS evaluation software

Product variants

UBX-M10050-KB	u-blox M10 GNSS chip, 28 pin QFN
---------------	----------------------------------

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the product data sheet.

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.