

# Eaton 144060

Catalog Number: 144060

Eaton EU5E SWD input card, 24 V DC, 4 digital inputs with 24 V power supply, 0.5A, 3 conductor connection



### General specifications

Product Name	Catalog Number
Eaton EU5E I/O module	144060
EAN	Product Length/Depth
4015081405909	102 mm
Product Height	Product Width
90 mm	35 mm
Product Weight	Certifications
0.09 kg	UL File No.: E29184
	UL
	UL Category Control No.: NKCR
	CSA File No.: 2324643
	IEC/EN 61131-2
	CSA
	CSA Class No.: 3211-07

### Catalog Notes

Inputs with supply for sensor system.

## Features & Functions

### Electric connection type

Flat plug-in connection

### Features

Fieldbus connection over separate bus coupler possible

### Functions

For connection of digital I/O signals

## General

### Current consumption

33 mA, SmartWire-DT network

### Degree of protection

IP20

### Mounting method

Wall mounting/direct mounting

Top-hat rail fixing (according to IEC/EN 60715, 35 mm)

Rail mounting possible

### Overvoltage category

II

### Pollution degree

2

### Product category

SmartWire-DT slave

### Residual ripple

≤ 5 % (input voltage)

### Terminal capacity

0.25 - 1.5 mm<sup>2</sup> (24 - 16 AWG), flexible with ferrule, Terminal for I/O sensor

0.2 - 1.5 mm<sup>2</sup> (AWG 24 - 16), solid, Terminal for I/O sensor

### Type

Digital modules

### Voltage type

DC

## Ambient conditions, mechanical

### Constant acceleration

1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations

### Constant amplitude

3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations

### Drop and topple

50 mm Drop height, Drop to IEC/EN 60068-2-31

### Height of fall (IEC/EN 60068-2-32) - max

0.3 m

### Mounting position

As required

## Climatic environmental conditions

### Air pressure

795 - 1080 hPa (operation)

### Ambient operating temperature - min

-25 °C

### Ambient operating temperature - max

55 °C

### Ambient storage temperature - min

-40 °C

### Ambient storage temperature - max

70 °C

#### Shock resistance

15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts

#### Climatic proofing

Dry heat to IEC 60068-2-2

Damp heat, constant, to IEC 60068-2-3

#### Environmental conditions

Condensation: prevent with appropriate measures

#### Operating temperature - min

-25 °C

#### Operating temperature - max

55 °C

#### Relative humidity

5 - 95 % (non-condensing, IEC/EN 60068-2-30)

### Electro magnetic compatibility

#### Air discharge

8 kV, according to IEC 61131-2, level 3, ESD

#### Burst impulse

2 kV, Supply cable, according to IEC/EN 61131-2, Level 3

1 kV, SmartWire-DT cable, according to IEC/EN 61131-2, Level 3

1 kV, Signal cable, according to IEC/EN 61131-2, Level 3

#### Contact discharge

4 kV, according to IEC/EN 61131-2, Level 2, ESD

#### Electromagnetic fields

1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008)

10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008)

3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008)

#### Radiated RFI

10 V (IEC/EN 61131-2:2008, Level 3)

#### Radio interference class

Class A (EN 55011)

#### Surge rating

0.5 kV, Surge power cables, Surge (IEC/EN 61131-2:2008, Level 1), EMC

1 kV, Surge I/O cables, Surge (IEC/EN 61131-2:2008, Level 1), EMC

### Electrical rating

#### Input current at signal 1

4 mA

#### Output current

0 A

#### Power loss

1.1 W

#### Rated operational voltage

24 V DC (-15 %/+ 20 % - power supply)

#### Supply voltage at AC, 50 Hz - min

0 VAC

#### Supply voltage at AC, 50 Hz - max

0 VAC

#### Supply voltage at DC - min

0 VDC

#### Supply voltage at DC - max

28.8 VDC

### Communication

#### Connection to SmartWire-DT

Yes

#### Connection type

Plug, 8-pole, SmartWire-DT

Connection plug: external device plug SWD4-8SF2-5, SmartWire-DT

Push in terminals, Supply and I/O sensor

#### Data transfer rate

Setting automatically

250 kBit/s, SmartWire-DT

#### LED indicator

Status indication of SmartWire-DT network: Green LED

#### Protocol

Other bus systems

#### Station

SmartWire-DT slave, SmartWire-DT network

## Input/Output

Number of inputs (digital)

4

Number of outputs (digital)

0

## Safety

Explosion safety category for dust

None

Explosion safety category for gas

None

Potential isolation

Outputs to SmartWire-DT: yes

Inputs for SmartWire-DT: yes

Protection against polarity reversal

Yes

Yes, for supply voltage (Siemens MPI optional)

## Design verification

Equipment heat dissipation, current-dependent  $P_{vid}$

0 W

Heat dissipation capacity  $P_{diss}$

0 W

Heat dissipation per pole, current-dependent  $P_{vid}$

0 W

Rated operational current for specified heat dissipation ( $I_n$ )

0 A

Static heat dissipation, non-current-dependent  $P_{vs}$

1.1 W

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

#### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

#### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

## Resources

### Brochures

[eaton-smartwire-dt-intelligent-wiring-brochure-br120001en-en-us.pdf](#)

### Catalogs

[Product Range Catalog Drives Engineering](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[SmartWire-DT Catalog](#)

### Declarations of conformity

[DA-DC-00003867.pdf](#)

[DA-DC-00003540.pdf](#)

### Drawings

[eaton-modular-plc-eu5e-i-o-module-dimensions.eps](#)

[eaton-modular-plc-eu5e-i-o-module-dimensions-002.eps](#)

[eaton-general-easy-control-relays-symbol-002.tif](#)

[eaton-general-approval-easy-control-relays-standards.jpg](#)

[eaton-general-eu5e-i-o-module-symbol.eps](#)

[eaton-modular-plc-swd-eu5e-i-o-module-3d-drawing.eps](#)

#### [10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects](#)

Meets the product standard's requirements.

#### [10.2.4 Resistance to ultra-violet \(UV\) radiation](#)

Meets the product standard's requirements.

#### [10.2.5 Lifting](#)

Does not apply, since the entire switchgear needs to be evaluated.

#### [10.2.6 Mechanical impact](#)

Does not apply, since the entire switchgear needs to be evaluated.

#### [10.2.7 Inscriptions](#)

Meets the product standard's requirements.

#### [10.3 Degree of protection of assemblies](#)

Meets the product standard's requirements.

#### [10.4 Clearances and creepage distances](#)

Meets the product standard's requirements.

#### [10.5 Protection against electric shock](#)

Does not apply, since the entire switchgear needs to be evaluated.

#### [10.6 Incorporation of switching devices and components](#)

Does not apply, since the entire switchgear needs to be evaluated.

#### [10.7 Internal electrical circuits and connections](#)

Is the panel builder's responsibility.

#### [10.8 Connections for external conductors](#)

Is the panel builder's responsibility.

#### [10.9.2 Power-frequency electric strength](#)

Is the panel builder's responsibility.

#### [10.9.3 Impulse withstand voltage](#)

Is the panel builder's responsibility.

#### [10.9.4 Testing of enclosures made of insulating material](#)

Is the panel builder's responsibility.

#### [10.10 Temperature rise](#)

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### [10.11 Short-circuit rating](#)

Is the panel builder's responsibility.

#### [eCAD model](#)

[DA-CE-ETN.EU5E-SWD-4DX](#)

#### [Installation instructions](#)

[IL05006002Z](#)

#### [Installation videos](#)

[SmartWire-DT in Application](#)

#### [Manuals and user guides](#)

[MN05006002Z\\_EN](#)

[MN05006001Z\\_EN](#)

#### [mCAD model](#)

[eaton-eu5e\\_swd\\_4dx-drawing.dwg](#)

[eaton-eu5e\\_swd\\_4dx-3d-model.stp](#)

[DA-CS-eu5e\\_swd\\_1](#)

[DA-CD-eu5e\\_swd\\_1](#)

#### [Multimedia](#)

[How to process SmartWire-DT modules using the EASY-COM-SWD-C1 module connected to an easyE4?](#)

[SmartWire-DT Overview and how to use in easySoft 7](#)

[easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator](#)

#### [Sales notes](#)

[eaton-electro-hydraulic-module-eu1h-flyer-fl120003en-en-us.pdf](#)

[eaton-rmq-chemical-resistance-flyer-fl047011en-en-us.pdf](#)

#### [Wiring diagrams](#)

[eaton-modular-plc-power-supply-eu5e-i-o-module-wiring-diagram.eps](#)

10.12 Electromagnetic compatibility

Is the panel builder's responsibility.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.  
  
All other trademarks are property of their respective owners.



Eaton.com/socialmedia