

Universal Condenser		Model	
SPECIFICATIONS	UNIT	GUD36W/A-D(U)	GUD60W/A-D(U)
Cooling Capacity	Btu/h	34000	54000
Cooling Capacity Range	Btu/h	18000-37000	35000-55000
Heating Capacity	Btu/h	35000	54000
Heating Capacity Range	Btu/h	18000-38000	35000-60000
EER	(Btu/h)/W	10.00	10.50
COP	(Btu/h)/W	10.57	11.80
SEER	—	16.00	17.00
HSPF	—	9.00	10.00
Air Flow Volume	CFM	3470	4700
Sound Pressure Level (H)	dB(A)	60	58
Rated Voltage	V	208/230	208/230
Rated Frequency	Hz	60	60
Phases	—	1	1
Min/Max. Voltage	V	187/253	187/253
Max. Over Current Protection	A	35	45
Min. Current (MCA)	A	24	35
Net Dimension (WxDxH)	inch	37.01 x 18.11 x 32.28	39.37 x 14.57 x 53.74
Package Dimension (WxDxH)	inch	42.64 x 22.56 x 38.31	45.39 x 19.41 x 59.25
Net Weight	lb	217.2	308.7
Gross Weight	lb	240.3	337.4
Connection Pipe Connection Method		Quick connect, braze or flare	Quick connect, braze or flare
Refrigerant Type		R-410A	R-410A
Warranty Coverage		10-year warranty on parts and a 10-year warranty on the compressor	

Air Handler		Model	
SPECIFICATIONS	UNIT	GUD36AH2/A-D(U)	GUD60AH2/A-D(U)
Air Flow Volume	CFM	1000	1500
Sound Pressure Level	dB(A)	47	51
Rated Voltage	V	208/230	208/230
Rated Frequency	Hz	60	60
Phases	—	1	1
Min/Max Voltage	V	187/253	187/253
Max. Overcurrent Protection	A	15	15
System Operation Control		Wired controller	Wired controller
Net Dimension (WxDxH)		21.26 x 21.26 x 48.19	24.80 x 21.26 x 57.01
Package Dimension (WxDxH)		25.98 x 23.74 x 50.39	27.28 x 25.98 x 59.37
Net Weight	lb	156.5	203.0
Gross Weight	lb	169.8	218.0
Refrigerant		R410A	R410A



Data from GREE LABOTARY