

Application

This luminaire is designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space.

Materials

- Hand-blown opal glass
- Aluminum housing
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 5.5 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	28.1 W
System wattage	33.0 W
Controllability	DALI-2
Color rendering index	Ra > 90
Luminaire lumens	2109lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

Dynamic range

Tunable white color temperature range is adjustable from 2700K to 6500K

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)

Type:


BEGA Product:

Project:

Modified:

Available options

- CP50291 Ceiling Pan (DALI-2 controlled)



Recessed ceiling luminaire · Opal glass · Tunable white				
		LED	A	B
B50291	ADA	28.1 W	13 ³ / ₈	2 ³ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805)684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2025 Updated 07/11/25

