

# GUH/GDD96C

## Accessories

### SINGLE-STAGE CONSTANT TORQUE GAS FURNACE

96% AFUE



#### California Only

*This furnace does not meet the South Coast Air Quality Management District (SCAQMD) Rule 1111 and San Joaquin Valley Air Pollution Control District (SJVAPCD) Rule 4905 NOx emission limit (14 ng/J) and cannot be installed within the SCAQMD or SJVAPCD and Bay Area.*

#### ACCESSORY LIST

PART NUMBER	DESCRIPTION
<b>External Filter Rack kits</b>	
1.841018	1 pack (16 x 25)
1.841039	10 pack (16 x 25)
<b>Natural to LP Kits</b>	
11K50	1-Stage GUH/GDD96C
11K45	High Altitude 1-Stage > 7500ft
17H62	30K BTUH
<b>High Altitude Pressure Switch Kits</b>	
11U66	4,501 - 7,500 ft [030, 045]
11U70	4,501 - 7,500 ft [070, 090, 110]
11U69	7,501 - 10,000 ft [030, 045]
11U68	7,501 - 10,000 ft [070]
11U64	7,501 - 10,000 ft [090, 110]
<b>Return Air Base</b>	
68W62	17.5" B Width
68W63	21.0" C Width
68W64	24.5" D Width
<b>Downflow Combustible Flooring Base</b>	
11M60	17.5" B Width
11M61	21.0" C Width
<b>Horizontal Suspension Kit</b>	
51W10	80% & 90% Kit
<b>Flush Mount Termination (90% Furnaces only) US Only</b>	
51W11	2" & 3" Vent Version
<b>Concentric Vent Kit (90% Furnaces only) US Only</b>	
71M80	1-1/2" Vent Version
69M29	2" Vent Version
60L46	3" Vent Version
<b>Concentric Vent Kit (90% Furnaces only) Canada</b>	
44W92	1-1/2" and 2" Vent Version
44W93	3" Vent Version
<b>Twinning Kit</b>	
27J32	Recommended when furnace is used with zoning or defrost thermostats and other 24V accessories requiring a higher VA rating
	Circuit breaker (furnished) is wired in series
	Replaces the standard 40VA transformer

For vent length and clearances to combustibles, please reference installation instructions.

*Comfort-Cire®*

#### Warranty

Standard warranty or Extended warranty available with product registration. See warranty document for details or visit [www.marsdelivers.com](http://www.marsdelivers.com)