

QWCd Slimline

Quantum, the world's most advanced direct-electric hot water cylinder

Controls

Electronic thermostatic control with internet-connected smartphone app connectivity for remote operation (a DimplexHub is required)

Safety Features

- Manual reset thermal cut-out
- Legionella purge

Colour/Finish

Black.

Element

1 ¾" M BSP 3kW immersion and boost element.

Supply

1/N/PE 230-240V, 50Hz (Peak/Off Peak).


Guarantee

- Inner cylinder - 25 year UK manufacturer Guarantee on parts and labour
- Immersion heaters - 2 year UK manufacturer Guarantee (excluding the effects of limescale)
- Other components - 2 year UK manufacturer Guarantee (excluding the effects of limescale)

IP Rating

IPX1

Product Dimensions



Dimplex Control
See page 10
for details

Model	Capacity (L)	Height (mm)	Diameter (mm)	Weight (kg)	Reheat (mins)
QWCd135-480RF	135	1387	480	22	132
QWCd180-480RF	180	1761	480	30	200

ECsd Direct Water Cylinder

EC Unvented Stainless Steel Direct Hot Water Cylinders

Controls

Mechanical thermostat control.

Safety Features

Manual reset thermal cut-out.

Colour/Finish

Black.

Element

Electronic thermostat control.

Supply

1 ¾" M BSP 3kW immersion and boost element.


Guarantee

- Inner cylinder - 25 year UK manufacturer Guarantee on parts and labour
- Immersion heaters - 2 year UK manufacturer Guarantee (excluding the effects of limescale)
- Other components - 2 year UK manufacturer Guarantee

IP Rating

IPX1

Product Dimensions



Model	Capacity (L)	Height (mm)	Diameter (mm)	Weight (kg)	Reheat (mins)
ECsd100-580	100	795	580	20	88
ECsd125-580	125	945	580	23	122
ECsd150-580	150	1115	580	27	150
ECsd175-580	175	1265	580	29	170
ECsd210-580	210	1490	580	34	218
ECsd250-580	250	1765	580	42	284
ECsd300-580	300	2065	580	48	313