

MTPX-MF V3

MIFARE RFID READER

MTPX-MF is a Mifare reader with a polycarbonate front plate, available in a ABS housing in silver or black. It is elegant, slim and compact and its design is suitable for inside and outside use. MTPX-MF is compatible with most access controllers and time & attendance systems. It incorporates industry standard protocols such as Wiegand 24, 26, 32, 34, 40, 42, 56, 58 bit.

FEATURES

- Mifare Card Serial Number Reader
- Resin Potted Electronics
- Distance Read range up to 6 cm
- Configurable WIEGAND output 24, 26, 32, 34, 40, 42, 56, 58 bit
- 13.56 MHz operation
- Reads Mifare Classic CSN, Ultralight and Desfire
- ABS housing
- Colours: Silver and Black

FOBS & CARDS




Ref.	PBX-1E-MS50	PBX-2-MS50	PBX-2C-MS50
Features	ABS Keyfob 13.56MHz	0.75mm ISO Card - 13.56MHz	2mm NISO Card - 13.56MHz

COLOURS



MTPXS-MF
Silver - ABS



MTPXBK-MF
Black - ABS



Black Edition

Product available in Black ABS

SPECIFICATIONS

Electrical Characteristics:

Operating Voltage:	9 to 14V DC
Current consumption:	Maximum 130 mA
Operating frequency:	13.56 MHz
Read range:	Up to 6 cm
Backlight control:	Red, green, orange controlled by master device
Audible Signal:	1 Internal buzzer

Environmental Characteristics:

Operating Temperatures:	-20°C to +60°C
Operating Humidity:	0 to 95% (non-condensing)
Protection standard:	IP65

Mechanical Characteristics:

Dimensions (mm)	51 L x 92 H x 27 W
-----------------	--------------------

DIMENSIONS

