



# SmartBright All-inone Solar Street Light

## BRP110 LED180/757 G2

Integrated solar street light with Lithium Ferro Phosphate battery, solar panel and charger built into the luminaire. Independently tilt-able LED source and pole mounting bracket allows light beam to focus on road, and solar panel towards the sun. Microwave based motion sensor for optimizing battery autonomy.

#### **Product data**

General information	
Driver included	Yes
Optical cover/lens type	Polycarbonate
Control interface	IR remote
Cable	-
Material	Aluminum
EU RoHS compliant	Yes
Operating and electrical	
Battery type	Lithium Ferro Phosphate
Battery ampere hour	30 Ah
Battery voltage	25.6 V
Battery charging & discharging cycles	2000
Panel type	Mono crystalline
Panel voltage	34.5 V
Panel peak wattage	125 W
Charge controller type	MPPT
Controls and dimming	
Dimmable	Yes

Configurability	Configurable
Mechanical and housing	
Overall length	1320 mm
Overall width	525 mm
Overall height	161 mm
Color	RAL7040
Approval and application	
Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 6 J]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	18000 lm
Initial LED luminaire efficacy	195 lm/W
Init. Corr. Color Temperature	5700 K
Init. Color Rendering Index	>70

Datasheet, 2023, March 11 data subject to change


## SmartBright All-in-one Solar Street Light

Over time performance (IEC complia	ant)
Median useful life L70B50	50000 h
Application conditions	
Ambient temperature range	0 to +50 °C
Ambient temperature range for charging	0 to +50 °C
Ambient temperature range for	-10 to +600C
discharging (when light is on)	
Autonomy	2 h
Solar dimming profile	First 2 Hrs - On motion : 100%, without
	motion :30%; Next 3 Hrs - On motion : 60%,
	without motion :20%; Next 6 Hrs On motion :
	30%, without motion :10%; Rest of the Night:
	On motion : 50%, without motion :30%
Grid connection type	Off grid

Battery location	Inbuilt	
Product data		
Full product code	692382865730700	
Order product name	BRP110 LED180/757 G2	
EAN/UPC - Product	6923828657307	
Order code	911401834202	
Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	1	
Material Nr. (12NC)	911401834202	
Net Weight (Piece)	30.990 kg	



### Dimensional drawing



#### BRP110 LED180/757 G2



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.