


Submittal Data: SC-36CD-UM / SC-36Z-UM

36000 BTUH Slim Duct Heat Pump System

Job Name		Location	Date
Purchaser		Engineer	
Submitted To		For	☐ Reference ☐ Approval ☐ Construction
Unit Designation		Schedule No.	
GENERAL FEATURES -Multi-Speed Fan -Medium Static Pressure Capability -Return Air From Rear Only -Internal Condensate Drain Pump -Sentry Condensate Overflow Protection -Wired Remote Controllers -Acrylic Resin/Anti-Corrosion Fin Coating			
System Ratings		Indoor Unit Data	
Cooling		Fan Motor	Output Power 249 W
Rated Capacity	34000 BTU/H		FLA 2.1 A
Capacity Range	10800-39000 BTU/H	Airflow	
Power Input (Max)	4500 W	Cooling Wet (Lo/Hi)	950/1175 CFM
SEER	16.0	Heating Dry (Lo/Hi)	950/1175 CFM
EER	10.4	Sound Power Level	
Heating at 47° F		Cooling (Min/Max)	44/52 dB(A)
Rated Capacity	41000 BTU/H	Heating (Min/Max)	44/52 dB(A)
Capacity Range	9800-49500 BTU/H	Dehumidification	1.28 pt/hr
Power Input (Max)	4600 W	Condensate Drain Lift (Height)	33-in
HSPF	9.0	Power Supply (Dedicated Circuit: Size Per Local Code)	
COP	3.2	Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz
Heating at 17° F		Voltage Range	187 - 253 V
Rated Capacity	24600 BTU/H	MCA	3 A
Operating Range		MOCB/Breaker Size	15A
Cooling	(Max) 118°F (48°C)	Communication Wire Size	18-2 AWG / 300V THHN
	(Min) 0°F (-18°C)	Outdoor Unit Data	
Heating	(Max) 75°F (24°C)	Compressor	DC Inverter Driven Rotary
	(Min) 0°F (-18°C)	RLA	21.2 A
Refrigerant Piping Data		Refrigerant Type	R410A
Gas Pipe Size (OD)	5/8-in	Fan Motor	Output Power 2/9HP
Liquid Pipe Size (OD)	3/8-in		FLA 2.0 A
Connection Method	Flared	Sound Power Level	
Factory Charge	123.2 oz	Cooling/Heating	63/63 dB(A)
Additional Charge	0.6 oz/ft	Power Supply (Dedicated Circuit)	
Pre-Charge Length	25-ft	Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz
MAX Refrigerant Pipe Length	164-ft	Voltage Range	187 - 253 V
MIN Refrigerant Pipe Length	10-ft	Main Supply Wire Size	8 AWG
MAX Refrigerant Pipe Elevation	49-ft	MCA	27.7 A
		MOCB/Breaker Size	45 A


SYSTEM FEATURES

Inverter Type	G10
Ultra Low Frequency Torque Control	YES
Power Factor Correction	YES
Compressor Type	Rotary
Refrigerant Type	R410A
Basepan With Electric Heater	YES
Compressor With Electric Heater	NO
Outdoor Fin Coating	Acrylic Resin
Intelligent Defrosting	YES
Intelligent Preheating	YES
Low Voltage Startup	YES
Memory/Power Failure Recovery	YES
Self Diagnosis	YES
Low Ambient Cooling	YES
Internal Condensate Pump	YES
XK60 Wired Controller Interface	YES
Wi-Fi Interface	NO
Indoor Fan Type	Centrifugal
Multi Fan Speeds	3 Speeds
LED Display Indoor Unit	NO
Advance Filter	NO
Auxiliary Electrical Heater	NO
Ventilation (Outdoor Air)	Optional

WIRED CONTROLLER FUNCTIONS


Auto Mode	YES
Auto Fan	YES
Auto Swing (Continuous Sweep)	NO
Adjustable Swing Louvers (5 pos.)	NO
Clock on Remote Controller	YES
Dry Mode	YES
Dry Anti-Mildew (X-Fan) Mode	YES
Energy Saving Mode	NO
Dirty Filter Alert	NO
I Feel Function	YES
Lock on Wired Controller	YES
Quiet Mode	NO
Room Temperature Display (5 sec.)	YES
Sleep Mode	YES
Timer Mode	YES
Turbo Mode	YES
Display On/Off Control	NO
Freeze Guard Mode	YES

FAN PERFORMANCE CURVES




EXTENDED RATINGS

COOLING PERFORMANCE




HEATING PERFORMANCE



MINIMUM SPACING REQUIREMENTS


Units: inch (mm)

INDOOR



Units: inch (mm)

OUTDOOR




DIMENSIONAL SPECIFICATIONS

SC-36CD-UM

INDOOR UNIT DIMENSIONS & WEIGHTS

Units: inch (mm)



Notes:

1. Size refrigerant lines based on evaporator port sizes.
2. Refrigerant and Drain pipe configurations vary by unit size.
3. Pump Drain outlet is above gravity drain outlet.


A	39.75	(1011)
B	29.5	(748)
C	32.25	(820)
D	43.875	(1115)
E	48.25	(1226)
F	30.5	(775)
G	38.5	(979)
H	6.25	(160)
I	9.125	(231)
J	11.375	(290)

Net Weight	101.2' lbs
Shipping Weight	116.6 lbs

Liquid Line Valve	3/8-in OD Flared
Gas Line Valve	5/8-in OD Flared
Drain Connector	13/16 in OD

OUTDOOR UNIT DIMENSIONS & WEIGHTS

Units: inch (mm)



A	43.625	(1107)
B	17.375	(440)
C	43.25	(1100)
D	24.875	(631)
E	15.75	(400)

Net Weight	204.6 lbs
Shipping Weight	222.2 lbs

Liquid Line Valve	3/8-in OD Flared
Gas Line Valve	5/8-in OD Flared

Notes:

1. Recommended Communication WireType 18-2 AWG Stranded Copper THHN 300V Wire
2. Power wiring size must comply with applicable national and local codes for both ID and OD dedicated circuits.
3. Test conditions are based on AHRI 210/240.

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All rights reserved.