

ZW350

Compact high brightness laser projector









- Bright WXGA DuraCore laser projector
- Easy installation 1.3x zoom, 360-degree and portrait projection
- Ultimate control Crestron, Extron, AMX, PJ-Link and Telnet LAN commands
- DuraCore laser technology 30,000 hours maintenance-free laser light source



The ZW350 is a compact WXGA DuraCore IP6X laser projector. Designed for maintenance-free continuous operation, it can be installed in virtually any orientation. Its small and lightweight footprint and 1.3x zoom combined with 360-degree and portrait projection make it easy to install

This feature-packed projector has a built-in speaker and its laser technology delivers up to 30,000 hours of maintenance-free laser light source. For ultimate control, it comes with an RJ45 connection for monitoring and controlling a network across multiple rooms.



Specifications

 Resolution
 WXGA (1280x800)

 Brightness
 3,500 lumens

 Contrast ratio
 3,00,000:1

 Native aspect ratio
 16:10

 Aspect ratio - compatible
 43,16:9,16:10

 Keystone correction - vertical
 +/-40°

 Displayable colours (millions)
 1073.4

 Horizontal scan rate
 15.375 ~ 91.146 Khz

 Vertical scan rate
 50 ~ 85 Hz (120Hz for 3D)Hz

Uniformity 75%

Screen size 0.76m ~ 7.62m (30" ~ 300") diagonal

Lamp info
Light source type

Laser 30,000 hours

Optical
Throw ratio
Projection distance

1.187:1 ~ 1.544:1 1.1m - 7.7m 1.3 Manual 16.901 ~ 21.6076

Focal length 16.90 Native offset 113%

Connectivity

Connections Inputs 2 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 1

x Audio 3.5mm

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A **Control** 1 x RS232, 1 x RJ45, 1 x micro USB service

General

Zoom

Zoom type

Noise level (typical) 27dB Noise level (max) 32dB

PC compatibility WUXGA,1080P,UXGA, SXGA+,SXGA

,WXGA+,WXGA,720P,XGA,SVGA,VGA

2D compatibilityNTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack;

3D compatibilitySide-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

3D Full 3

Security Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operationYes360° operationYes

Operating conditions 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Speaker count 1 Watts per speaker 15W

In the box

AC power cord
Remote control

Remote control Basic user manual

Networking LAN - control

LAN - control Yes
Power

Power supply $100V \sim 240V$, 50-60Hz Power consumption (standby) <0.5W

Power consumption (standay) <0.5W
Power consumption (min) 138W
Power consumption (max) 161W

Weight and dimensions

 Dimensions (W x D x H)
 337 x 265 x 122.5

 Gross weight
 4.2 kg

 Net weight
 3 kg





