




20 Amp Power Control Relays


RIB2401B

Enclosed Relay 20 Amp SPDT with
24 Vac/dc/120 Vac Coil



RIB2402B

Enclosed Relay 20 Amp SPDT with
24 Vac/dc/208-277 Vac Coil



SPECIFICATIONS

Relays & Contact Type: One (1) SPDT Continuous Duty Coil
Expected Relay Life: 10 million cycles minimum mechanical
Operating Temperature: -30 to 140° F
Operate Time: 18mS
Relay Status: LED On = Activated
Dimensions: 2.30" x 3.20" x 1.80" with .50" NPT Nipple
Wires: 16", 600V Rated
Approvals: UL Listed, UL916, UL864, C-UL
California State Fire Marshal, CE, RoHS
Housing Rating: Plenum, NEMA 1
Gold Flash: No
Override Switch: No

Contact Ratings:

20 Amp Resistive @ 277 Vac
5 Amp Resistive @ 480 Vac
20 Amp Ballast N/O @ 277 Vac
10 Amp Ballast N/C @ 277 Vac
10 Amp Tungsten N/O @ 120 Vac
770 VA Pilot Duty @ 120 Vac
1,110 VA Pilot Duty @ 277 Vac
2 HP @ 277 Vac
1 HP @ 120 Vac

Coil Current:

50 mA @ 18 Vac
83 mA @ 24 Vac
47 mA @ 120 Vac (RIB2401B)
69 mA @ 208-277 Vac (RIB2402B)

Coil Voltage Input:

24 Vac/dc ; 120 Vac ; 50-60 Hz (RIB2401B)
24 Vac/dc ; 208-277 Vac ; 50-60 Hz (RIB2402B)
Drop Out = 2.1 Vac / 3.8 Vdc
Pull In = 18 Vac / 22 Vdc

Notes