

## **Neutrik TRUE1 2+PE powerCON Connector (Male)**

NT-NAC3M-TRUE1-S - Specifications

#### Description

This connector replaces appliance couplers wherever a very rugged solution in combination with a locking device is needed in order to guarantee a safe power connection. The powerCON TRUE1 is a connector series with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.

#### Features:

- · Heavy duty sealed power connector for harsh and demanding environment
- Uses high impact UV-resistant materials
- Lockable single phase connector
- Unique NEUTRIK locking bushing and strain relief for cable diameters 6 mm to 12 mm (0.23 0.47 inches)
- · Extremely robust and reliable
- ENEC and VDE certified according to IEC 60320-1 and EN IEC 60320-1
- UL and CSA Certified According to UL 60320-1 and CSA 22.2 No. 60320-1
- UL Certified According to UL 498
- · IP65 and IP67 (mated or with closed cap)
- True mains connector with breaking capacity (CBC)
- · Easy and reliable twist lock system

#### **Physical Characteristics**

Color Grey

Connector Type powerCON TRUE1 Temperature Range -30  $^{\circ}$ C to +80  $^{\circ}$ C

Contact Plating 2µm Ag

Contacts Copper Alloy

Insert Polyamide (PA6.6)

Locking Element Polyamide (PA6.6)

Shell Polyamide (PA6.6)

Strain Relief Polyketone

Gender Male

### **Electrical Characteristics**

Contact Resistance  $\leq 2 \text{ m}\Omega$ 

Dielectric Strength 4 kVdc / 2.8 kVac

Insulation Resistance >0.1GΩ (after damp and heat test IEC 68-2-30)

Number of electrical contacts 2 + PE

Rated Voltage 20A 250 VAC





# **Neutrik TRUE1 2+PE powerCON Connector (Male)**

NT-NAC3M-TRUE1-S - Specifications

### **Mechanical Characteristics**

Cable O.D. 6 - 12 mm (0.23 – 0.47 inches)

Lifetime > 5000 mating cycles

Wire size  $1.0 - 2.5 \text{ mm}^2$ 

14 AWG

Wiring Screw Type Terminals

Locking Device Twist lock

**Environmental** 

Protection class IP 65 / 67 (mated or with closed caps)

Flammability acc. to UL94 V-0

UV Resistance F1 rated material withstands UV exposure

IEC Compliant
UL Compliant
CSA Compliant
VDE Compliant

**Manufacturer Information** 

Neutrik Part Number NAC3F-TRUE1-S

**Packaging Information** 

Package Quantity 1

Product Weight 0.02 lbs [0.01 kg]

