


SOLAR INVERTER

IVEM3024/5048



FEATURES

- Configurable input voltage range for home appliances and personal computers via LCD setting.
- Configurable battery charging current based on applications via LCD setting.
- Configurable AC/Solar Charger priority via LCD setting.
- Compatible to mains voltage or generator power.
- Built-in MPPT solar charge controller.
- Auto restart while AC is recovering.
- Lithium battery activation function.
- Inverter running without battery.
- Cold start function.






CHARGING PROTECTION



SUPPORT A VARIETY OF BATTERIES



MAX 12 PCS IN PARALLEL FOR 5KVA



PURE SINE WAVE INVERTER



OVERLOAD PROTECTION



WORKING WITHOUT BATTERY



LOW NOISE



MAX PV VOLTAGE



OVER TEMPERATURE PROTECTION



SHORT CIRCUIT PROTECTION

PRODUCT PARAMETERS

Model	IVEM3024	IVEM5048
Line Mode Specifications		
Rated Output Power(VA)	3000VA	5000VA
Rated Output Power(W)	3000W	5000W
Nominal DC Input Voltage	24V	48V
Nominal Input Voltage	230Vac	
Max. AC Input Voltage	280Vac	
Nominal Input Frequency	50Hz / 60Hz (Auto detection)	
Efficiency(Line Mode)	> 95% (Rated R load, battery full charged)	
Pass Through Without Battery	Yes	
Utility Charge Mode Specifications		
Nominal Input Voltage	230Vac	
Input Voltage Range	90-280Vac	
Max. Charge Current	100A	
Over Charge Protection	Yes	
Solar Charging & Grid Charging		
Max. PV Open Circuit Voltage	500V	
PV Voltage Working Range	120V-500V	
Max. Input Power	4000W	6000W
Max. Solar Charging Current	100A	100A
Max. Charging Current(PV+Grid)	100A	100A
Max. Input Current	15A	20A
Min. Startup Voltage	125V	
Inverter Mode Specifications		
Output Voltage Waveform	Pure sine wave	
Nominal Output Voltage	230Vac+5%	
Nominal Output Frequency(Hz)	50±0.3Hz/60Hz±0.3Hz(Adjustable)	
Parallel capability	No	Yes, up to 12 units
Peak Efficiency	93%	
Over-Load Protection(SMPS load)	5.5s@≥150% load; 10.5s @105% ~150% load	
Surge Rating	2* rated power for 5s	
Capable of Starting Electric	Yes	
Output Short Circuit Protection	Yes	
General Specifications		
Operating Temperature	0°C~55°C	
Range Storage Temperature	-15°C~60°C	
Net Weight(KG)	10.8KG	13.2KG
Product Dimension(MM)	395*295*129MM	415*320*129MM
Package Dimension(MM)	472*372*202MM	494*399*202MM