Eanovo Technology (Shenzhen) Co., Ltd

A Building, ShangXue Technology Industrial Park, Bantian ,LongGuang , Shenzhen, Guangdong. China.

Contact person: Lena Lee   Mob/WhatsApp: 86-15899766616   Tel:86-755-83721915 Fax:86-755-26062035

Email:lena@eanovo.com.cn   Skype:lena0621   http://www.eanovo.com.cn   http://www.globalsources.com/eanovo.co

Quotation

Unit Price (USD)	10kpcs	5kpcs	3kpcs	Sample	Blood Fingertip Pulse Oximeter	Model NO.: EA-X8

Major Features	SpO2 value display
	Pulse rate value display, bar graph display
	Pulse waveform display
	PI value display
	The display mode can be changed
	low-voltage indicator appears before working abnormally which is due to low-voltage
	Pulse sound indication and over limit indication
Display Mode	0.96" color display
Screen Resolution	128*64
SpO2 Measuring Range	0%~100% (the resolution is 1%)
	Accuracy: 70%~100%: ±2%, Below 70% unspecified
PR Measuring Range	30 bpm ~ 250 bpm (the resolution is 1 pbm)
	Accuracy: ±2 bpm or ±2% bpm (select larger)
PI Measuring Range	0%~20%
	Accuracy: When the PI measure range is 1%~20%, the permission of absolute error is ±1%
	When the PI measure range is 1%~0.9%, the permission of absolute error is ±0.2%
Measurement Performance in Weak Filling Condition	SpO2 and pulse rate can be shown correctly when pulse-filling ratio is 0.4%. SpO2 error is ± 4%, pulse rate error is ±2 bpm or ±2%(select larger)
Resistance to surrounding light	The deviation between the value measured in the condition of man-made light or indoor natural light and that of darkroom is less than ±1%
Power Consumption	less than 80 mA
Voltage	DC 2.6V ~ 3.6V
Power Supply	1.5V (AAA size) alkaline batteries X 2
Safety Type	Interior Battery, BF Type
Package Contents	Gift box + Pules Oximeter + Hanging rope + user manual (Carry case and Battery optional)
Dimension	61(L) mm * 36(W) mm * 32(H) mm
Weight	About 60g (with the batteries)