

Technical Data	
Model	RF-NL-PB
Beam Angle	6°
Compatible Mount	NL Mount
Compatible Product	Evoke 900C / 1200 / 1200B / 2400B
Product Weight	NL Mount Parallel Beam Reflector: 9.37kg / 20.66lb Carrying Bag: 9.22kg / 20.33lb
Product Size	Reflector with snoot retracted: φ774 x 499mm / φ30.5 x 19.6" Reflector with snoot installed: φ774 x 710.8mm / φ30.5 x 28.0" Carrying Bag: φ860 x 550mm / φ33.9 x 21.7"
Includes	NL70 Parallel Beam Reflector x 1 Plastic Protective Cover x 1 User Manual x 1 Carrying Bag x 1

Illumination (lux / fc)		
Evoke 900C + RF-NL-PB		
Distance	3200K	5600K
5M	22370 lux / 2078 fc	22940 lux / 2131 fc
10M	9450 lux / 878 fc	9524 lux / 885 fc
15M	3430 lux / 319 fc	3415 lux / 317 fc
20M	1989 lux / 185 fc	1997 lux / 186 fc
Evoke 1200B + RF-NL-PB		
Distance	3200K	5600K
5M	69000 lux / 6410 fc	95040 lux / 8829 fc
10M	20810 lux / 1933 fc	25080 lux / 2330 fc
15M	7087 lux / 658 fc	8607 lux / 800 fc
20M	3975 lux / 369 fc	4706 lux / 437 fc
Evoke 2400B + RF-NL-PB		
Distance	3200K	5600K
5M	65400 lux / 6076 fc	76300 lux / 7088 fc
10M	19590 lux / 1820 fc	22420 lux / 2083 fc
15M	8861 lux / 823 fc	10160 lux / 944 fc
20M	4991 lux / 464 fc	5749 lux / 534 fc