

90W external power adapter

The Shuttle Accessory PE90 is an external AC to DC power adapter meant as a replacement device for certain Shuttle products. It provides a maximum output wattage of 90W.

XPC Accessory
PE90

Feature Highlight	
Package contents	- Power adapter (90W) with DC cable and DC output plug - AC power cord with Schuko-plug - Quick guide
Input	- Input Voltage: 100~240 VAC, 50~60 Hz - Input Current: max. 1.5 A
Output	- Output Voltage: 19 V DC - Output Current: max. 4.74A - Output Wattage: max. 90W
Cooling	Passive, fanless cooling
Connectors	- DC connector: 5.5/2.5mm (outer/inner diameter) - AC connenctor: angled Schuko safety plug (with earthing contact)
Environ-mental	- Operation temperature range: 5~35 °C (41~95 °F) - Relative humidity range: 10~90% (non-condensing)
Safety/EMI	Compliance and Logos: CE, WEEE and others
Dimensions	- Dimensions: 127 x 51 x 30.5 mm (LWH) - Weight: 310 g (max.)



Images for illustration purposes only.



DH410



DL30N



Compatibility

the Shuttle PE90 power adapter is compatible with the following Shuttle products (also downward compatible with 40/65 power adapters):

Product Category	Original Power Supply of the Shuttle Product				
	40 W	65 W	90 W	120 W	180 W
XPC slim	XS35/XS36 series DX30 DL10J DL20N(6)	DS47, DS407T, DS437(T) DS57U(x), DS67U(x), DS68U(x), DS77U(x) DS10U(x), DS20U(x) XC60J DL30N(x)	DS50U(x) DS61, DS81, DS87 DH110(SE), DH170, DQ170 DH270 DH310(S)(V2), DH370 DH410(S), DH470 XH61(V), XH81(V), XH97V XH110(V), XH170, XH310(R)(V)	DH610(S) DH670(V2) DH770 DH810 XH610(V) XH810	DB860 XH110G XH410G XH510G XH510G2 XH610G2 XB860G2
XPC nano	—	NC01U(x), NC02U(x), NC03U(x) NC10U(x), NC40U(x) NE10N	—	DN11H* NA10H* NT10H*	—
XPC All-in-one	X50V2 (Plus) X50V3(L)	X50, X50V4 X50V5(U3), X50V6(U3) X50V7(U3), X50V8(U3) P20U, P22U, P25U P51U(3), P52U(3) P90U(x), P92U(x)	X50V9(Ux) P55U(3)	—	—
Edge PC	—	SPCELxx	EN01J3, EN01J4	—	—