



翔鑫科技股份有限公司

Oro Technology Co., LTD

**無線胎壓監測器**

**Tire Pressure Monitoring System**

**Model: BTX-202**

## BTX-202 Specification

Power Supply	3V
Operating Humidity	最大 95%
Storage Temperature	-40℃ ~ 85℃
Operation Temperature	-20℃ ~ 85℃
Pressure Monitoring Range	0 psi ~ 50 psi
Transmitting Frequency	2.4 GHz
Battery capacity	350mAh
Module Weight	13g±0.5g

## Tire Sensor Installation

1. Take off the tire and bleed the air. To change to the ORO-Technology TPMS valve.



2. Put the sensor to the tire and follow steps:



- 2.1 Install the tire sensor to the valve.
- 2.2 Use the nylok screw and tighten up with the tire sensor. (Please use the screwdriver to lock the nylok screw using  $2.2\text{N} \cdot \text{m}$  ( $22.4\text{kg} \cdot \text{cm}$ ) torque)

## **FCC Notices**

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules.

These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

### **CAUTION:**

Any changes or modifications not expressly approved by the grantee of this device could void the user's authority to operate the equipment.

### **RF exposure warning:**

The equipment complies with FCC RF exposure limits set forth for an uncontrolled environment.

To comply with FCC RF exposure requirements, a minimum separation distance of 20 cm must be maintained between the device and any persons during operation.

The equipment must not be co-located or operating in conjunction with any other antenna or transmitter.

## **NCC 警語**

取得審驗證明之低功率射頻器材，非經核准，公司、商號或使用者均不得擅自變更頻率、加大功率或變更原設計之特性及功能。低功率射頻器材之使用不得影響飛航安全及干擾合法通信；經發現有干擾現象時，應立即停用，並改善至無干擾時方得繼續使用。前述合法通信，指依電信管理法規定作業之無線電通信。低功率射頻器材須忍受合法通信或工業、科學及醫療用電波輻射性電機設備之干擾。