

## Audi of America Audi Q5 3.2 Technical Specifications 2011 Model Year


Technical Specifications		2011 Audi Q5 3.2 FS						
ENGINE:								
Туре	Direct Injection, 24 valve, DOHC V6, continu	ious camshaft adjustment						
Arrangement	Front mounted, longitudinal							
Bore	3.37 in. 92.8 mm							
Stroke	3.65 in. 85.5 mm							
Displacement	195.1 cu. in. 3197 cc							
Compression ratio	12.5:1							
Fuel requirement	Premium unleaded (91 Octane) recommended for maximum performance							
Horsepower (SAE)	270 hp @ 6500 rpm	199 kw						
Max. Torque	243 lbs. ft. @ 3000 rpm	330 nm						
ENGINE DESIGN:								
Cylinder block	Aluminum-alloy							
Cylinder head	Aluminum-alloy							
Valve train / intake	Double overhead cam, compact four-valve of	lesign, auxiliaries and camshafts driven by maintenance-free chains, Audi valvelift system						
Firing order								
Fuel injection /	Fully electronic engine management, seque	ntial, direct petrol injection with adaptive idle charge control						
Ignition system	Adaptive lambda control, cylinder selective	adaptive knock regulation with two sensors						
Emission system	dual catalytic converters, four oxygen senso	rs						
Emissions level	Tier2 BIN5 / ULEV II							
ELECTRICAL SYSTEM:								
Battery	12 volts 92 amp/hr							
Alternator	14 volts 150 amp							
DRIVETRAIN:	) 14 Yold Too dinp							
Transmission	Six and automatic with Tintronic@ with DS	D and Coast shift program						
Type	Six-speed automatic with Tiptronic® with DSP and Sport shift program							
Туре	quattro Tiptronic							
Gear ratios: 1st	Automatic 4.171:1							
2nd	2.340:1							
3rd	1.521:1							
4th	1.143:1							
5th	0.867:1							
6th	0.691:1							
reverse	3.403:1							
Final Drive	4.216:1							
Front Differential	Hypoid gear, electronically locking (EDL)							
Center Differential	Self-locking differential providing automatic and variable front to rear power proportioning							
Rear Differential	Hypoid gear, electronically locking (EDL)							
STEERING:								
Туре	Servotronic, speed-sensitive power rack and	I ninion maintenance-free						
Ratio	16.3:1							
Turns (lock-to-lock)								
Turning circle (curb-to-curb)	38.1 ft. 11.6 m							
SUSPENSION:								
Front	Front five-link independent steel spring susp	ension						
Rear	Rear trapezoidal-link independent steel spring suspension							
BRAKES:	,	<del></del>						
DINAILU.		A (						
	Dual-circuit brake system with diagonal split, Anti-lock Brake System (ABS), Electronic Brake pressure Distribution (EBD)							
	and Electronic Stabilization Program (ESP); brake booster							
Front, size and type	12.6 in. 320 mm - Ventilated disc							
Rear, size and type	11.8 in. 300 mm - solid disc							
•••								
Parking brake	electro-mechanically actuated at the rear wh	eels						

## Audi of America Audi Q5 3.2 Technical Specifications 2011 Model Year

Technical Specif	ications (contin	ued)							2011 Audi Q5 3.2
WHEELS:									
Size		8.0J x 19, cast	alloy, five-arm des	ign		stan	dard		
		8.5J x 20, cast alloy, five-segment spoke design			optio	onal			
		8.5J x 20, cast alloy, Chrome-clad ten-spoke design			optio				
TIRES:									
		005/55 040 #							
Size		235/55 R19 all season tire 255/45 R20 summer performance tire				dard			
		255/45 R20 Su	mmer periormance	ure		optio	onai		
BODY:									
Material		Unitized steel structure with integrated aluminum and magnesium co							
Corrosion protection						limited warra	nty against corrosion	n perforation)	
WARRANTY/MAINTENANCE:		4-Year/50,000 mile new vehicle limited warranty							
		12-Month/5,000 mile (whichever occurs first) NO CHARGE first scheduled maintenance							
CAPACITIES:									
		3.2 զւ	uattro						
Engine oil		6.6 qt.	6.2 liter						
Fuel tank		19.8 gal.	75 liter						
Cooling system		9.2 qt.	8.7 liter						
EXTERIOR DIMENSIC	NS:								
		}	3.2 quattro						
Wheelbase		110.5 in.	2807 mm						
Track:	front / rear	63.7 / 63.5	1617 / 1613						
Overall length		182.2 in.	4629 mm						
Overall width	mirrors	74.0 / 82.2	1880 / 2089						
Height (unloaded)		65.1 in.	1653 mm						
Ground clearance (I	oaded)	7.9 in.	200 mm						
Curb weight		4,299 lbs.	1950 kg						
Drag coefficient		Cw = 0.33	Frontal Area =	=	2.65 sq. m.				
INTERIOR DIMENSIO	NS:								
EPA Class		Light Truck							
Seating Capacity		5							
Head room	front / rear	39.4 in.	1000 mm	1	39.0 in.	990 mm			
w/sunroof	front / rear	38.1 in.	967 mm	/	37.7 in.	958 mm			
Shoulder room	front / rear	57.7 in.	1465 mm	/	56.4 in.	1433 mm			
Leg room	front / rear	41.0 in.	1041 mm	1	37.4 in.	950 mm			
Int. vol. (EPA)	front / rear	53.9 cu. ft.			47.6 cu. ft.				
Luggage capacity (E	EPA)	29.1 cu. ft.	57.	3 cu. ft.	(2nd row folde	d)			
PERFORMANCE:									
			3.2 quattro						
0-60 mph		6.7	sec.		T				
Top speed		Electronically li	mited to 130 mph	(209 km/h	1)				
FUEL ECONOMY:		21	011 EPA figures						
			3.2 quattro						
City		18	mpg						
Highway		23	mpg		<del> </del>				
Combined		20	mpg						
					- /				

## Audi Q5

Dimensions 04/08



<sup>\*</sup> maximum headroom Dimensions in milimeters and inches Dimensions of vehicle unloaded