

Application

A square, surface mounted wall washer with asymmetric wide beam light distribution. Designed for the illumination of walls in corridors and covered pedestrian walkways.

Materials

- Clear safety glass with optical texture
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 7.5 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	36.8 W
System wattage	42.0 W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	5527 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options	
CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL finish



Wall washer · Asymmetric				
	LED		A	B
B24090	36.8 W		76°x68°	9 ⁵ / ₈ 4 ¹ / ₈

