# **WATSON**°

4 Bay **Charger** 

for AA/AAA NiMH or NiCd Rechargeable Batteries

Owner's Manual

### **FEATURES**

- Accepts up to four AA/AAA NiMH or NiCd rechargeable batteries.
- Four independent battery charging channels.
- · Four charging status LEDs.
- · Folding outlet prongs.
- Protection against short circuits, power surges, and reverse polarity.
- Universal 100-240 V AC input for worldwide use.

## SAFETY WARNINGS

- Do not charge any battery other than AA or AAA NiMH or NiCd batteries. Other types of batteries can burst, causing personal injury and damage.
- Do not disassemble the charger. Take the charger to a qualified service technician when service or repair is required. Improper assembly may result in the risk of electric shock or fire.
- Do not operate the charger if it has received a sharp blow or has been dropped or damaged in any way.
- · Never expose the charger to rain or moisture.
- Do not use an extension cord when using the charger. This can result in a fire or electric shock.
- Never use the charger as a DC power source for any electrical equipment.

#### # I WATSON

- Always unplug the charger from the AC outlet before handling the batteries.
- Unplug the charger from the AC outlet before attempting maintenance or cleaning.
- Do not use any attachment not recommended or sold by Watson, as this could result in the risk of fire, electric shock, or injury.

## CHARGING BATTERIES

Insert up to 4 AA/AAA NiMH or NiCd rechargeable batteries into the battery chambers as indicated by the + and - symbols marked inside each chamber.

The charging status LEDs will glow red when the batteries are charging, and green when charging is complete.

Note: If the LED flashes, remove the batteries and make sure they're seated properly. If flashing continues, this may indicate a defective battery. Remove the batteries and replace with new ones.

## **SPECIFICATIONS**

Input Voltage	100~240 V AC, 50/60 Hz, 15 W max
Max. Output	1.2 V 1800 mA AA: 1800 mA AAA: 900 mA
Automatic Shutoff	Negative Delta V and Zero Slope Detection
Operating Temperature	32°F to 95°F (0°C to 35°C)
Dimensions (H × W × D)	4.3 × 2.6 × 1.1 in. (11 × 6.5 × 2.75 cm)
Weight	2.75 oz. (78 g) charger
Certifications	FCC

#### ONE-YEAR LIMITED WARRANTY

This Watson product is warranted to the original purchaser to be free from defects in materials and workmanship under normal consumer use for a period of one (1) year from the original purchase date or thirty (30) days after replacement, whichever occurs later. The warranty provider's responsibility with respect to this limited warranty shall be limited solely to repair or replacement, at the provider's discretion, of any product that fails during normal use of this product in its intended manner and in its intended environment. Inoperability of the product or part(s) shall be determined by the warranty provider. If the product has been discontinued, the warrantu provider reserves the right to replace it with a model of equivalent quality and function. This warrantu does not cover damage or defect caused by misuse. improper installation maintenance. EXCEPT AS PROVIDED HEREIN. THE WARRANTY PROVIDER MAKES NEITHER ANY EXPRESS WARRANTIES NOR ANY IMPLIED WARRANTIES INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. This warranty provides you with specific legal rights, and uou mau also have additional rights that varu from state to state. To obtain warranty coverage, contact the Watson Customer Service Department to obtain a return merchandise authorization ("RMA") number, and return the defective product to Watson along with the RMA number and proof of purchase. Shipment of the defective product is at the purchaser's own risk and expense. www.goweredbuwatson.com or call Customer Service at 212-594-2353.

Product warranty provided by the Gradus Group. www.gradusgroup.com

Watson is a registered trademark of the Gradus Group © 2023 Gradus Group LLC. All Rights Reserved.

