

Encode Control Tripple Channel DC Power Supplies

multicompPRO



Features

- Complete digital control for MPN 72-13300 & 72-13310 only
- Complete programmable for MPN 72-13320 & 72-13330 only
- 10mV / 1mA resolution
- Low noise and ripple
- C4V / CC constant voltage and constant current modes
- Industrial grade, with load for a long time
- Over-Current Protection, output ON/OFF control and panel LOCK function
- Shutdown memory
- Series and parallel connections

Specification Table

Characteristics	Values			
	72-13300	72-13310	72-13320	72-13330
Voltage Range / Current Range	0-30V / 0-3A × 2, 5V, 3.3V, 2.5V / 3A × 1	0-30V / 0-5A × 2, 5V, 3.3V, 2.5V / 3A × 1	0-30V / 0-3A × 2, 5V, 3.3V, 2.5V / 3A × 1	0-30V / 0-5A × 2, 5V, 3.3V, 2.5V / 3A × 1
Load Regulation	Voltage: ≤0.01%+3mv / Current: ≤0.1%+5mA	Voltage: ≤0.01%+5mV / Current: ≤0.1%+10mA	Voltage: ≤0.01%+3mv / Current: ≤0.1%+5mA	Voltage: ≤0.01%+5mV / Current: ≤0.1%+10mA
Line Regulation	Voltage: ≤0.01%+3mv / Current: ≤0.1%+3mA	Voltage: ≤0.01%+3mV / Current: ≤0.1%+3mA	Voltage: ≤0.01%+3mv / Current: ≤0.1%+3mA	Voltage: ≤0.01%+3mV / Current: ≤0.1%+3mA
Setup Resolution	Voltage: 10mV / Current: 1mA	Voltage: 10mV / Current: 1mA	Voltage: 10mV / Current: 1mA	Voltage: 10mV / Current: 1mA
Setup Accuracy (25°C ±5°C)	Voltage: ≤0.5%+20mV / Current: ≤0.5%+5mA	Voltage: ≤0.5%+20mV / Current: ≤0.5%+10mA	Voltage: ≤0.5%+20mV / Current: ≤0.5%+5mA	Voltage: ≤0.5%+20mV / Current: ≤0.5%+10mA
Ripple (20Hz ~ 20M)	Voltage: ≤1mVrms / Current: ≤3mA _{Arms}	Voltage: ≤2mVrms / Current: ≤3mA _{Arms}	Voltage: ≤1mVrms / Current: ≤3mA _{Arms}	Voltage: ≤2mVrms / Current: ≤3mA _{Arms}
Temp. Coefficient	Voltage: 100ppm+10mV / Current: ≤100ppm+5mA	Voltage: 100ppm+10mV / Current: ≤100ppm+5mA	Voltage: 100ppm+10mV / Current: ≤100ppm+5mA	Voltage: 100ppm+10mV / Current: ≤100ppm+5mA
Read Back Accuracy	Voltage: 10mV / Current: 1mA	Voltage: 10mV / Current: 1mA	Voltage: 10mV / Current: 1mA	Voltage: 10mV / Current: 1mA
Read Back Temp. Coefficient	Voltage: ≤100ppm+10mv / Current: ≤100ppm+5mA	Voltage: ≤100ppm+10mV / Current: ≤100ppm+5mA	Voltage: ≤100ppm+10mv / Current: ≤100ppm+5mA	Voltage: ≤100ppm+10mV / Current: ≤100ppm+5mA

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO

Encode Control Tripple Channel DC Power Supplies

multicompPRO

Characteristics	Values			
	72-13300	72-13310	72-13320	72-13330
Reaction Time (10% Rated load)	Voltage Rise: ≤100mS / Voltage Drop: ≤100mS	Voltage Rise: ≤100mS / Voltage Drop: ≤100mS	Voltage Rise: ≤100mS / Voltage Drop: ≤100mS	Voltage Rise: ≤ 100mS / Voltage Drop: ≤ 100mS
Load Regulation of Parallel	Voltage: ≤0.1%+0.2V	Voltage: ≤0.1%+0.2V	Voltage: ≤0.1%+0.2V	Voltage: ≤0.1%+0.2V
Load Regulation of Series	Voltage: ≤0.1%+0.2V	Voltage: ≤0.1%+0.2V	Voltage: ≤0.1%+0.2V	Voltage: ≤0.1%+0.2V
CH3 Specifications	Voltage Accuracy: ±50mV Load Regulation: ±50mV	Voltage Accuracy: ±50mV Load Regulation: ±50mV	Voltage Accuracy: ±50mV Load Regulation: ±50mV	Voltage Accuracy: ±50mV Load Regulation: ±50mV
Accessories	User manual, Power cord (1.2m, 1×UK plug & 1×EURO plug)		User manual, Power cord (1.2m, 1×UK plug & 1×EURO plug), USB cord (1.2m), Software CD	
Interfaces	-		USB, RS232 & LAN	
Weight	7.8kgs	10.3kgs	7.88kgs	10.38kgs
Dimension (W×H×D)	146mm×252mm×375mm			

Input Voltage: 230V (±10%)

Part Number Table

Description	Part Number
Tripple Channel DC Power Supply with Digital Encoder Control	72-13300
	72-13310
Tripple Channel DC Power Supplies with USB, RS232 & LAN Interfaces	72-13320
	72-13330

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO