

ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU

Product Guide

The ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU is built on the NVIDIA Ampere GPU architecture and brings the power of AI and ray tracing acceleration to entry-level workstations, making it accessible to more professionals. The RTX A400 GPU features 768 CUDA Cores, 24 third-generation Tensor Cores, six second-generation RT Cores, and 4GB of GDDR6 graphics memory.

The RTX A400 GPU delivers the performance, AI capabilities, enterprise reliability, and features professionals need in a small-form-factor solution.



Figure 1. ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU

Did you know?

NVIDIA RTX professional graphics cards are certified for a broad range of professional applications, tested by leading independent software vendors (ISVs) and workstation manufacturers, and backed by a global team of support specialists. Get the peace of mind to focus on what matters with the premier visual computing solution for mission-critical business.

Part number information

The following table shows the part numbers for the RTX A400 GPU.

Table 1. Ordering information

Part number	Feature code	Description	Controlled GPU status
4X67B03688	C9KE	ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU	No

The RTX A400 GPU is not Controlled which means the GPU is unrestricted and is available in all markets.

The option part numbers includes the following:

- One RTX A400 GPU
- Full-height (3U) and Low profile (2) adapter brackets
- Documentation flyer

Features

The RTX A400 GPU is an efficient, single slot professional solution for CAD, DCC, financial service industry (FSI) and visualization professionals in general looking to reach great performance in a compact form factor. Building upon the enhancements from the Turing GPU, the NVIDIA Ampere architecture enhances ray tracing operations, tensor matrix operations, and concurrent executions of FP32 and INT32 operations.

Key features:

- Second-generation RT Cores
- Third-generation Tensor Cores
- Four Mini DisplayPort 1.4a
- AV1 decode support
- DisplayPort with audio
- NVIDIA RTX Experience
- NVIDIA RTX Desktop Manager software
- NVIDIA RTX IO support
- HDCP 2.2 support
- NVIDIA Mosaic technology
- PCI Express Gen 4 host interface

Key workloads:

- Design and Visualization
- Digital Content Creation
- Computer-Aided Design
- Multi-Display Work Environments
- Edge Computing Applications
- Productivity Applications

Technical specifications

The following table lists the specifications of the RTX A400 GPU.

Table 2. RTX A400 GPU specifications

Feature	Specification
GPU Architecture	NVIDIA Ampere Architecture
GPU Memory	4 GB GDDR6
Memory Interface	64-bit
Memory Bandwidth	96 GB/s
ECC	Yes
NVIDIA CUDA Cores	768 Ampere CUDA Cores
NVIDIA Tensor Cores	24 third-generation Tensor Cores
NVIDIA RT Cores	6 second-generation RT Cores
Peak Single-Precision Performance	2.7 TFLOPS (peak)
Peak RT Core performance	5.3 TFLOPS (peak)
FP16 Tensor Performance	21.7 TFLOPS (peak) (with sparsity)
INT8 Tensor Performance	43.3 TOPS (peak) (with sparsity)
NVLink support	No
Host Interface	PCI Express 4.0 x8
Power Consumption	50 W
Thermal Solution	Active cooling
Form Factor	2.7" H x 6.4" L (Low Profile), single slot
Display Connectors	4x Mini DisplayPort (mDP) 1.4a
Maximum simultaneous displays	4x 4096 x 2160 @ 120 Hz, 4x 5120 x 2880 @ 60 Hz
Encode / Decode Engines	1x encode, 1x decode (+AV1 decode)
VR Ready	No
Graphics APIs	DirectX 12, Shader Model 6.6, OpenGL 4.6, Vulkan 1.3
Compute APIs	CUDA 11.6, DirectCompute, OpenCL 3.0

Server support

The following tables list the ThinkSystem servers that are compatible.

Table 3. Server support (Part 1 of 4)

Part Number	Description																																								
		AMD V3			2S Intel V3/V4			4S 8S Intel V3		Multi Node V3/V4	1S V3																														
4X67B03688	ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU	N	SR635 V3 (7D9H / 7D9G)	N	SR655 V3 (7D9F / 7D9E)	N	SR645 V3 (7D9D / 7D9C)	N	SR665 V3 (7D9B / 7D9A)	N		ST650 V3 (7D7B / 7D7A)	N	SR630 V3 (7D72 / 7D73)	8	SR650 V3 (7D75 / 7D76)	N	SR630 V4 (7DG8 / 7DG9)	N	SR650 V4 (7DGC / 7DGD)	N	SR650a V4 (7DGC / 7DGD)	N	SR850 V3 (7D97 / 7D96)	N	SR860 V3 (7D94 / 7D93)	N	SR950 V3 (7DC5 / 7DC4)	N	SD535 V3 (7DD8 / 7DD1)	N	SD530 V3 (7DDA / 7DD3)	N	SD550 V3 (7DD9 / 7DD2)	N	ST45 V3 (7DH4 / 7DH5)	N	ST50 V3 (7DF4 / 7DF3)	1	ST250 V3 (7DCF / 7DCE)	1

Table 4. Server support (Part 2 of 4)

Part Number	Description	GPU Rich					Edge				Super Computing				
		N	N	N	N	N	N	N	N	N	N	N	N	N	
4X67B03688	ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU	N	SR670 V2 (7Z22 / 7Z23)												
		N	SR675 V3 (7D9Q / 7D9R)												
		N	SR680a V3 (7DHE)												
		N	SR685a V3 (7DHC)												
		N	SR780a V3 (7DJ5)												
		N	SE100 (7DGR)												
		N	SE350 (7Z46 / 7D1X)												
		N	SE350 V2 (7DA9)												
		N	SE360 V2 (7DAM)												
		N	SE450 (7D8T)												
		N	SE455 V3 (7DBY)												
		N	SC750 V4 (7DDJ)												
		N	SC777 V4 (7DKA)												
		N	SD665 V3 (7D9P)												
		N	SD665-N V3 (7DAZ)												
N	SD650 V3 (7D7M)														
N	SD650-I V3 (7D7L)														
N	SD650-N V3 (7D7N)														

Table 5. Server support (Part 3 of 4)

Part Number	Description	1S Intel V2		2S Intel V2		AMD V1				Dense V2				4S V2		8S																					
		N	Z	N	Z	N	Z	N	Z	N	Z	N	Z	N	Z																						
4X67B03688	ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU	N	ST50 V2 (7D8K / 7D8J)	N	ST250 V2 (7D8G / 7D8F)	N	SR250 V2 (7D7R / 7D7Q)	N	ST650 V2 (7Z75 / 7Z74)	N	SR630 V2 (7Z70 / 7Z71)	N	SR650 V2 (7Z72 / 7Z73)	N	SR635 (7Y98 / 7Y99)	N	SR655 (7Y00 / 7Z01)	N	SR655 Client OS	N	SR645 (7D2Y / 7D2X)	N	SR665 (7D2W / 7D2V)	N	SD630 V2 (7D1K)	N	SD650 V2 (7D1M)	N	SD650-N V2 (7D1N)	N	SN550 V2 (7Z69)	N	SR850 V2 (7D31 / 7D32)	N	SR860 V2 (7Z59 / 7Z60)	N	SR950 (7X11 / 7X12)

Table 6. Server support (Part 4 of 4)

Part Number	Description			
		4S V1	1S Intel V1	2S Intel V1
4X67B03688	ThinkSystem NVIDIA RTX A400 4GB PCIe Gen4 Active GPU	N	SR850 (7X18 / 7X19)	Dense V1
		N	SR850P (7D2F / 2D2G)	
		N	SR860 (7X69 / 7X70)	
		N	ST50 (7Y48 / 7Y50)	
		N	ST250 (7Y45 / 7Y46)	
		N	SR150 (7Y54)	
		N	SR250 (7Y52 / 7Y51)	
		N	ST550 (7X09 / 7X10)	
		N	SR530 (7X07 / 7X08)	
		N	SR550 (7X03 / 7X04)	
		N	SR570 (7Y02 / 7Y03)	
		N	SR590 (7X98 / 7X99)	
		N	SR630 (7X01 / 7X02)	
		N	SR650 (7X05 / 7X06)	
		N	SR670 (7Y36 / 7Y37)	
		N	SD530 (7X21)	Dense V1
		N	SD650 (7X58)	
		N	SN550 (7X16)	
		N	SN850 (7X15)	

NVIDIA GPU software

This section lists the NVIDIA software that is available from Lenovo.

- [NVIDIA HPC Compiler Software](#)

NVIDIA HPC Compiler Software

Table 7. NVIDIA HPC Compiler

Part number	Feature code 7S09CTO6WW	Description
HPC Compiler Support Services		
7S090014WW	S924	NVIDIA HPC Compiler Support Services, 1 Year
7S090015WW	S925	NVIDIA HPC Compiler Support Services, 3 Years
7S09002GWW	S9UQ	NVIDIA HPC Compiler Support Services, 5 Years
7S090016WW	S926	NVIDIA HPC Compiler Support Services, EDU, 1 Year
7S090017WW	S927	NVIDIA HPC Compiler Support Services, EDU, 3 Years
7S09002HWW	S9UR	NVIDIA HPC Compiler Support Services, EDU, 5 Years
7S090018WW	S928	NVIDIA HPC Compiler Support Services - Additional Contact, 1 Year
7S09002JWW	S9US	NVIDIA HPC Compiler Support Services - Additional Contact, 3 Years
7S09002KWW	S9UT	NVIDIA HPC Compiler Support Services - Additional Contact, 5 Years
7S090019WW	S929	NVIDIA HPC Compiler Support Services - Additional Contact, EDU, 1 Year
7S09002LWW	S9UU	NVIDIA HPC Compiler Support Services - Additional Contact, EDU, 3 Years
7S09002MWW	S9UV	NVIDIA HPC Compiler Support Services - Additional Contact, EDU, 5 Years
HPC Compiler Premier Support Services		
7S09001AWW	S92A	NVIDIA HPC Compiler Premier Support Services, 1 Year
7S09002NWW	S9UW	NVIDIA HPC Compiler Premier Support Services, 3 Years
7S09002PWW	S9UX	NVIDIA HPC Compiler Premier Support Services, 5 Years
7S09001BWW	S92B	NVIDIA HPC Compiler Premier Support Services, EDU, 1 Year
7S09002QWW	S9UY	NVIDIA HPC Compiler Premier Support Services, EDU, 3 Years
7S09002RWW	S9UZ	NVIDIA HPC Compiler Premier Support Services, EDU, 5 Years
7S09001CWW	S92C	NVIDIA HPC Compiler Premier Support Services - Additional Contact, 1 Year
7S09002SWW	S9V0	NVIDIA HPC Compiler Premier Support Services - Additional Contact, 3 Years
7S09002TWW	S9V1	NVIDIA HPC Compiler Premier Support Services - Additional Contact, 5 Years
7S09001DWW	S92D	NVIDIA HPC Compiler Premier Support Services - Additional Contact, EDU, 1 Year
7S09002UWW	S9V2	NVIDIA HPC Compiler Premier Support Services - Additional Contact, EDU, 3 Years
7S09002VWW	S9V3	NVIDIA HPC Compiler Premier Support Services - Additional Contact, EDU, 5 Years

Auxiliary power cables

The RTX A400 GPU does not require an auxiliary power cable.

Regulatory approvals

The RTX A400 GPU has the following regulatory approvals:

- RCM
- BSMI
- CE
- FCC
- ICES
- KCC
- cUL, UL
- VCCI

Operating environment

The RTX A400 GPU has the following operating characteristics:

- Ambient temperature
 - Operational: 0°C to 50°C (-5°C to 55°C for short term*)
 - Storage: -40°C to 75°C
- Relative humidity:
 - Operational: 5-85% (5-93% short term*)
 - Storage: 5-95%

* A period not more than 96 hours consecutive, not to exceed 15 days per year.

Warranty

One year limited warranty. When installed in a Lenovo server, the GPU assumes the server's base warranty and any warranty upgrades.

Related publications

For more information, refer to these documents:

- ThinkSystem and ThinkAgile GPU Summary:
<https://lenovopress.lenovo.com/lp0768-thinksystem-thinkagile-gpu-summary>
- ServerProven compatibility:
<https://serverproven.lenovo.com/>
- NVIDIA RTX A400 product page:
<https://www.nvidia.com/en-us/design-visualization/rtx-a400/>

Related product families

Product families related to this document are the following:

- [GPU adapters](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP2171, was created or updated on March 18, 2025.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP2171>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP2171>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkAgile®

ThinkSystem®

The following terms are trademarks of other companies:

AMD is a trademark of Advanced Micro Devices, Inc.

Intel® is a trademark of Intel Corporation or its subsidiaries.

DirectX® is a trademark of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.