We connect and protect

ClimaGuard Air-to-Air Heat Exchanger Outdoor, X23 14w/F 230V

CATALOG NUMBER

TX231426100



nVent Hoffman's ClimaGuard Outdoor Heat Exchangers offer reliable closed-loop cooling while sealing out harsh environments including temperature extremes, dirt, dust, corrosive elements and wind-driven rain. This robust heat exchanger features a double-crimped and dip-sealed core, allowing efficient thermal transfer while ensuring maximum protection against leaks. With ClimaGuard Outdoor Heat Exchangers providing a tight seal against air and water infiltration, units can be simply surface- or recess-mounted to an enclosure with no loss of enclosure integrity.

INDUSTRY STANDARDS

UL/cUL Listed; Type 12, 4; 4X optional; File No. SA7402

UR/cUR Recognized

UR/cUR Recognized on select models, reference performance data tables.

CE

EAC

Telcordia GR-487 capable

FEATURES

Unique counterflow aluminum core for high efficiency and high performance heat transfer
Engineered for temperature extremes, corrosive environments and wind driven rain
Models for 24 VDC, 48 VDC, 115 VAC and 230 VAC power supplies
Variable speed blowers standard on DC powered units for quiet running
Filterless design for low maintenance and easy cleaning
Painted galvanized or stainless steel sheet-metal cover for rugged factory and outdoor environments
Easy-mount flanges for simple installation
Surface or recessed mount capable
Every unit functionally tested before shipping
Mounting hardware, gaskets and user manual furnished with the unit

PRODUCT ATTRIBUTES

Article Number: 23417

Capacity Watts Per °F: 14W

Capacity Watts Per °C: 25W

Nominal Voltage: 230V

Height: 23in

Width: 12in

Depth: 7.1in

Material: Mild Steel

Finish: Powder Coated

Color: Light Gray

Color Code: RAL 7035

Weight: 30lb

Thickness: 18ga

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.