



E901RF | Programmable, wireless thermostat

FULL MANUAL

TABLE OF CONTENTS

1. Introduction.....3

1.1 Product Compliance3

1.2 Safety Informations.....3

2. Product Overview4

2.1 Package content.....5

2.2 Proper thermostat location5

2.3 Wall mounting6

2.4 Free-standing thermostat7

3. Receiver8

3.1 Receiver’s switches description.....8

3.2 LED indications in the receiver.....9

3.3 Connection description.....10

4. Before you start (first power on)11

4.1 LCD icon description12

4.2 Button description.....12

5. Time settings.....13

6. Operation.....14

6.1 Manual mode.....14

6.1.1 Comfort mode.....14

6.1.2 Economic mode.....15

6.2 AUTO mode - two schedule types.....16

6.2.1 First type schedule16

6.2.2 Second type schedule.....16

6.2.3 Switching between schedules (AUTO Mode) type 1 and 2.....17

6.3 First type schedule programming.....18

6.3.1 Default program settings (1-3)18

6.3.2 Choosing and programming user programs (4-9)19

6.3.3 Frost Protection program setting21

6.3.4 Temporary override mode22

6.4 Second type schedule programming.....23

6.4.1 Temporary override mode24

6.5 Party mode.....25

6.6 Holiday mode.....26

6.7 Key lock function.....27

7. Pairing with the E901RX receiver28

7.1 Transmission test.....30

8. Installer settings32

9. User settings reset34

10. Clear settings - factory reset34

11. Cleaning and Maintenance35

12. Technical Informations35

13. Warranty36

1. Introduction

1.1 Product Compliance

This product complies with the essential requirements and other relevant provisions of Directives 2014/53/EU and 2011/65/EU.

1.2 Safety Informations

- Before starting installation work and before using the product, read the entire manual.
- The information contained in the instructions is essential for proper functioning.
- To avoid accidents resulting in personal injury and material damage, please follow all safety precautions, specified in this manual.
- The device should not be used by people with limited mental, sensory or mental abilities, without experience, of insufficient knowledge as well as children.
- Do not use an unassembled device (eg without a cover).
- The device may only be opened by a qualified person.
- Keep electrical devices out of the reach of children and ensure that they do not play with it. Children should not be left unattended. If necessary, disconnect the control system for the entire room.
- Do not leave the packaging, cabinet, or any loose parts of the device unattended, as they pose a risk to children.

WARNING!

- Installation must be carried out by a qualified person with appropriate electrical qualifications in accordance with standards and regulations in force in the given country and in the EU.
- Never try to connect the device other than as described in the manual.
- Before assembly, repair or maintenance as well as during any connection works it is absolutely necessary disconnect the mains supply and make sure that the terminals and electric wires are not live.
- The device may not be exposed to extreme temperatures, strong vibrations or subjected to mechanical shock.
- The device should not be used in unfavorable environmental conditions or in rooms where there is a concentration of flammable gases, fumes or dust.

WARNING!

- There may be additional protection requirements for the entire installation that the installer is responsible for maintaining.



Care for the natural environment is of paramount importance to us. The awareness that we manufacture electronic devices obliges us to dispose of used electronic components and devices safely. Therefore the company has received a registration number issued by the Chief Inspector for Environmental Protection. The crossed out symbol the trash can on the product means that the product must not be disposed of with ordinary waste containers. Sorting waste for recycling helps to protect the environment. It is the user’s responsibility to surrender used equipment to a designated collection point for recycling waste from electrical and electronic equipment.

2. Product Overview

E901RF is a weekly, surface-mounted electronic room thermostat, used for wireless control of heating devices (e.g. gas, oil boilers, heat pumps) or cooling devices. It has the function of creating your own schedules. Thanks to the built-in algorithms, it offers much better temperature control accuracy than traditional mechanical thermostats. Please read these instructions carefully before using the device for the first time. The thermostat should use 2xAA, 1.5V alkaline batteries. Rechargeable batteries are not allowed.

In the set:

- thermostat transmitter
- thermostat receiver

Product features:

- has 2 types of time schedules
- possibility to choose hysteresis or built-in TPI algorithm
- maximum / minimum temperature limitation
- two relay types (selectable in thermostat settings): NO (normally open) or NC (normally closed)
- has the HEATING / COOLING function
- PIN lock
- has unique transmission codes
- working range up to 60m in open space
- automatically renews the operating signal

2.1 Package content

1) E901RF thermostat

2) E901RX receiver

3) Quick Guide

4) Thermostat bracket

5) Power supply wire and control wire

6) 2xAA batteries

7) Mounting screws



E901RF thermostat

E901RX receiver

Quick Guide


Thermostat bracket

Power supply wire and control wire

2xAA batteries

Mounting screws

2.2 Proper thermostat location



Please note:

The ideal position to thermostat mounting is about 1,5m under floor level far from heating or cooling sources. Thermostat can't be exposed to sunlight or any extreme conditions like for example draft.

Because of fire and explosion risk there is not allowed to use thermostat in atmosphere of explosive gases and flammable liquids (eg coal dust). In case if any of listed dangers occur you have to use additional protection measures – anti-dust and explosive gases (tight cover) or prevent their formation. Furthermore, thermostat can't be used in condensation of water vapor conditions and be exposed to water action.

2.3 Wall mounting



Remove the thermostat cover as shown in the picture. If there are batteries inside, remove them.

Use a screwdriver to push the plastic tabs in as shown in the figure until you feel resistance, and tilt the front part of the housing.



Separate the front part from the back part in the direction shown above.

Then fix the back cover to the wall using the supplied mounting screws and the holes provided (see red arrows).



Using the hinges, fold the back and front covers by moving as shown in the picture above.

2.4 Free-standing thermostat

With the bracket attached to the E901RF set, you can use the thermostat anywhere in the house and put it on a table, desk, etc. To use the bracket properly, see the steps below:



Mount the bracket on the back of the thermostat with use of the two designed holes.



Place the thermostat in a comfortable and accessible place (see „Please note” in chapter 2.2 page 5).

3. Receiver

The thermostat communicates wirelessly with the receiver. The receiver should be supplied with 230VAC, the maximum switching load of the receiver is 16A. Avoid installing the device in places directly exposed to water, moisture and air condensation. The receiver can operate in two different modes - AUTO (automatic) and MANUAL (manual). To select a specific mode, use the switches on the front of the receiver.



3.1 Receiver's switches description



LEFT SWITCH	
1.	ON - receiver ON
2.	OFF - receiver OFF
RIGHT SWITCH	
3.	MANUAL - Receiver works in manual mode (receiver operation state depends on the position of the left switch)
4.	AUTO - Receiver works in AUTO mode (according to the thermostat's commands)

 **REMEMBER!:**

Thermostat (transmitter) will communicate with receiver only when both are paired together and receiver's switches are set to ON and AUTO position.

3.2 Receiver LED indicators

The status of the receiver is indicated by two LEDs. These are LEDs with the following colors:

- 1 - green (upper one),
- 2 - orange (lower one).




A detailed explanation of the meaning of the LEDs can be found in the table below:


	DESCRIPTION
The green LED lights up	The receiver is connected to the 230V power supply.
The green LED flashes	The receiver is in the pairing mode (then you must activate the "SYNC" parameter in the thermostat).
The green LED is off	The receiver is disconnected from the 230V power supply or the left switch is in the OFF position.
The orange LED lights up	In automatic mode, the receiver received a heating / cooling signal from the thermostat. The receiver was started in manual mode (left switch is set to ON and right switch is set to MANUAL)
The orange LED flashes	The receiver was paired but lost communication with the thermostat due to out of range or low battery in the thermostat. The receiver starts flashing after 40 minutes of time when it does not receive a signal from the thermostat.
The orange LED is off	In automatic mode, the receiver didnt get a heating / cooling signal from the thermostat. The receiver is OFF in manual mode (left switch is set to OFF and right switch is set to MANUAL).

3.3 Connection description


a) Connection diagram to gas boiler



b) Connection diagram to the pump / actuator



c) Connection diagram to the control box



Legend:



Boiler - Boiler connection*
- Boiler's contacts for ON/OFF thermostat (according to the boiler's instructions)



Pump





Valve actuator

Symbols explanation:

L, N - power supply 230V


COM, NO - voltage-free output



4. Before you start (first power on)


The thermostat is powered by two 1.5V AA alkaline batteries. Insert the batteries into the compartment under the front housing, paying attention to their polarity. The thermostat will start up showing the current software version and then go to the main screen.

1




PULL OFF THERMOSTAT SLIDE COVER.

2



INSERT THE BATTERIES, PAYING ATTENTION TO THEIR POLARITY!


3



PLACE AND SLIDE THERMOSTAT FRONT HOUSING.
THE LCD WILL TURN ON WHEN THE BATTERIES ARE INSERTED.



4.1 LCD icon description



1. Program timeline indicator

2. AM/PM

3. Clock

4. Day of the week indicator

5. Settings icon

6. Key lock function

7. Send a signal (pairing)* only E901RF

8. Holiday Mode

9. Low battery indicator
10. Frost Protection Mode

11. Comfort Mode

12. Economic Mode

13. Cooling status

14. Heating status

15. Temperature unit

16. Room / setpoint temperature

17. Temporary override


18. Program number

4.2 Button description

Button	Function
✓	Change the parameter value down
^	Change the parameter value up
D	Set the day of the week
H	Set the hour
M	Set the minutes
☀	Comfort temperature
🌙	Economic temperature / Holiday mode
AUTO	AUTO mode / Back button
PROG	Programming schedule / schedule type selection
✓	Confirm button
● Reset	Factory Reset

5. Time settings

Day/time settings are set using the D, H and M buttons. Please see steps below how to set time/day:



6. Operation


6.1 Manual mode

There are two temperature setpoint levels at our disposal. In manual mode chosen setpoint temperature level is maintained permanently until user changes operation mode or set a different temperature for each level.

-  - **Comfort Mode** - in this mode, the thermostat is to maintain a constant day temperature. When the temperature is set manually, e.g. 23°C, the thermostat maintains it until user switches to another operating mode or set a different temperature, e.g. 21°C.
-  - **Economic Mode** - in this mode, the thermostat is to maintain the reduced (night) temperature. When the temperature is set manually, e.g. 17°C, the thermostat maintains it until user switches to another mode or set a different temperature, e.g. 19°C.


6.1.1 Comfort mode

In the comfort temperature mode, the thermostat is to maintain a constant day temperature. The comfort temperature level is indicated by sun icon. To set the comfort temperature, see the steps below:



6.1.2 Economic mode


In the economic temperature mode, the thermostat is to maintain a reduced (night) temperature. This is to ensure a more economical operation of the heating system when, for example, you are away from home. The economic temperature level is indicated by the moon icon. To set the economic (night) temperature, see the steps below:



6.2 AUTO mode - two schedule types

- **AUTO Mode** - In the automatic mode, the thermostat maintains the set temperature according to the schedule selected by the user. You can choose from 2 types of schedule to manage the temperature during the week.

6.2.1 First type schedule



First type schedule mode is represented by timeline - 24 hours of a day. Empty „boxes” means hours where Economic (Moon) setpoint temperature will be maintained, black „boxes” means hours where Comfort (Sun) setpoint temperature will be maintained.

There are three different configurations in a schedule type 1:

- Two different programs (timelines), separate program for working days (Monday to Friday) and separate program for weekends (Saturday to Sunday)
- Individual programs (timelines) for each day of the week
- Same program (timeline) for the whole week

6.2.2 Second type schedule


Schedule type 2 enables the programming of 6 time intervals per day, with precision up to 10 minutes. Each of the 6 time intervals allows you to set a different temperature (schedule type 1 is limited to switching between two setpoint temperatures (SUN/MOON) at full hours time periods).

When creating a schedule type 2, you must define time and temperature setpoint (thermostat will start to maintain given setpoint temperature from given time setting). There are three different schedule configurations:


- Two different programs, separate program for working days (Monday to Friday) and separate program for weekends (Saturday to Sunday)
- Individual programs for each day of the week
- Same program for the whole week

Schedule of the second type example

TIME INTERVAL	DAYS OF THE WEEK (1 TO 5) MON-FRI	DAYS OF THE WEEK (6 TO 7) SAT-SUN
P1	Time 6:00 Temp. setpoint 21 °C	Time 6:00 Temp. setpoint 18°C
P2	Time 8:00 Temp. setpoint 14°C	Time 8:00 Temp. setpoint 20°C
P3	Time 11:00 Temp. setpoint 21°C	Time 11:00 Temp. setpoint 22°C
P4	Time 13:00 Temp. setpoint 14°C	Time 13:00 Temp. setpoint 20°C
P5	Time 16:00 Temp. setpoint 21°C	Time 16:00 Temp. setpoint 18°C
P6	Time 21:00 Temp. setpoint 14°C	Time 21:00 Temp. setpoint 14°C




6.2.3 Switching between schedules (AUTO Mode) type 1 and 2



Press any button to highlight the display.

Press and hold button for 5 seconds to enter to the schedule type selection.




Using or buttons choose type of schedule.

Confirm by button. Thermostat will return to the main screen saving chosen type of schedule (timeline will disappear if schedule type 2 is chosen).

6.3 First type schedule programming

6.3.1 Default program settings (1-3)

Within first type schedule mode there are 9 programs available. Programs 0 to 3 are factory-defined programs that cannot be changed. In this chapter you will find detailed information on the built-in factory programs (1-3) in the E901. These are pre-programmed time settings for the comfort and economy temperature that can be assigned to a selected day. To set up the program, see the steps below. The black squares on the timeline indicate the operating time for the comfort temperature mode, while the absence of them - for the economy temperature mode. Under the chart of each program, there is time (hour) when each mode is active. By default, program 1 is set for each day of the week.





PLEASE NOTE!
Programs should be set for all days of the week.

6.3.2 Choosing and programming user programs (4-9)

In order to program your own schedule its necessary to choose user program (4-9), because only user programs are editable. Then we must draw our own timeline using Sun/Moon buttons. Thermostat will be switching between two setpoint temperatures (Comfort and Economy) which are represented by Sun and Moon icons. Switching time is represented by timeline. See steps below how to programm your own schedule:


Example: below, program 4 will be defined for the MON - FR period with a comfort temperature from 8:00 to 16:00 and economic from 0:00 to 8:00 and 16:00 to 0:00. Programming starts from 0:00.





Then from 16:00 to 0:00 use the button several times to set the economic temperature.

Confirm by button.



The thermostat will proceed to program selection/editing for the next day/days period. Repeat steps 4-8. The thermostat will save changes and return to the main screen.




Please note!

Programs 0, 1, 2, 3 are factory set and cannot be edited.

Programs 4 to 9 are user defined (editable). One program (e.g. program 4) can be assigned to several days of the week. If this program is edited, the change affects all days to which given program is assigned to.


6.3.3 Frost Protection program setting

Frost protection mode (program 0) protects heating system against freezing. It is recommended to set this program if you are planning a long winter trip or if you do not heat up for a long time. The thermostat will maintain a constant temperature of 7°C, thus reducing energy consumption to a minimum.




Press any button to highlight the display.

Press button to enter the programming mode.



Select the week period using or buttons. Confirm by button.

Using or buttons choose program number 0. Confirm by button. The thermostat will proceed to program selection for the next day / days.



The thermostat will return to the main screen saving the set program. Snowflake - icon will appear on the display.




PLEASE NOTE!

In the frost protection mode, the temperature setpoint can't be changed and it is maintained constantly at 7°C.

6.3.4 Temporary override mode

When thermostat is running schedule (automatic mode) we can temporarily override it by new setpoint temperature:




6.4 Second type schedule programming

There are three different configurations in a schedule type 1:


- Two different programs (timelines), separate program for working days (Monday to Friday) and separate program for weekends (Saturday to Sunday)
- Individual programs (timelines) for each day of the week
- Same program (timeline) for the whole week

Exemplary schedule setting for working days and weekend:




6.4.1 Temporary override mode

When thermostat is running schedule mode we can temporarily override it by setting new work mode or setpoint temperature:




6.5 Party mode

In the party mode, the user can override schedule with comfort setpoint temperature by defined number of hours. To do this, follow the steps below:



The maximum duration of party mode is 9 hours. The temperature setpoint does not change during this mode. When party mode is enabled, pressing SUN, MOON or AUTO button twice (or 3 times if backlight is OFF) will disable it and thermostat will go back to appropriate mode.


To cancel active party mode (example):



6.6 Holiday mode


Holiday mode is a special program temperature setpoint which thermostat will maintain for specified days. During holiday mode thermostat is maintaining frost protection setpoint temperature. To set holiday mode, follow the steps below:

1




Press any button to highlight the display.

2




Press and hold  button for 3 seconds.

3




Use  or  buttons to select duration of the holiday mode (in days).

4




Confirm by  button.

5



Use  or  buttons to set temperature setpoint which thermostat will maintain for defined number of days.
Confirm by  button.


6



The thermostat is working in holiday mode. Plane icon is on the display.


TO STOP HOLIDAY MODE:

1




Press  button.

2



Confirm by  button.

3




The thermostat will return to the previous mode.

6.7 Key lock function


To LOCK the thermostat keys, follow the steps below:

1



Press and hold  and  buttons for 3 seconds.


2



A lock icon will appear on the screen.
The buttons on the thermostat have been locked.


To UNLOCK the thermostat keys, follow these steps:

1



Press and hold  and  buttons again for 3 seconds.

2



The lock icon will disappear from the screen.
The buttons on the thermostat have been unlocked.



The user has the option to set a PIN code, which he will have to enter each time he wants to unlock the buttons of the thermostat. To set a PIN code, go to parameter P12 (please refer to „Installer settings” section).

7. Pairing with the E901RX receiver

PLEASE NOTE!
E901RF thermostat is already paired with the receiver!


In order to pair the devices correctly, you must first prepare the receiver for synchronization!



If you want to re-pair the devices with each other, make sure that the receiver is disconnected from the power supply and the switches on it are in the AUTO and ON positions. Then connect the receiver to the power supply and wait for the green diode to glow continuously.


Move the left switch to the OFF position and back to the ON position with a quick motion.

The green LED will start blinking to confirm that the receiver has entered the pairing mode.




Press and hold ✓ button for 5 seconds.

Use ▼ button to select SYNC parameter.




Confirm by ✓ button.

Using ▲ or ▼ buttons choose YES and start the pairing process on a new frequency by pressing the ✓ button.



The thermostat started to send a signal to find the receiver (the symbol of the blinking antenna) and started the countdown with the number 10 (min). The pairing process may take up to 10 minutes.

When the green diode on the receiver lights up continuously, the devices have been paired on a new frequency.




The thermostat will display the message „good“, which means that the devices are successfully paired with each other.

The thermostat will return to the main screen.

WARNING! If the green diode on the receiver has not stopped blinking after 10 minutes, repeat the pairing process taking into account the distance between devices, obstacles and interference.


7.1 Transmission test

It is important to place the receiver and transmitter in places where nothing is interfering with the radio signal. The range of communication between the transmitter and the receiver in an open area is up to 60m. The radio transmission is influenced by many factors that can shorten the working distance, such as thick walls, drywall covered with aluminum foil, metal objects such as cabinets, general radio interference, etc. However, the range is sufficient for most domestic applications. It is recommended that the radio transmission between devices has to be tested before mounting the thermostat to the wall. The test can be performed by changing the set temperature, i.e. by activating or deactivating the heating.




Check that the thermostat is not sending a signal to heat.
Press any button to highlight the display.

Press button to enter comfort temperature mode.
The sun icon should be visible on the display.




Using or buttons set new comfort temperature value.

Confirm by button or wait until the thermostat will approve your choice itself and display the main screen.




The thermostat started sending a heating signal when the screen went blank, which was signaled by the antenna symbol.



The flame icon will start to animate, which means that the thermostat is sending a signal to heat.



Check that the orange LED on the receiver is on. If so, it means that the communication between the devices is correct.



Set the temperature setpoint a few degrees lower than the room temperature by repeating steps 1 to 5. Wait a few seconds. The flames icon should stop animating...




...and the orange LED on the receiver should go out.

Please note:

If the orange LED does not turn on / off as indicated by the transmitter flame icon, try moving the transmitter closer to the receiver and repeat all steps from the beginning.
If it still doesn't work, try the pairing process again.

8. Installer settings




INSTALLER PARAMETERS:

Pxx	Function	Value	Description	Default value
P01	Heating/Cooling mode selection	❄️	Cooling	🔥
		🔥	Heating	
P02	Control method temperature	1	SPAN ±0,25°C	1
		2	SPAN ±0,5°C	
		3	TPI for Underfloor Heating	
		4	TPI for Radiators	
		5	TPI for Electrical Heating	
P03	Display temperature resolution	0,5°C	This parameter specifies the accuracy of the displayed (measured) temperature.	0,5°C
		0,1°C		
P04	Offset temperature	-3.5°C to + 3.5°C	If the thermostat indicates wrong temperature, you can correct it by ± 3.5°C	0°C
P05	Relay type	NO	Normally Open type of relay	NO
		NC	Normally Closed type of relay	
P06	Clock format	24h	24 hour	24h
		12h	12 hour	
P07	Temperature Scale	°C	Celsius	°C
		°F	Fahrenheit	
P08	Minimum setpoint	5°C - 34,5°C	Minimum heating / cooling temperature that can be set	5°C
P09	Maximum setpoint	5,5°C - 35°C	Maximum heating / cooling temperature that can be set	35°C

Pxx	Function	Value	Description	Default value
P10	Key sound	NO	Off	YES
		YES	On	
P11	PIN Code	NO	Disabled	NO
		PIN	Enabled	
P12	Require a PIN to unlock the keys every time	NO	Function disabled	NO
		YES	Function enabled	
CLR	Clear settings factory reset	NO	No action	NO
		YES	Factory Reset	
*Only for E901RF thermostat				
SYNC	Pairing function with RXRT510 receiver (SYNC)	NO	Pairing disabled	NO
		YES	Pairing enabled	

9. User settings reset

There is a small hole to the right of the OK button. This is the reset button. Pressing the reset button will restore the default values in the user settings (i.e. time, schedule).




 Please note:

Do not use a pencil to press the reset button as the graphite build-up on the stylus can short-circuit and damage the thermostat. In environments with very strong electrostatic discharge (+/- 8KV), the product may not function as under normal conditions. So the device may need to be reset.

10. Clear settings - factory reset


To perform factory reset (which will remove all user/installer settings), use the CLR parameter from installer parameters menu. After confirming the parameter, the thermostat will restore the default settings.

1




Press any button to highlight the display.

2




Press and hold  button for 5 seconds.

3



Use  or  buttons to move to CLR parameter.

4



Confirm the new parameter value with the  button.

11. Cleaning and Maintenance

The **E901RF thermostat** requires no special maintenance. Periodically, the outer casing can be wiped clean using a dry cloth (please DO NOT use solvents, polishes, detergents or abrasive cleaners, as these can damage the thermostat). There are no user serviceable parts within the unit; any servicing or repairs could only be carried out by **ENGO Controls** or their appointed agents.

12. Technical Informations

Transmitter's power supply	2 x AA batteries
Receiver's power supply	230V AC 50 Hz
Rating max	16 (5) A
Output signal	NO/COM relay
Temperature range	5 - 35°C
Display temperature accuracy	0.1°C or 0.5°C
Control algorithm	TPI or Hysteresis: $\pm 0.25^{\circ}\text{C}$ and $\pm 0.5^{\circ}\text{C}$
Communication	Wireless, 868Mhz
Dimension [mm]	transmitter: 150 x 84 x 22 receiver: 96 x 96 x 27



13. Warranty

ENGO Controls warrants this product to be free from any defects in material or workmanship and to perform as specified for a period of five years from the date of installation. ENGO Controls reserves the sole responsibility for breach of this warranty by repairing or replacing the defective product. This product includes software that matches the distributor’s identification at the time of sale. The manufacturer / distributor provides a guarantee covering all functions and specifics of the product in accordance with this marking. The distributor’s warranty does not cover the correct operation of the functions and features available as a result of a product software update.

Customer Name:
Customer Address:
..... Post Code:
Tel No: Email:

Company Name:
Tel No: Email:
Installation Date:
Installer Name:
Installer Signature:





Ver. 5

Date of issue: X 2024

Power supply: 2xAA batteries

Producer:

ENGO CONTROLS Sp z o.o. Sp. k.

43-262 Kobielice

4 Rolna St.

Poland

www.engocontrols.com