ingenico

AXIUM RX7000

Deliver value-added services in multilane retail stores with a smart and customizable commerce solution





Based on Android 11, the AXIUM RX7000 is designed for advanced check out services and an intensive use in full security.

The power of Android 11. Harness the power of the Appstore.

Powerful processing to increase speed and output

- Boosted memory (Up to 4GB RAM 32GB FLASH)
- High speed processor (ARM Quad-core cortex A55)

Large, up to 5.5" HD IPS and ergonomic interface

Powerful cameras

- Front camera (5MP)
- Optional rear camera (0.3MP)

Raising the bar on security

- PCI PTS v6
- Overlay detection
- Abnormal cable removal detection which can generate an alert to inhibit the terminal
- PCI compliant privacy pin shield



Specifications

Processor	Application processorCrypto processor	64-bit ARM, Cortex Quad-core A55, 1.8GHz 32-bit ARM, security core SC300, 192MHz	~
Memory	Internal External	16GB Flash,2GB RAM32GB Flash 4GB RAMMicroSD Card slot	Option
OS	Android	Android 11 Security OS	~
Card readers	Magnetic card reader Smart card reader Contactless	Support ISO 1/2/3 track data, bi-directional swiping Backlit indicator EMV L1 and ISO7816 spec compliant Backlit indicator EMV Contactless L1 3.0 spec compliant; support ISO / IEC 14443 Type A / B Backlit logo + 4 transaction LEDs	· · · · · · · · · · · · · · · · · · ·
SAM	SAM slots	• 2 slots	~
Display & Touchscreen	Color / capacitive multi-touch Finger & stylus	 5.5"HD IPS, 1280 x 720 px, 16:9 1000K lifespan signature 	~
Keypad	Virtual screen keys Physical keys	Menu, Home, Back15 keys, raised markings, backlit	~
Terminal wake-up	Wake-up gesture	Double click capacitive screen to wake up the terminal system By command send from the ECR	~
Audio	SpeakerAudio JackBuzzer	Dual channels	· ·

Connectivity	WiredWireless	 Ethernet 10/100 base T WiFi IEEE8.2.11 a/b/g/n 2.4G and 5G Bluetooth 5.0, support BLE 	· ·
Connections	• IDMI	Power USB Host USB Device RS232 Ethernet	* * * * * * * * * * * * * * * * * * * *
Data capture	Front camera Rear camera	5M pixels , autofocus, for photo/video 0.3 pixels, fixed focus camera, for code scanning	Option
Privacy shield	Standard privacy shield	PCI compliant	~
Stand Mounting	Universal Payment Mount	Standardized mounting pattern	~
Size	Terminal only	• 5.9 x 6.4 x 1.1" (151 x 163 x 27mm)	~
Weight	Terminal only	• 15.5oz (468g)	~
Security	PCI Overlay detection Anti-removal Anti-theft	PCI PTS V6 compliant Proximity sensor on surface of the keyboard* Active connector removal Kensington lock receptacle	Option
Environment	Operating Temperature Storage Temperature Operating Humidity	• 14°F to 122°F (-10°C to +50°C) • -4°F to 158°F (-20°C to +70°C) • 10% to 90% non-condensing	· · · · · · · · · · · · · · · · · · ·
Accessories	Signature stylusPOE BoxFlat stand mount	Passive stylus + holder + cord Power over Ethernet Desktop use	Option Option Option