

Application

A perfectly shaped sphere is one of the most important elements of design. As a fundamental geometric shape, the form is pure and timeless. These captivating pendant luminaires complement any design aesthetic, making them well suited for a multitude of space types. Also available with an impact resistant acrylic diffuser for special applications, add P as suffix.

Materials

Hand-blown opal glass  
Aluminum structure  
White or black connecting cable

NRTL listed to North American Standards, for interior use only

Weight: 11.0lbs.

Electrical

|                           |                            |
|---------------------------|----------------------------|
| Operating voltage         | 120-277VAC                 |
| Minimum start temperature | -30° C                     |
| LED module wattage        | 34.5 W                     |
| System wattage            | 40.5 W                     |
| Controllability           | 0-10V dimming down to 0.1% |
| Color rendering index     | Ra > 80                    |
| Luminaire lumens          | 3544 lm                    |
| LED service life (L70)    | 60000hrs                   |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

|             |                      |
|-------------|----------------------|
| White (.1)  | Stainless steel (.2) |
| Chrome (.3) | Brass (.4)           |

Type:


BEGA Product:

Project:

Modified:

Available options

|     |                    |
|-----|--------------------|
| FSC | Fusing             |
| LPC | Low profile canopy |



| Pendant · Opal glass |        |        |    |
|----------------------|--------|--------|----|
|                      | LED    | A      | B  |
| B56591               | 34.5 W | 15 3/4 | 81 |