

# ID TECH TLV Tag Reference Guide



**ID TECH** 

10721 Walker Street, Cypress, CA 90630-4720 Tel: (714) 761-6368 Fax (714) 761-8880 www.idtechproducts.com support@idtechproducts.com



#### © 2020 ID TECH. All rights reserved

ID TECH 10721 Walker Street, Cypress, CA 90630 Voice: (714) 761-6368

**Fax**: (714) 761-8880

Visit us at http://www.IDTECHproducts.com

The information contained herein is provided to the user as a convenience. While every effort has been made to ensure accuracy, ID TECH is not responsible for damages that might occur because of errors or omissions, including any loss of profit or other commercial damage, nor for any infringements or patents or other rights of third parties that may result from its use. The specifications described herein were current at the time of publication but are subject to change at any time without prior notice.

ID TECH and Value through Innovation are trademarks of International Technologies & Systems Corporation. Other trade names mentioned herein are the trademarks of their respective holders.

#### **Revision History**

Date	Revision	Changes	Author
А	07/28/2016	First edition of document.	KT
В	07/28/2016	Removed most vendor names.	KT
		Edits for consistency.	
		Eliminated duplicate tags and empty rows.	
В	07/29/2016	SmartSoft changed to Smart Tap.	KT
		"Added for" removed.	
		Removed "Tentative" tags.	
		Fixed formatting issues.	
С	09/20/2016	Added new tags DFEF4B and subsequent.	KT
D	11/18/2016	Added Appendix for DFEE1E.	KT
		Added new tags DFEF53 to DFEF65.	
		Added new tags FFEE12 to FFEE17 and FFEE69.	
Е	03/06/2017	Added tag DFEE25 (Response Codes), with its own Appendix.	KT
F	06/12/2017	Added Appendix D on tag DFEE1B usage.	KT
		Added tags DFEF69 to DFEF7E.	
G	05/15/2018	Added new tags in the DFEDxx range.	KT
		Added new EMV status codes in Appendix.	
Н	04/15/2019	Corrected appendix reference in DFEE1B comments.	СВ
	07/03/2019	Added 0x50, 0x36 to Appendix C.	
К	12/31/2019	Reinsertion of revision history.	СВ
		Changed Tag FFEE1F to DFEE02 to indicate TLV Contactless Error Code.	
		Miscellaneous other style updates.	
L	01/21/2020	Updated DFEF1A name and description; the tag is a SmartTap delimiter.	СВ
М	03/13/2020	Updated DFEE51 description: KSN of online PIN DUKPT. The previous version	
		of DFEE51 is still active as a two-byte tag, DF51.	
N	11/03/2020	Removed the following tags: DFEF63, DFEF65, DFEF66, DFEF67, DFEF68,	СВ
		DFEF69, DFEF6A, DFEF6B, DFEF6C, DFEF6D	

### **Table of Contents**

1. INTRODUCTION	5
1. INTRODUCTION	
1.2. Abbreviations	5
2. CONSTRUCTED VERSUS PRIMITIVE TAGS	5
3. PRIMITIVE TAG	ε
1: MSR ONLY ENABLED. 0: MSR ONLY DISABLED	
FOR CODE DFEF25 = 5038 VIEW SECTION 3.1 FOR MORE INFORMATION	
3.1. Note for Tag DFEE25	39
3.2. Note for Tag DFEF36	42
4. CONSTRUCTED TAGS	43
5. APPENDIX A: CONTACT EMV CONFIGURATION VALUES (TAG DELETE)	46
6. APPENDIX B: ENCRYPTED TRACK DATA STATUS (TAG DFEF4B)	49
6.1. Compressed Numeric Elements	50
7. APPENDIX C: CONTACT RESPONSE CODE (TAG DFEE25)	5
8. APPENDIX D: DFEF61 (CONTACT EMV STATUS CODES)	54
9. APPENDIX E: TAG DFEE1B	57

#### 1. Introduction

This document describes ID TECH proprietary TLV tags as used in a variety of products. It does not include industry standard EMV tags defined by EMVCo.

#### 1.1. Format

b = binaryn = numerican = alpha-numericcn = compressed numeric

**Note**: All tag payloads should be assumed to be in raw binary format unless otherwise specified.

#### 1.2. Abbreviations

**ACT** Activate Transaction

**AR** ID TECH Advanced Reader Series Firmware

**Cfg** Config

**CL** Contactless

**CONAIDS** Configurable AIDs

**GR** ID TECH Global Reader Series Firmware

**NEO** ID TECH NEO-Series

## 2. Constructed Versus Primitive Tags

We distinguish between tags that can wrap other tags and ordinary tags that cannot. When TLVs are nested the outer (wrapper) tag is said to be constructed. The Value of the associated "wrapper" TLV is one or more TLVs.

Tags are specified in accordance with **Basic Encoding Rules** (BER-TLV), per Annex B, Book 3 of EMV 4.3, and obey the following conventions:

- All ID TECH proprietary tags will be 3 bytes long.
- Byte 1 will be FF if constructed or DF if primitive.
- Byte 2 has bit 8 set.
- Byte 3 does not have bit 8 set but does have at least one other bit set.

Example: Vags.

# 3. Primitive Tag

Tag	Name	Focus	Description	Format	Comments
DF891C	Interac Retry Limit	Vendi	Configured value	N1	Interac Card Used
Dros ic	interac Netry Limit	vendi	for the total	INI	mterat card 03ed
			number of tap		
			attempts during an		
			Interac Mobile		
			Debit (NFC)		
			application		
			transaction.		
DFED01	Merchant Category	SmartTap 2.1	e. a. isaeci oi ii		
DFED02	POS	SmartTap 2.1			
	Capabilities Bitmaps	Ja.c.ap			
DFED03	Retry Times	SmartTap 2.1			
DFED04	Select OSE Support	SmartTap 2.1			
DFED05	Skip Second Select	SmartTap 2.1			
	Support				
DFED06	Stop Payment if Smart	SmartTap 2.1			
	Tap 2.1 Failed Support	·			
DFED07	Pre-Signed Support	SmartTap 2.1			
DFED08	Security Option	SmartTap 2.1			Reserve for auto poll.
DFED09	Service Type	SmartTap 2.1			Reserve for auto poll.
DFEDOA	Determines if Fallback	QuickChip	Controls the output	b-1	00 - Switch is OFF, not output
	Reason should be		Fallback Reason.		fallback.
	output.		The default switch		Reason 01 - Switch is ON, output
			is OFF.		fallback reason.
DFEDOB	Debug Flag for Interac	Vendi	Upon card	b-1	<b>Bit 0</b> - Enabled debug function.
			termination,		Bit 1- Disable "Enter PIN"
			perform all the		Message.
			steps of the card		
			deactivation and		
			send all card		
			data to the host.		
DFEDOC	Default Transaction	VP3300	This tag is setting	b-1	
	Type for Mastercard		in Group0. When		
			the Active		
			command does		
			not have tag 9C,		
			the reader will use		
			the tag to replace		
			9c.		
DFEDOD	Default Transaction	VP3300	This tag is setting	b-1	
	Type for Visa Card		in Group0. When		
			the Active		
			command does not		
			have tag 9C,		
			the reader will use		
			the tag to replace		
			9c.		

Tag	Name	Focus	Description	Format	Comments
DFEDOE	Default Transaction	VP3300	The tag is set in	b-1	
	Type for Amex card		Group0.The tag is		
			set in Group0.		
			When the Active		
			command does not		
			have tag 9C, the		
			reader will use the		
DFEDOF	Default Transaction	VP3300	tag to replace 9c. This tag is setting	b-1	
DEEDOF	Type for Discover card	VF3300	in Group0. When	D- 1	
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		the Active		
			command does not		
			have tag 9C, the		
			reader will use the		
			tag to replace 9c.		
DFED10	Default Transaction	VP3300	This tag is setting	b-1	
	Type for Interac card		in Group0. When		
			the Active		
			command does not		
			have tag 9C, the reader will use the		
			tag to replace 9c.		
DFED11	Enable Non- EMV tag	KIII	This tag is set in	b-1	0: Disable
	2.145.6 115.1 2.111 446		Group0. The		1: Enable
			default is 1.		
DFED12	Log tag for MCL	MCL Lab Test			
DFED13	Log tag for MCL	MCL Lab Test			
DFED14	Log tag for MCL	MCL Lab Test			
DFED15	Log tag for MCL	MCL Lab Test			
DFED16	Log tag for MCL	MCL Lab Test			
DFED17	Log tag for MCL	MCL Lab Test			
DFED18	Poll Mode	Vendi	Has a one-byte	b	Value = 00: Auto-Poll Value = 01:
			payload and sets		Poll on Demand
			Vendi Poll Mode		
DFED19	Enable LOG	MCLL	(see Comments).		Value 00 Biankla LOCValue
טרבט ופ	Enable LOG	MCL Log Enable	This tag is used to enable and disable		Value = 00: Disable LOG Value = 01: Enable LOG
		LIIADIE	log. Send with ACT.		or. Enable Lod
DFED20	Company Name	Augusta	Is used for meta	b - 16	Able to store name of the
	, ,		data for the		company who configured the
			company's name.		device.
DFED21	Configure Date	Augusta	Able to track the	b - 3	Format: yymmdd
			date the device		
		_	was configured.		
DFED22	Current Configuration	Augusta	Stores unique serial	b - 32	Freeform tag. Used based on the
	Version		number and		customer preference.
			versioning information used		
		<u> </u>	by the company	L	

Tag	Name	Focus	Description	Format	Comments
DFED23	Quick Chip: ApplePay				
	Terminal Application				
	Version Number				
DFED24	Quick				
	Chip: ApplePay				
	Terminal Capabilities				
	Information				
DFED25	Quick				
	Chip: ApplePay VAS				
	Filter				
DFED26	Quick				
	Chip: ApplePay VAS				
	Protocol				
DFED27	SmartTap Delimiter for				
	Service Objects				
DFED28	SmartTap Service Type				
	Requests				
DFED74	MC DE Log	VP8800	Contains C-APDU	b	
	CAPDU Entry		bytes for logging in.		
DFED75	MC DE Log	VP8800	Contains R-APDU	b	
	RAPDU Entry		bytes for logging in.		
DFED76	MC DE Logging Enable	VP8800	Indicates Data	b-1	
			Exchange APDU		
			Logging is enabled		
			for Mastercard.		
DFED77	ZIP PPSE Event	VP8800	Defines ZIP's	b - 4	See Combined Selection
	Handling		response to PPSE		Supplement – PPSE Failure Mode
	IDTECH PROFE	\/Doogo	events.		spec.
DFED78	IDTECH PPSE Event	VP8800	Defines IDTECH's	b - 4	See Combined Selection
	Handling		response to PPSE		Supplement – PPSE Failure Mode
D=====	C   DDCEE	VPOOCO	events.		spec.
DFED79	Custom PPSE Event	VP8800	Defines the	b - 4	See Combined Selection
	Handling		Customer response		Supplement – PPSE Failure Mode
DEEDZA	Masternal DDCE	VDOOO	to PPSE events.	b - 4	spec.
DFED/A	Mastercard PPSE	VP8800	Defines the	D - 4	See Combined Selection Supplement – PPSE Failure Mode
	Event Handling		Mastercard		
			response to PPSE events.		spec.
DFED7B	Visa PPSE Event	VP8800	Defines the Visa	b - 4	See Combined Selection
DED/B	Handling	VF0000	response to PPSE	0-4	Supplement – PPSE Failure Mode
	ו ומווטווווצ		events.		spec.
DFED7C	Amex PPSE Event	VP8800	Defines the Amex	b - 4	See Combined Selection
טיינים ו	Handling	11 0000	response to PPSE		Supplement – PPSE Failure Mode
	- Tanamia		events.		spec.
DFED7D	Discover PPSE Event	VP8800	Defines the	b - 4	See Combined Selection
5. 25,5	Handling	1, 5555	Discover response		Supplement – PPSE Failure Mode
			to PPSE events.		spec.
DFED7E	Interac PPSE Event	VP8800	Defines Interac's	b - 4	See Combined Selection
	Handling	1. 5555	response to PPSE		Supplement – PPSE Failure Mode
			events.		spec.
		<u> </u>	EVELICS.	I .	sher:

Tag	Name	Focus	Description	Format	Comments
DFED7F	Default DRL  ApplePay VAS Protocol	VP8800 Apple	Default Dynamic Reader Limits for XP 3.1	18 bytes b-1	Contains 6 bytes each of Contactless Terminal Floor Limit, Transaction Limit, and CVM Required Limit. Data from DF8123, DFEE34, and DF8126. This is a proprietary TLV always
			used to select between Full VAS protocol and URL VAS protocol.		enclosed in the ApplePay VAS collective TLV FFEE06
DFEE02	ApplePay VAS Failure Report	Apple	ApplePay VAS is used to return the Error Code, SW1-SW2, RFState for a Failed VAS transaction embedded in the FFEE06.	b-4	This is a proprietary TLV always enclosed in the ApplePay VAS collective TLV FFEE06
DFEE02	TLV Contactless Error Code Table	Unipay III/ Kiosk III	Error Code for Contactless.	4 bytes	Byte 1: Error Code (Error Code giving the reason for the failure). Byte 2: SW1 (Value of SW1 returned by the Card (SW1SW2 is 0000 if SW1 SW2 not available)). Byte 3: SW2 (Value of SW2 returned by the Card (SW1SW2 is 0000 if SW1 SW2 not available)). Byte 4: RF State Code (RF State Code indicating exactly where the error occurred in the Reader-Card transaction flow).
DFEE03	ViVOtech Proprietary Suite	MVS	MVS		
DFEE04	TAC Online	SmartTap	Used by SmartTap Kernel for Terminal Configuration (set in and picked up from the Contact Group).		
DFEE05	Threshold Value for Biased Random Selection.	SmartTap	Being used by Smart Tap Kernel for Terminal Configuration (set in and picked up from the Contact Group).		
DFED06	Stop Payment if Smart Tap 2.1 Failed Support	SmartTap 2.1			
DFED07	Pre-Signed Support	SmartTap 2.1			
DFED08	Security Option	SmartTap 2.1			Reserve for Auto Poll.
DFED09	Service Type	SmartTap 2.1			

Tag	Name	Focus	Description	Format	Comments
DFEDOA	Fallback Reason to	QuickChip	The switch		
	Output is determined	,	controls		
	by a Switch.		the Output Fallback		
	,		reason. The default		
			switch is OFF.		
DFEDOB	Debug Flag for Interac	Vendi	When the card is		
	0 0		terminated, it is		
			necessary to		
			perform all the		
			steps of the card		
			and send all card		
			data to the host.		
DFEDOC	Default Transaction	VP3300	This tag is setting	b-1	
	Type for Mastercard		in GroupO. When		
			the Active		
			command does		
			not have tag 9C,		
			the reader will		
			use the tag to		
			replace 9c.		
DFEDOD	Default Transaction	VP3300	This tag is setting	b-1	
	Type for Visa Card		in Group0. When		
			the Active		
			command does		
			not have tag 9C,		
			the reader will		
			use the tag to		
			replace 9c.		
DFED0E	Default Transaction	VP3300	This tag is setting	b-1	
	Type for AmEx Card		in Group0. When		
			the Active		
			command does		
			not have tag 9C,		
			the reader will		
			use the tag to		
			replace 9c.		
DFEDOF	Default Transaction	VP3300	This tag is setting	b-1	
	Type for Discover card		in Group0. When		
			the Active		
			command does		
			not have tag 9C,		
			the reader will		
			use the tag to		
			replace 9c.		

Tag	Name	Focus	Description	Format	Comments
DFED10	Default Transaction Type for Interac card	VP3300	This tag is setting in GroupO. When the Active command does not have tag 9C, the reader will use the tag to replace 9c.	b-1	
DFED11	Enable Non- EMV tag	KIII	This tag is set in Group0. Default is 1.	b-1	0: Disable 1: Enable
DFED12	Log tag for MCL	MCL Lab Test			
DFED13	Log tag for MCL	MCL Lab Test			
DFED14	Log tag for MCL	MCL Lab Test			
DFED15	Log tag for MCL	MCL Lab Test			
DFED16	Log tag for MCL	MCL Lab Test			
DFED17	Log tag for MCL	MCL Lab Test			
DFED18	Poll Mode	Vendi	One-byte payload. Sets Vendi Poll Mode (See comments).	Ь	Value = 00: Auto-Poll Value = 01: Poll on Demand
DFED19	Enable LOG	MCL Log Enable	This tag is used to enable and disable log. Send with ACT.		Value = 00: Disable LOG Value = 01: Enable LOG
DFED20	Company Name	Augusta	Use for meta data for company name.	b - 16	Able to store name of company who configured the device.
DFED21	Configure Date	Augusta	Able to track the date the device was configured.	b - 3	Format: yymmdd
DFED22	Current Configuration Version	Augusta	The company uses the store's unique serial number + versioning information.	b - 32	Freeform Tag: Used based on the customer preference.
DFED23	Quick Chip: ApplePay Terminal Application Version Number				
DFED24	Quick Chip: ApplePay Terminal Capabilities Information Quick				
	Chip: ApplePay VAS Filter				
DFED26	Quick Chip: ApplePay VAS Protocol				

Tag	Name	Focus	Description	Format	Comments
DFED27	SmartTap Delimiter for				
	Service Objects				
DFED28	SmartTap Service Type				
	Requests				
DFED74	MC DE Log	VP8800	Contains C-APDU	b	
	CAPDU Entry		bytes for logging		
DFED75	MC DE Log	VP8800	Contains R-APDU	b	
DFED76	RAPDU Entry	VP8800	bytes for logging Indicates Data	b - 1	
DFED/6	MC DE Logging Enable	VP6600	Exchange APDU	U - 1	
			Logging is enabled		
			for Mastercard		
DFED77	ZIP PPSE Event	VP8800	Defines the ZIP	b - 4	See Combined Selection
	Handling		appropriate		Supplement – PPSE Failure Mode
			response to PPSE		spec.
			events		
DFED78	IDTech PPSE Event	VP8800	Defines the IDtech	b - 4	See Combined Selection
	Handling		appropriate		Supplement – PPSE Failure Mode
			response to PPSE events		spec.
DFED79	Custom PPSE Event	VP8800	Defines the	b - 4	See Combined Selection
DFED/9	Handling	VF8800	Customer	0-4	Supplement – PPSE Failure Mode
			appropriate		spec.
			response to PPSE		
			events		
DFED7A	Mastercard PPSE	VP8800	Defines the	b - 4	See Combined Selection
	Event Handling		Mastercard		Supplement – PPSE Failure Mode
			appropriate		spec.
			response to PPSE events		
DFED7B	Visa PPSE Event	VP8800	Defines the Visa	b - 4	See Combined Selection
512575	Handling	V1 0000	appropriate	D 4	Supplement – PPSE Failure Mode
			response to PPSE		spec.
			events		<u> </u>
DFED7C	Amex PPSE Event	VP8800	Defines the Amex	b - 4	See Combined Selection
	Handling		appropriate		Supplement – PPSE Failure Mode
			response to PPSE		spec.
	D' DD55.5	L/DOOG 5	events		
DFED7D	Discover PPSE Event	VP8800	Defines the	b - 4	See Combined Selection
	Handling		Discover		Supplement – PPSE Failure Mode
			appropriate response to PPSE		spec.
			events		
DFED7E	Interac PPSE Event	VP8800	Defines the Interac	b - 4	See Combined Selection
	Handling		appropriate		Supplement – PPSE Failure Mode
	·		response to PPSE		spec.
			events		

Tag	Name	Focus	Description	Format	Comments
DFED7F	Default DRL	VP8800	Default Dynamic Reader Limits for XP 3.1	18 bytes	Contains 6 bytes each of Contactless Terminal Floor Limit, Transaction Limit, and CVM Required Limit. Data from DF8123, DFEE34 and DF8126.
DFEE01	ApplePay VAS Protocol	Apple	ApplePay VAS, used to select between Full VAS protocol and URL VAS protocol.	b-1	This is a proprietary TLV always enclosed in the ApplePay VAS collective TLV FFEE06
DFEE02	ApplePay VAS Failure Report	Apple	Before ApplePay VAS, returned the Error Code, SW1- SW2, RFState for a failed VAS transaction embedded in the FFEE06.	b-4	The proprietary TLV is enclosed in the ApplePay VAS collective TLV FFEE06
DFEE03	ViVOtech Proprietary Suite	MVS	MVS		
DFEE04	TAC Online	SmartTap	Used by Smart Tap Kernel for Terminal Configuration (set in and picked up from Contact Group).		
DFEE05	Threshold Value for Biased Random Selection.	SmartTap	Used by Smart Tap Kernel for Terminal Configuration (set in and picked up from Contact Group).		
DFEE06	Target Percentage for Random Transaction Selection	SmartTap	Used by Smart Tap Kernel for Terminal Configuration (set in and picked up from Contact Group).		
DFEE07	Maximum Target Percentage for Random Transaction Selection	Smart Tap	Used by Smart Tap Kernel for Terminal Configuration (set in and picked up from Contact Group).		

Tag	Name	Focus	Description	Format	Comments
DFEE08	RID (in AR)	ACT	The RID to be used		
			for the transaction.		
			Passed from PPSE		
			to the AID module		
			in the ACT		
			parameters.		
DFEE09	Last 4 digits of	Discover	Discover Zip (DGI		
DEECOS	•	Discovei	'7006')		
	Primary		7006)		
	Account				
D===0.0	Number (PAN)				
DFEEOA	Group 0	Kiosk III	Value = 00: not		
	Initialize Flag		initialized. (If the		
			tag is not found		
			or Value is not 1,		
			the reader will		
			initialize group 0		
			with default		
			setting		
			automatically		
			when the power		
			cycle is on) Value		
			= 01: Initialized		
DFEE0B	Issuer Script Results	ACT, Smart	Used in ViVOtech 2		
	·	Тар	Serial Interface		
			(Activate Trans and		
			Continue Trans		
			Response).		
			Also being used by		
			Smart Tap Kernel		
			for Terminal		
			Configuration		
			(set in and picked		
			up from Contact		
			Group).		
DFEEOC	Iccupr Script Doculto	Contact	May be used in the		
D. L.LOC	Issuer Script Results	CUITACL	future by		
			Contactless.		
DFEEOD	Force Transaction	ACT, Smart	Used in ViVOtech 2		
DEECO	Online	Tap	Serial Interface		
	Offilitie	ιαμ			
			(Activate		
			Transaction		
			Command.		
			Also being used by		
			Smart Tap Kernel		
			for Terminal		
			Configuration		
			(set in and picked		
			up from Contact		
			Group).		

Tag	Name	Focus	Description	Format	Comments
DFEE0E	Default DDOL	Smart Tap	Used by Smart Tap		
		·	Kernel for Terminal		
			Configuration (set		
			in and picked up		
			from Contact		
			Group).		
DFEEOF	Enable Revocation List	Smart Tap	Used by Smart Tap		
	Processing		Kernel for Terminal		
			Configuration (set		
			in and picked up		
			from Contact		
			Group).		
DFEE10	Terminal Languages	Smart Tap	Used by Smart Tap		
	Supported		Kernel for Terminal		
			Configuration (set		
			in and picked up		
			from Contact		
			Group).		
DFEE11	Enable Transaction	ACT, Smart	Used in ViVOtech 2		
	Logging	Тар	Serial Interface		
			(Activate		
			Transaction		
			Command). Also		
			used by Smart Tap		
			Kernel for Terminal		
			Configuration.		
DFEE12	KSN	Cfg	Transaction Result		Encryption Format data.
			(response):		(Reserved for existing products)
			TDES/AES mode		FFEE12 is used by Kiosk3, Vendi
			Data encryption		and Unipay3/Unipay1.5.
			Key (DUKPT Key) -		
			KSN, 10 bytes		
DEEE43	TAC Defects	C	Value.		
DFEE13	TAC Default	Smart Tap	Used by Smart Tap		
			Kernel for Terminal		
			Configuration (picked up from		
			Contact Group).		
DFEE14	TAC Denial	Smart Tap	Used by Smart Tap	<del>                                     </del>	
J. L. 14	The Defila	Jinaic Tap	Kernel for Terminal		
			Configuration (set		
			in and picked up		
			from Contact		
			Group).		
DFEE15	Application Selection	Contact	Contact L2		Contact EMV L2
	Indicator		command		
DFEE16	DUKPT Key or MKSK	Contact	Contact L2	1	Contact EMV L2
	Select for Online PIN		command		
	Encrypted				
	, , p	1	1	I	

Tag	Name	Focus	Description	Format	Comments
DFEE17	ICC Terminal Entry	Contact	Contact L2		Contact EMV L2. This configures
	Mode		command		the output value for 9F39, which
					is the POS entry mode.
					If 9F39 is included in the DFEF5A
					tag, expect to see the contents of
					DFEE17 returned.
DFEE18	MSR Terminal Entry	Contact	Contact L2		Contact EMV L2
	Mode		command		
DFEE19	Online DOL	Contact	Contact L2		Contact EMV L2
			command		
DFEE1A	Output Data Element	Contact	Contact L2		Contact EMV L2
			command		
DFEE1B	Authorization Request	Contact	Contact L2		Contact EMV L2 See Appendix E.
D===46	Data Elements	C.C.	command		
DFEE1C	LCD Font Size	Cfg			
DFEE1D	Sensitive Data Mask	Cfg	NEO (K3, Vendi,		<b>byte1</b> : Pre-PAN clear datalength,
			Unipay III,		range 0-6, default 4
			Unipay1.5) and AR		<u>byte2</u> : Post-PAN clear data
			(VendIII) Secure		length, range 0-6, default 4
			Mode		<u>byte3</u> : Mask Character for <b>ASCII</b>
			Configuration of		Code Value, range 0x20-0x7E,
			encrypting and		default 0x2A(*)
			masking data		<u>byte4</u> : Mask Character for Hex
					Code Value, range 0x0A-0x0F,
					default 0x0C <b><u>byte5</u></b> : Expire date
					output option, 0x30=Mask,
					0x31=NotMask, default 0x31.
DFEE1E	Terminal Configuration	Contact	Contact L2		Contact EMV L2 config. See
					Appendix A.
DFEE1F	Issuer Script Limit	Contact	Contact L2		Contact EMV L2
					Control issuer script MAX limit.
DFEE20	ICC Power on Waiting	Contact	Contact L2		Contact EMV L2
<b></b>	Time		6		Detect card in waiting time.
DFEE21	ICC L1 Data	Contact	Contact L2		Contact EMV L2
	Transaction Waiting				Do ICC L1 data exchange waiting
DEEESS	Time	Contact	Contact 13		time.
DFEE22	Driver (Menu, Get Pin,	Contact	Contact L2		Contact EMV L2
	Get Msr) Timeout				3 Values: Timeout for Menu
					(Seconds), Timeout for Get PIN
					(Seconds), and Timeout for Get
DEEE22	MCD all track data	Contact	Contact L2		MSR (Seconds)  Contact EMV L2
DFEE23	MSR all track data	Contact	CONTACT LZ		When fallback to MSR, MSR data
					· ·
DEEE3/	Force Accortance	Contact	Contact 1.3		will store the tag.
DFEE24	Force Acceptance	Contact	Contact L2		Contact EMV L2
DFEE25	ICC Response Code	NEO			See <u>Appendix</u> .

Tag	Name	Focus	Description	Format	Comments
Tag DFEE26	Name Encryption Status Information	NEO NEO	Description  Vendi (Encryption on Only), Unipay III, Unipay 1.5	Format	Byte 1: Bit 4/3/0: Captured Data Type 0 0 0 = Contact Card 0 1 = Contactless Card / EMV 0 1 = Contactless Card / MSD 0 1 x = MSR Card Bit 2/1: Encryption Mode 0 0 = TDES 1 = AES x = Refer to "Extended Encryption Mode" Bit 5: Reserved for Attribution Byte Extension. Bit 6/7: Encryption Status (For ViVOpay IDG) 0 = MSR/MSD off, EMV off 0 1 = MSR/MSD off, EMV on 0 = MSR/MSD on, EMV off 1 1 = MSR/MSD on, EMV on Byte 2: (Optional) Bit 3/2/1/0: Extended Encryption Mode 0 0 0 0 = TDES 0 0 1 = AES 0 0 1 0 = TransArmor Algorithm
					0 0 1 1 = Voltage Algorithm 0 1 0 0 = Visa FPE 0 1 0 1 = Verifone FPE Bit 4~6: Reserved Bit 7: 0 = Without MAC Verification Data 1 = With MAC Verification Data
DFEE27	MSR Control	Contact	Contact L2 CMD (60-10) in Unipay1.5		MSR Only Flag In contact EMV reader. Host need MSR transaction.  1: MSR only enabled. 0: MSR only disabled.
DFEE28	Terminal Capabilities - No CVM Required	MasterCard	MasterCard. Group 0 (Contactless)	b-3	
DFEE29	Terminal Capabilities - CVM Required	MasterCard	MasterCard. Group 0 (Contactless)	b-3	
DFEE2A	Threshold Value for Biased Random Selection (Intera c)	Interac	IDG Get/Set Configuration (Not Group Specific) (Interac Parameter)		Value used in <b>Terminal Risk Management</b> for random transaction selection.
DFEE2B	Maximum Target Percentage for Biased Random Selection (Interac)	Interac	IDG Get/Set Configuration (Not Group Specific) (Interac Parameter)		Value used in <b>Terminal Risk Management</b> for random  transaction selection.

Tag	Name	Focus	Description	Format	Comments
DFEE2C	Target Percentage for	Interac	IDG Get/Set		Value used in terminal risk
	Random Selection		Configuration (Not		management for random
	(Intera c)		Group Specific) (Interac Parameter)		transaction selection.
DFEE2D	Group Number	CONAIDS	CONAIDS	n2-1	When the group cannot be derived
	And Fallback Group	CONTRIBE	CO10/11D3	112 1	from the <b>Kernel ID Transaction</b>
	7 ma 1 ambaeix er eap				<b>Type Group</b> this is the group that
					will be used.
DFEE2E	Max AID Length	CONAIDS	CONAIDS	n2-1	
DFEE2F	AID Disabled	CONAIDS	CONAIDS	b-1	
DFEE30	Track Data Source	Clearing	Clearing Record	b-1	
DFEE31	DD Card Track 1	Clearing	Transaction and	b < 60	
DEFEND	DD Coult and D	Charles	Clearing Record	1 0	
DFEE32	DD Card Track 2	Clearing	Transaction and Clearing Record	b < 9	
DFEE33	Interac Receipt	Interac	Interac		
	Required				
DFEE34	Terminal Contactless	CONAIDS	CONAIDS	n12-6	
DEFERE	Transaction Limit	COMME	CONTAIDS		
DFEE35	Visa Reader Risk Flags	CONAIDS	CONAIDS	b-3	
DFEE36	CVM Required Limit	CONAIDS	CONAIDS	n12-6	
DFEE37	UI Scheme	CONAIDS	CONAIDS	b-1	UI Scheme
DFEE38	Language Option for LCD	CONAIDS	CONAIDS	n2-1	
DFEE39	Force MagStripe	CONAIDS	CONAIDS	n2-1	
DFEE3A	TAC - Online	CONAIDS	CONAIDS	b-5	
DFEE3B	TAC - Default	CONAIDS	CONAIDS	b-5	
DFEE3C	TAC - Denial	CONAIDS	CONAIDS	b-5	
DFEE3D	Reader Contactless	CONAIDS	CONAIDS Group	n12-6	Related to the AID indicating the
	Floor Limit Data		Tag		limit for which the Terminal will
					ask the card to perform an online
					transaction if the amount of the
					transaction is greater than this
					limit. Terminal - Group Tag n12 - 6
DFEE3E	Enable Exception List	SmartTap	Used by Smart Tap		reminai - Group Tag 1112 - 0
	Processing	Jinarerap	Kernel for Terminal		
	Ŭ		Configuration (set		
			in and picked up		
			from Contact		
			Group).		
DFEE3F	Default TDOL	SmartTap			
			_		
DFEE3F	Default TDOL	SmartTap	Group).  Used by Smart Tap Kernel for Terminal Configuration (set in / picked up from Contact Group)		

Tag	Name	Focus	Description	Format	Comments
DFEE40	Message to be	SmartTap	Used by Smart Tap		
	Displayed by EMV		Kernel for Terminal		
	Kernel on "PIN Try		Configuration (set		
	Limit Exceeded"		in / picked up from		
	condition		Contact Group).		
DFEE41	Message to be	SmartTap	Used by Smart Tap		
	Displayed by EMV		Kernel for Terminal		
	Kernel on "Last PIN		Configuration (set		
	Try" Condition		in and picked up		
			from Contact		
			Group).		
DFEE42	Message to be	SmartTap	Used by Smart Tap		
	Displayed by EMV		Kernel for Terminal		
	Kernel on "Please Try		Configuration (set		
	Again" condition		in / picked up from		
			Contact Group)		
DFEE43	Message to be	Smart Tap	Used by Smart Tap		
	Displayed by EMV		Kernel for Terminal		
	Kernel on "Call Your		Configuration (set		
	Bank" Condition		in and picked up		
			from		
			Contact Group)		
DFEE44	Application Capability	Cfg		b-2	
DFEE47	SoftCard Read Cmd	SoftCard	IDG Activate		
	Data		Transaction (Cmd)		
DFEE48	SoftCard Write Data	SoftCard	IDG Activate		
			Transaction (Cmd)		
DFEE49	SoftCard Transaction	SoftCard	IDG Activate		
	Data		Transaction		
			(Response)		
DFEE12	KSN of Data encryption				
	Key				
DFEE23	MSR all track data		IDTech - DFEE23		
5A	Masked PAN		IDTech - 5A with		
			Special Length		
DFEE4A	Registered Application	CONAIDS	CONAIDS	b-5	
	Provider Identifier (RID)				
DFEE4B	Partial Selection	CONAIDS	CONAIDS	b-1	
	Allowed				
DFEE4C	Application Flow	CONAIDS	CONAIDS	n2-1	
DFEE4D	Selection Features - GR	CONAIDS	CONAIDS AID	b-1	
	1.2.10		section - Flags for		
			application		
			selection features		
			for this AID.		
DFEE4E	Polling Options	ACT		b-1	If Bit 1 is '1', switch to MSR after
	0 - F				CL failure in PPSE.
L		<u> </u>		1	CE Tandie IIII I JE.

Tag	Name	Focus	Description	Format	Comments
DFEE4F	Interface Support	CONAIDS	CONAIDS	b-1	Used to declare AID as a Contact or Contactless AID. 01h = Contactless AID, 02h = Contact AID. If this Tag is missing, then the AID defaults to a Contactless AID.
DFEE50	Special Flow	ACT	IDG Activate Transaction (Cmd)		For defining special pre- and post- PPSE flows for SoftCard and other non- payment Apps.
<del>DFEE51</del>	Amex Terminal Capability (used for Amex only). Still available as two-byte tag DF51.	Amex	A stand in for 9F6D in GR based products, since that tag is used in Visa for something different.	b-1	
DFEE51	KSN of online PIN DUKPT	Contact		b10- 12	
DFEE52	Transaction CVM	Clearing	Transaction and Clearing Record	b-1	
DFEE53	Exclude from Processing	CONAIDS	CONAIDS	b-1	Indicates that this AID should not be considered as a Terminal Supported AID for the specified operations. <b>Bit 0</b> (LSB): Exclude from PPSE Processing Flag. <b>Bit 1</b> : Exclude from Trial & Error Processing Flag
DFEE54	Kernel ID Transaction Type Group List	CONAIDS	CONAIDS - Kernel ID Transaction Type Group List is a variable length list of 3-byte elements with a maximum size in the GR of 24 bytes, which is 8 triplets. Each triplet containing a supported Kernel ID, a transaction type and a group. This list defines the supported Kernel ID's and each triplet defines which group to use if that specific kernel and transaction type is requested.	b-24	CONAIDS tag to support Combined Selection. (CONAIDS only.)
DFEE55	RID			b-5	

Tag	Name	Focus	Description	Format	Comments
DFEE56	Activate Trans for	DesFire	IDG Get and Set		
	DESFireViVOCo mm		Configuration (Not		
	Flows		Group Specific)		
DFEE57	Reader Primary	Cfg	IDG Get and Set		
	Language		Configuration (Not		
			Group Specific)		
DFEE58	Reader Secondary	Cfg	CONAIDS - AID		
	Language		section - Kernel ID		
			used if the card		
			does not provide a		
			Kernel ID or		
			provides one that is		
			length 0.		
DFEE59	Default Kernel ID	CONAIDS	ViVOtech	n2-1	CONAIDS tag to support
			Proprietary. IDG Act		Combined Selection. (CONAIDS
			Trans with		only.)
			Encryption (02-05,		
			02-15)		
DFEE5A	TLV Exclusion List	ACT	ViVOtech		
			Proprietary		
DFEE5B	Terminal Entry	Cfg	ViVOtech	n2-1	Used to communicate the
	Capability		Proprietary		Terminal Entry Capability to the
					POS Value 5 - Support VSDC
					Contact Chip Value 8 doesn't
					support VSDC Contact Chip;
					(If the TTQ is set to support
					contact chip, the value will set to
					5, otherwise it is 8).
					The RF field will be deactivated up
					to four-byte BCD period
					representing microseconds of
					delay that during a Mobile CVM
					Processing Try Again.
DFEE5C	RF Deactivate Period	Cfg		b-4	The RF field will be deactivated up
					to four-byte BCD period
					representing microseconds of
					delay that during a <b>Mobile CVM</b>
					Processing Try Again.
DFEE5D	D-PAS Issuer Script	Discover			
	Response status				
DFEE5E	Transaction Timing	ACT	ViVOtech	b-1	For updated modules, this tag is
	Information		Proprietary		used to enable the collection of
					transaction timing data per
					activity when it is provided in the
					Activate Transaction Command
					The actual timing data will be
					provided in the Activate
					Transaction Response.

Tag	Name	Focus	Description	Format	Comments
DFEE5F	Encrypted PAN for remote PIN Pad	ACT	ViVOtech Proprietary is used in the Activate Transaction Command.		Used for PIN Pad Pairing. See "Serial Interface Supplement - PIN Pad Pairing" and "Serial Interface Supplement - Enhance Activate Transaction SRED".
DFEE60	Product ID	MVS	ViVOpay Proprietary (SRED)		
DFEE61	Processor ID	MVS	MVS		
DFEE62	Main Firmware Build ID	MVS	MVS		
DFEE63	CB Enhanced DDA Indicator (same block as DF03)	Visa	MVS		aka DF03
DFEE64	CB Wave 2 CVM Requirements (same block as DF04)	Visa	Visa Proprietary		
DFEE65	Build ID Num (Cxx)	MVS	Visa Proprietary		
DFEE66	SVN Number	MVS	MVS		
DFEE67	Specific Features Switch	Cfg	MVS	b-3	
Dfee68	Enable or Disable Stop Command Processing	MasterCard	Enables for misc features: CVN17, Track1 and Track2 in response.		The <b>STOP Command Processing</b> requires the receiving of a serial comm and inside the transaction loop, which could affect timing. This is especially true for SELECT PPSE. To implement a flag that will turn it on and off.
DFEE69	Configure Proprietary Tags	MasterCard	MChip 3.0 STOP Command Support		This tag will encapsulate a list of proprietary TLVs. These proprietary TLVs may be configured and used to supply information for DOLs.
DFEEGA	Enable and Disable Comm Error Recovery		GR		Enables (1) or Disables (0) the communications error handling in which the reader institutes a UI message delay and begins a new transaction automatically. This feature may have to be disabled to pass certain MChip3 Torn Transaction tests, with multiple transactions. (Perhaps for Eval Tool Timing?)
DFEE6B	Terminal IFD	Cfg			
DFEE6C	FTP Phase 2 Mode Options		TR3-FTP Phase 2		Bit flags to enable or disable specific Phase 2 functionality.

Tag	Name	Focus	Description	Format	Comments
DFEE6D	Mode 3 Match AID		TR3-FTP Phase 2		Provides the kernel with an AID to match in Mode 3 which is a <b>Bridge Mode</b> to allow distance-based travel using some special cards before this mode is available with bank cards.
DFEE6E	Torn Transaction Log Clean Interval (minutes)	Cfg	IDG Get/Set Configuration (Not Group Specific)		M/Chip 3.0
DFEE6F	Timestamp Data		TR3-FTP Phase 2		Allows numbered list of transaction point timestamps to be returned to the terminal.  Transaction point numbers are defined in the Design Spec.
DFEE70	Loyalty Program ID	Discover	IDG Get/Set Configurable Group (DPAS Parameter)		
DFEE71	Value Added Tax 1	Discover	IDG Get/Set Configurable Group (DPAS Parameter)		
DFEE72	Value Added Tax 2	Discover	IDG Get/Set Configurable Group (DPAS Parameter)		
DFEE73	Merchant Category Code	Discover	IDG Get/Set Configurable Group (DPAS Parameter)		
DFEE74	Discover Optional Features	Discover	IDG Get/Set Configurable Group (DPAS Parameter)		
DFEE75	Communications Error Message Delay	Cfg	System Level TLV used for Communication Error Message Delay configuration parameter. Unit of measure: milliseconds.	n6-3	Minimum value 500ms, BCD characters

Tag	Name	Focus	Description	Format	Comments
DFEE76	TVR from GenAC	Clearing	Contains the value	b-5	
		0.008	of the TVR at the	5 5	
			instant of sending		
			it to ICC during		
			GenAC. Tag 95		
			contains the Final		
			TVR that is sent to		
			the terminal.		
			These tag values		
			may or may not		
			match. It is possible		
			that the reader		
			sets bits in the TVR		
			between		
DFEE77	ViVOpay MSR Custom	Clearing	This TLV denotes		
	Data Output Tag	_	the custom data		
			output from MSR		
			transactions.		
DFEE78	MC Timing	GR	This TLV is a 1-		
	Performance		byte value which		
	Enable		toggles the		
			MasterCard		
			timing		
			performance		
			behavior, and		
			avoids using		
			EEPROM read		
			Access. The		
			transaction runs		
			faster and this will		
			save		
			~30msec because		
			Group 1 is pre-		
			loaded into RAM		
			and not loaded,		
			from EEPROM.		
DFEE79	Card Disable	CoinCo	TENTATIVE: Used		
	Mask		in CoinCo		
			experimental		
			firmware to provide		
			a mask of card		
			types from PCC.h		
			to be disabled		
			(ignored) during		
			polling.		

Tag	Name	Focus	Description	Format	Comments
DFEE7B	Serial Port (UART) Inter- character Timeout Period	CoinCo	TENTATIVE: Used in CoinCo experimental firmware to define the number of 100ms'ticks' the CL interface remains disabled during polling after disabled card is presented.  AR (2.1.5)	romat	The maximum time, in milliseconds, between characters of a <b>Receive</b> sequence. When no characters are received for this length of time SRED will consider <b>Message Complete</b> .  Default is 2000 (2 seconds). Twobyte value allows 0 to 65535 ms, a value of 0 disables the timeout function. <b>Example</b> : Things will work as they
DFEE7C	Auto Switch Feature	Cfg			did prior to AR 2.1.5.
DFEE7D	Track Formatting	Cfg			
DFEE/D	Feature				
DFEE7E	Burst Mode	Cfg	b-1		Used only in AR 2.1.4 and previous.

Tag Name Focus Description Format Comments    DFEE7F
value, range of 0- 255.  If 0, the Improved  Collision Feature is disabled & EMEA Anti- Collision Feature is enabled and the reader polls normally.  If 1, Improved EMEA Feature is
255.  If 0, the Improved  Collision Feature is disabled &  EMEA Anti- Collision Feature is enabled and the reader polls normally.  If 1, Improved  EMEA Feature is
Collision Feature is disabled & EMEA Anti- Collision Feature is enabled and the reader polls normally. If 1, Improved EMEA Feature is
is disabled &  EMEA Anti-  Collision Feature  is enabled and the  reader polls  normally.  If 1, Improved  EMEA Feature is
EMEA Anti- Collision Feature is enabled and the reader polls normally. If 1, Improved EMEA Feature is
Collision Feature is enabled and the reader polls normally. If 1, Improved EMEA Feature is
is enabled and the reader polls normally. If 1, Improved EMEA Feature is
reader polls normally. If 1, Improved EMEA Feature is
normally. If 1, Improved EMEA Feature is
If 1, Improved  EMEA Feature is
EMEA Feature is
disabled and the
disabled and the
reader polls
normally.
If 2 to 255,
Improved Collision
Feature is enabled
& EMEA Feature is
disabled. Reader
does additional
polling to verify
each polling event.
<b>Example</b> : Multiple
successful reads
are required before
the reader
acknowledges a
successful read.
DFEF01 2nd Usage: Remaining Cfg Identifies how
Candidates many candidates
are left on the
candidate list.
DFEF02     2nd Usage: Single     Cfg     Identifies if all candidates on the       Application Flow in All     candidates on the
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Candidate's Flag candidate list has
the same
DFEF03     GMEDs Data     GMAD     Transaction and
DFEF03     GMEDs Data     GMAD     Transaction and       Clearing Record
(GMAD)

Tag	Name	Focus	Description	Format	Comments
DFEF04	MSR Encryption Option	Cfg	Forced encryption setting for each track	b-1	Bit 0: T1 force encrypt. Bit 1: T2 force encrypt. Bit 2: T3 force encrypt.  Bit 3: T3 force encrypt when card type is 0x80.  Default value should be 0x08.  Refer to 80000403-001  Enhanced  Encrypted MSR Data Output  Format specification.  Reserved for MSR Options.
DFEF05	CVMRequiredLimit_JCB Scheme	Visa	Visa Proprietary (VisaWave), JCB		Visa aka DF01
DFEF06	CB Display Offline Funds Indicator (same block as DF05)	Visa	Visa Proprietary		aka DF05
DFEF07	CB Terminal Type (same block as 9F35)	Visa	Visa Proprietary		aka 9F35
DFEF08	Generic Name String	MVS	MVS		
DFEF09	Serial Finite State Machine Version	MVS	MVS		
DFEFOA	Generic Numeric	MVS	MVS		
DFEFOB	Generic Specification String	MVS	MVS		
DFEFOC	System Information Suite	MVS	MVS		
DFEFOD	Generic Implementation String	MVS	MVS		
DFEF0E	Serial Protocol Version	MVS	MVS		
DFEFOF	Serial Protocol Suite	MVS	MVS		
DFEF10	L1 Paypass Version	MVS	MVS		
DFEF11	L1 LCR Version	MVS	MVS		
DFEF12	VIUDS Scheme IDs Supported	Visa	VTPS/VIUDS		Allows up to 4 - 4-byte scheme ID's. 16 bytes, 4 bytes per Scheme ID, hexadecimal
DFEF13	VIUDS Scheme ID Selection Criteria	Visa	VTPS/VIUDS		0 = Select all matching, 1 = Select first matching. 1 byte, numeric
DFEF14	Transaction Finite State Machine Version	MVS	MVS		
DFEF15	L2 Card App Version	MVS	MVS		
DFEF16	TLV available				
DFEF17	Track 1 Data	Clearing	Contactless Card Transaction Result (response)		Track 1 Data. DiscoverZip, Visa MSD, Amex, PBOC
DFEF18	Track 2 Data	Clearing	Contactless Card Transaction Result (response)		Track 2 Data. DiscoverZip, Visa MSD, Amex, PBOC

Tag	Name	Focus	Description	Format	Comments
DFEF19	Unpredictable Number Range	Amex	KIII - Customer specific		This tag decides the range of unpredictable number; if UN is greater than this value, UN can MOD the range.
DFEF1B	L2 Card App Suite	MVS	MVS		
DFEF1A	SmartTap Delimiter	SmartTap	Delimiter for service numbers used in simplified output for SmartTap 2.1.		
DFEF1C	User Experience Version	MVS	MVS		
DFEF1D	User Experience Suite	MVS	MVS		
DFEF1E	Encrypted Sensitive Tags	Clearing			Single encrypted blob that when decrypted will contain multiple tag sensitive data. KSN DFEE12 needed for decryption
DFEF1F	Auto authenticate	Contact	Authenticates the card after Start Transaction without the need for command.		Byte 1: Auto authenticates option Byte 2: Force online option
DFEF20	MAC option in response data	Contact	Add MAC message to the response for EMV L2 command	ASCII	
DFEF21	BIN	White List	Used to define the BIN to be used for the White List	ASCII	May contain wildcards
DFEF22	AID	White List	Used to define the AID to be used for the White List	binary	May contain wildcards
DFEF23	HMAC	White List	The HMAC provided to authenticate the origin of the White List	binary	SHA-256, RCF-2104
DFEF24	HMAC KSN	Contact	The DUKPT KSN for the MAC key used in HMAC calculation	binary	
DFEF25	Output Data Format Select	UniPayIII	Select Vivopay or ICC encrypt Output Format in Auto Mode.	binary	For code DFEF25 = 5038 view Section 3.1 for more information.
DFEF26	MSR fallback	Spectrum Pro	Allow MSR fallback in EMV L2 transaction	binary	
DFEF27	Online capability	Spectrum Pro	Select whether support Online or not	b-2	

Tag	Name	Focus	Description	Format	Comments
DFEF29	LCD Delay Time	Cfg			
DFEF2A	Serial heartbeat Reguired	Cfg			
DFEF2B	Display Unsupported Card	Cfg	To display a Fail message or an Insert or Swipe Message based on terminal configuration.		
DFEF2C	Terminal AID List	Vendi		binary	0: Disable <b>1: Enable</b>
DFEF2D	Online Authentication Data	Kiosk III	When select PPSE Fail, reader will follow this tag one by one resend select AID to card.	TLVs	
DFEF2E	Terminal Transaction Log	Kiosk III	CUP application, Including Online Authentication Data (TLVs) from issuer.	binary	Byte 1: PAN length Byte 2~21: PAN Hash(sha1) Byte 22~34: Amount (ASCII code) Byte 35: PAN sequence number Byte 36~42: Transaction Date (ASCII code, value of tag 9A)
DFEF2F	CUP Configuration	Kiosk III	Including transaction log which might be used in Terminal Risk Management.	binary	
DFEF30	White List	Kiosk III		bianry	
DFEF31	Blacklist	Kiosk III	Support UPI	binary	
DFEF32	Auto-Switch	UniPay III	Support UPI	binary	Data Format reference neo spec. (Auto switch section)  Byte 1: Card Type  Byte 2: Serial Number  Other: UID or AID
DFEF33	Online PIN Block	Kiosk III	Used in command 02-40 response. (TLV output format)		
DFEF34	Antenna Detection Switch	Kiosk III			
DFEF35	Communications Watchdog Period	AR		binary	Two bytes.  0 = feature disabled.  1 - 65535 seconds timeout. generates a system reboot if V2 serial communications are not periodically received to reset it. Initially inserted in AR.  2.1.5 for customer as a method to automatically reset Vend III readers that hangs.

Tag	Name	Focus	Description	Format	Comments
DFEF36	Media Control & Status	Kiosk II	Used to control	binary	Data format = 4 bytes
	Tracking		media	'	See note following this table.
	o o		presentation/		J
			removal, and		
			reports the status		
			of same		
DFEF37	Interface Select		Interface Select	binary	Interface Select. Bit 0: MSR
			Tag:		Bit 1: Contactless
			This tag can select		Bit 2: Contact
			transaction		
			interface of reader.		
DFEF38	Timeout for Next		A contact	binary	Two bytes. (Unit: Sec)
	Command		transaction needs	,	·
			2 or 3 commands		
			to be completed.		
			This tag is the		
			defined timeout of		
			the next command.		
DFEF39	Network Indicate		When transactions	binary	0: Network is failed.
			go online and need		1: Network is Okay.
			this tag to indicate		·
			if the network is ok		
			or has failed.		
DFEF3A	Reader Behavior Mode	Kiosk2	The reader can		Has 2 permissible values:
			operate in either		00 – NORMAL
			modes.		01 - COMPATIBLE
			NORMAL: Kiosk2		
			BL and Image both		
			operate normally.		
			COMPATIBLE:		
			BL will not execute		
			flashISP		
			commands. It will		
			only simulate and		
			acknowledge them.		
			Main Image will		
			exhibit command		
			behaviors		
			compliant with <b>GR</b>		
			1.1.0, even though		
			it is new firmware.		

Tag	Name	Focus	Description	Format	Comments
DFEF3B	Autopoll Transaction Separation Interval	Kiosk 2	This is configurable, defaults to 0. After a transaction (successful or unsuccessful), the reader will not begin the next transaction until this interval has expired. In milliseconds"  0001 = 1 msec,  000A = 10 msec,  1388 = 5000 msec. This is a system tag and is configurable via the 04-00 command.	binary	Default value = 0000
DFEF3C	Fallback Support And Timeout For Waiting Next Command	NEO2.0	Used in Activate Transaction Command (02- 40) and decides CT Transaction Fallback Support and Timeout for the next command.	3 bytes	Byte 1: Fallback support Byte 2~3: Timeout for next command (Unit: Sec)
DFEF3D	Legacy Tag Support	NEO 2.0	Enables support for legacy tags on older products	1 Byte	Byte1bit0: Support Old TLVs

Tag	Name	Focus	Description	Format	Comments
DFEF40	Ascii-code	UniPay CPR			Original - The Value of 57 A1 18
	encryption Tag57 TLV	41665-1			is encrypted data for 57 11 43
	Tago/ Tev				35 12 89
					62 82 19 87 D1 21 22 01 00 00 00 00
					00 (Pad 0x00)
					<b>New</b> : Change 57 11 xx xx to
					Ascii-
					code     35     37     31     31     34     33     33       35     31     32       38     39     62     82     31     39     38     37
					3D 31 32 31 32 32 30 31 30 30 30 30 30 30 30 30
					30 30 (Hex D> '=' (0x3D))
					Encrypt the Ascii-code (Pad 0x00)
					to be 48 bytes data yy yy yy yy yy yy
					Use this New Tag to create TLV data -
					<b>DFEF40</b> 30 yy yy yy yy yy yy yy yy
DFEF41	MAC	SRED	NGA Protocol	16	Encrypted EMV L2 output data
	Verification Data for		Products - Augusta	Bytes	must with MAC Verification Data
	SRED		S, Augusta S		while "Verify Encryption Output  Data Option" is On.
DEFF42	MAC	SRED	NGA Protocol	10	Encrypted EMV L2 output data
	Verification KSN for		Products - Augusta	Bytes	must with MAC Verification Data
	SRED		S, Augusta S		while Verify Encryption Output
DEEE/ 2	Land T7/DCT		The level time area	,	Data Option is On.
DFEF43	Local TZ/DST information.		The local time zone & daylight	4 Bytes	<b>Byte1</b> : +/-, indicates current timezone is ahead or behind UTC.
			saving information	2,003	Byte2: HH, hours of the time
			of the transaction		difference with UTC.
			time.		Byte3: MM, minutes of the time
					difference with UTC.
					<b>Byte4</b> : Flag for daylight saving, set
					1 to indicate daylight saving enabled.
DFEF44	Combination Options	JCB	See JCB	2 bytes	See
	·		specification for more details.	,	JCB_Contactless_Terminal_Spec _v1.3 for details
DFEF45	Removal Timeout	JCB	When the	2 bytes	See
			cardholder is asked		JCB_Contactless_Terminal_Spec
			to remove their card.		_v1.3 for details
<u> </u>		L	Lalu.		

Tag	Name	Focus	Description	Format	Comments
DFEF46	ACT Pass Response DOL	Cfg	Used to define the additional TLV's desired for the ACT Pass Response.	T&L's	See ACT Response DOL specification
DFEF47	CDA Hash Input	DPAS CL2.5:C6 PayPass CL2.5:C2	Stores the CDA Hash Input data.	<= 1024 bytes	Tag used to store the <b>CDA Hash Input</b> data in the <b>TLV Database</b> . Used by ModTLV: HandleDOL() in the TIvDb static library to pick up data when indicated and append to the other DOL data.
DFEF48	Indicate - Retrieve Transaction Result Again (Due to Output Ram Not Being Enough).	Contact Reader	RAM not Enough - Augusta or Augusta S with TransArmor.	n bytes	If RAM is not enough, the Tag Value will be tailed in Transaction Result or response of Retrieve Transaction Result Command. If RAM is enough, the Tag Value will not exist.
DFEF49	Outcome Parameter Set	JCB	Combination of Transaction Outcome Parameters	9 bytes	See  JCB_Contactless_Terminal_Spec _v1.3 ,EMV Book A 6.2 for details
DFEF4A	User Interface Request Data	JCB	Combination of Transaction User Interface Request Data	14 bytes	See JCB_Contactless_Terminal_Spec _v1.3 ,EMV Book A 7.1 for details
DFEF4B	MSR Equivalent Data Option		Terminal Setting for MSR Equivalent Data Tag DFEF4D	3 bytes	See <u>Appendix</u> B.
DFEF4C	MSR Equivalent Data Track Lengths		Track(s) data length for MSR Equivalent Data Tag DFEF4D	6 bytes	<pre><track 1="" length=""/><track 2="" length=""/><track 3="" length=""/><pan length=""><rfu><rfu> Length of 0 indicates track disabled in DFEF4B or data not available. This tag also serves as an indicator of which data element are found first when "Only First Element Found" is enabled in DFEF4B.</rfu></rfu></pan></pre>
DFEF4D	MSR Equivalent Data		MSR Equivalent Data reconstructed from existing EMV tags. Alpha- numeric format.	an	Data populated with element(s) according to configuration tag DFEF4B
DFEF4E	ACT MSD Response DOL	Cfg	Used to define the additional TLV's desired for the ACT MSD response.	T&L's	See ACT Response DOL specification

Tag	Name	Focus	Description	Format	Comments
DFEF4F	ACT Decline Response DOL	Cfg	Used to define the additional TLV's desired for the ACT Decline and Failed responses.	T&L's	See ACT Response DOL specification
DFEF50	Terminal Interchange Profile (JCB)	JCB	It's a terminal configuration replacement for 9F53 in JCB, since that tag is used in MasterCard and Interac for something different.	3 bytes	See JCB_Contactless_Terminal_Spec _v1.3 for details
DFEF51	Bypass EMV Completion Output	Contact		1 byte	O1 = Suppress Output (DFEF510101)
DFEF52	Re- Fallback Times	Contact	Used for Re- Fallback implementation times setting.	1 byte	If this TLV data is not in  Transaction Command, the default is 5 times. The value size will be 3 (DFEF520103) ~10(DFEF52010A). If the Value is not 3~10, use 5 times.
DFEF53	Dynamic Reader Limits	XP 3.1 to start with	Used to provide a kernel with a variety of reader limits that may vary depending on the card brand.	var	For XP 3.1 this list is 16 sets of <b>Transactions</b> , <b>Floor</b> , and <b>CVM Required</b> limits (3 each).
DFEF54	SmartTap AID Index	Kiosk III	Used to select SmartTap AID	1 byte	<b>00</b> : use AID A0 00 00 04 76 D0 00 01 01 <b>01</b> : use AID A0 00 00 04 85 10 01 01 01

Tag	Name	Focus	Description	Format	Comments
DFEF55	Kernel Specific	Cfg	This TLV will	var	Defined per card brand kernel.
	Features		contain whatever		Used ONLY in the datasets.
			appropriate feature		
			switches for the		
			kernel dataset it		
			has been		
			configured in.		
			Meaning in		
			Expresspay it may		
			have different		
			meanings than in Visa or MC.		
DFEF56	Retry Limit	Interac	The total number	1 byte	Maximum (and default value) is 3.
	I Redry Emilie	terde	of taps allowed	. 5,10	Wideling and deradic value, 13 3.
			before transaction		
			is terminated.		
DFEF57	Firmware Version No.		Encodes Firmware	var	In QuickChip products, specify this
			Version info (ASCII).		tag in <b>DFEF5A</b> (see below) to
	_				appear in <b>Transaction Output</b> .
DFEF58	Current KSN of PIN	VP8800			
DEEEE	Encryption DUKPT Terminal Data Setting -	OuisleChin			
DFEF59	Default Amount	QuickChip			
DFEF5A	Terminal Data Setting -	QuickChip			
DI LI SA	Tags to Return	Quickemp			
DFEF5B	Mask for Tag5A	QuickChip			
DFEF5C	Mask for Tag56	QuickChip			
DFEF5D	Mask for Tag57	QuickChip			
DFEF5E	Mask for Tag 9F6B	QuickChip			
DFEF5F	Mask for Tag FFEE13	QuickChip			
DFEF60	Mask for Tag FFEE14	QuickChip			
DFEF61	Error Code	QuickChip			<b>Note</b> : The list below is not
					exhaustive. For the complete list,
					see <b>Appendix D</b> of this guide.
					F2 20 Insert ICC again /
					Swipe (used for all other fallback)
					F2 21 Prompt Fallback
					(used for case of no
					matching AID)
					F2 22 Counter
					reached/almost
					exhausted
			<u> </u>		

Tag	Name	Focus	Description	Format	Comments
DFEF62	Allow MSRSwipe data	QuickChip	Determines if an	1 byte	If value = 0x00, then any MSR
212.02	from ICC Card	quickerp	ICC must be	. 5700	swipe with an ICC card requires
	Hom rec eard		attempted to be		the card to be inserted instead of
			read first or		returning MSR swipe data. MSR
			allowed to return		swipe data from an ICC card can
			the MSR Swipe		only be captured in a fallback
			data instead (non-		situation.
			fallback) before		If value = 0x01, any card swiped
			attempting to read		(MSR or ICC) will return MSR
			ICC.		swipe data.
DFEF64	Referral timeout		Shows the referral	2 bytes	Swipe data.
DILIOT	nerchai ameda		message while	2 bytes	
			waiting time for		
			key entry.		
DFEF6E	USB-KB Output Data		icy criciy.	0~8	
5. 2. 02	Postfix			bytes	
DFEF6F	Inter-character Delay			1 byte	
2.2.0.	for USB- KB Interface			l byte	
DFEF70	VP8800 Dual Interface	VP8800/cfg	ID TECH	4 bytes	<b>b31~b28(4 bits)</b> : AS3911 "Wake-
	Interference		Proprietary.	,	up Timer Control Register"
	Prevention Mechanism		, ,		wur/wut2~0.
	Fine-Tune Parameters				<b>b27~b24(4 bits)</b> : AS3911
					"Amplitude Measurement Config
					Register" am_d3~0.
					<b>b23~b16(8 bits)</b> : Calibration IDG
					Command: Target Amplitude
					Value. <b>b15~b12(4 bits)</b> : AS3911
					"Antenna Calibration Control
					Register" tre_3~0.
					<b>b11~b08(4 bits</b> ): CTLS/MSR
					Identification Algorithm: Delta
					Threshold Value.
					b07~b00(8 bits): CTLS/MSR
					Identification Algorithm: No. of
					Amplitude Samples.
DFEF71	Waiting ICC Insert Time	contact EMV		2 bytes	Wait the ICC card's insert time
		L2		-,	when MSR card's service code is
					2/6, and the unit is second.
DFEF72	Pre-Poll Card	VP8800/cfg	ID TECH	1 byte	0: disable pre-poll card
	Mechanism Control in		Proprietary: If this	,	mechanism, 1: enable pre-poll
	ACT Cmd & Config		tag is not present		card mechanism
	Setting		in the ACT Cmd, the		
	_		tag stored in		Others: auto mode.
			configuration will		
			be referred. If this		Enable pre-poll card mechanism
			tag present in the		under the combination below:
			ACT Cmd, it will get		<ul> <li>Contactless + MSR</li> </ul>
			rid of the tag		<ul> <li>Contactless + Contact</li> </ul>
			stored in		Contactless + Contact +
			configuration.		MSR

Tag	Name	Focus	Description	Format	Comments
DFEF73	Transaction Message	Kiosk III		1 byte	b8~b4: RFU
	Туре				
					b3: Reversal Message
					b2: Confirmation Message
DEEE34	Deference Amerikada	\/D0000./-f-	M/hilaman mall	2 6. 4	b1: Authorization Message
DFEF74	Reference Amplitude Value	VP8800/cfg	While pre-poll contactless card	2 bytes	Reference amplitude value.
	value		mechanism		
			enabled, we will get		
			the current		
			amplitude value.		
			If the difference		
			between current		
			amplitude and		
			reference		
			amplitude is larger		
			or equal to		
			reference delta		
			value, it means		
			card detected, will		
			go to poll card		
			stage immediately.		
			The value of this		
			tag cannot be set		
			via IDG command,		
			it only set through		
			reference		
			amplitude		
DEFERE	Defense Della Val	\/D0000\/-f-	calibration process	41.1.	Dallacata
DFEF75	Reference Delta Value	VP8800/cfg	For pre-poll contactless card	1 byte	Delta value.
			mechanism.		
			Smaller value		
			means the event of		
			card detected will		
			be triggered easily.		
DFEF76	Transaction	NEO2.0	Is used in <b>Activate</b>	1 byte	
	Interface Type		Transaction		
	To Activate		Command (02-		
			40), to decide		
			which interface (Contact/MSR/Con		
			tactless) will be		
			activated.		
			activated.		

Tag	Name	Focus	Description	Format	Comments
DFEF77	Timeout For	NEO2.0	Used in <b>Activate</b>	1 byte	Unit of measure is seconds.
	Waiting Next		Transaction		
	Command		Command (02-		
			40), and decides		
			Timeout for		
			waiting next		
			command.		
DFEF78	EMV Contact L2	Contact L2	This is an option to	1 byte	0: Disable
	Display Messages		send display		
	Option		messages to the		1: Enable
			host even if the		
			reader already has		
			a		
			display. Request		
			from Cale for		
			Spectrum		
			Pro/L100.		
DFEF79	PIN Block Format	VP8800/Cf	Used for choosing	1 byte	Possible values: 0 or 3
	(When TDES)	g	PIN block format		
			when TDES is used		
DEFERM	Frakla Arala Davakasla	\/END:/-f-	for encryption.	4 5	O Disable
DFEF7A	Enable Apple Paycheck	VENDi/cfg	Enable a flag for send <b>Select OSE</b> to	1 byte	0: Disable
					1: Enable
DFEF7B	Apple Pay Status	VENDi	check Apple Pay.  If <b>DFEF7A</b> tag is	1 byte	0: RF Card, or not enable Tag
DFEF/B	Apple Pay Status	VENDI	enabled, then the	Tbyte	DFEF7A
			response is 1 for		1: Apple Pay
			read Apple pay or		1. Арріє Рау
			else the response		
			is 0.		
DFEF7C	Track Bit Encoding	VP8800/M SR	Returned by the	1 byte	
	Track Bit Effecting	li coco, misik	MSR module and	, byte	
			containing the		
			track encoding		
			information.		
DFEF7D	Re-power on Times	Contact L2	For control the	1 byte	Range :1-5, Default is 3
			times of re- power		
			on ICC card before		
			fall back to MSR		
DFEF7E	Fallback Response	Contact L2	To control the	var	List of the <b>Response Codes</b> from
	Code List		fallback when the		the transaction result
			response code is in		Response Code is in this list, then
			this list.		do fallback.

Tag	Name	Focus	Description	Format	Comments
Tag DFEF7F	Name Visa Oda And Online Indicator	Focus KIII	Description This tag is used to indicate the ODA and Online result of VISA.	Format 1 byte	Comments  Bit 7 – ODA and Online performed: 1 performed, 0 Not performed.  Bit 6 – RFU Bit 5 – RFU Bit 4 – RFU  Bit 3 – fDDA performed: 1 performed, 0 Not performed.  Bit 2 – fDDA failed: 1 Failed, 0  Succeed.  Bit 1 – SDA performed: 1 performed, 0 Not performed.  Bit 0 – SDA failed: 1 Failed, 0
					Succeed.

### 3.1. Note for Tag DFEE25

For contact EMV transactions, a two-byte result code may be returned in DFEE25. Check the contents of tag DFEE25, when it occurs, and interpret the results as follows:

**Note**: The result code is always two bytes long. The bottom two bits of the first byte are flags. If the zero bit is set, it means there was "advice." If the 1 bit was set, it means there was a "reversal." E.g.: 0203 means there was a reversal (02) and the result was 03 (declined).

### **EMV Result Codes**

Code	Message
0x0000	EMV_RESULT_CODE_APPROVED_OFFLINE
0x0001	EMV_RESULT_CODE_DECLINED_OFFLINE
0x0002	EMV_RESULT_CODE_APPROVED
0x0003	EMV_RESULT_CODE_DECLINED
0x0004	EMV_RESULT_CODE_GO_ONLINE
0x0005	EMV_RESULT_CODE_CALL_YOUR_BANK
0x0006	EMV_RESULT_CODE_NOT_ACCEPTED
0x0007	EMV_RESULT_CODE_FALLBACK_TO_MSR(EMV_RESULT_CODE_USE_MSR)
0x0008	EMV_RESULT_CODE_TIMEOUT
0x0010	EMV_RESULT_CODE_AUTHENTICATE_TRANSACTION
0x00FF	EMV_RESULT_CODE_UNABLE_TO_REACH_HOST
0x1001	EMV_RESULT_CODE_FILE_ARG_INVALID
0x2001	EMV_RESULT_CODE_MEMORY_NOT_ENOUGH
0x3004	EMV_RESULT_CODE_FALLBACK_SITUATION
0x3012	EMV_RESULT_CODE_MSR_CARD_ERROR_FALLBACK
0x3013	EMV_RESULT_CODE_TIMEOUT_FOR_WAITING_ICC_INSERT_OR_MSR_SWIPE_FALLBACK
0x5001	EMV_RESULT_CODE_PARSING_TAGS_FAILED
0x5002	EMV_RESULT_CODE_CARD_DATA_ELEMENT_DUPLICATE
0x5003	EMV_RESULT_CODE_DATA_FORMAT_INCORRECT
0x5004	EMV_RESULT_CODE_APP_NO_TERM
0x5005	EMV_RESULT_CODE_APP_NO_MATCHING
0x5006	EMV_RESULT_CODE_MANDATORY_OBJECT_MISSING
0x5007	EMV_RESULT_CODE_APP_SELECTION_RETRY
0x5008	EMV_RESULT_CODE_AMOUNT_ERROR_GET
0x5009	EMV_RESULT_CODE_CARD_REJECTED
0x5010	EMV_RESULT_CODE_AIP_NOT_RECEIVED
0x5011	EMV_RESULT_CODE_AFL_NOT_RECEIVED
0x5012	EMV_RESULT_CODE_AFL_LEN_OUT_OF_RANGE
0x5013	EMV_RESULT_CODE_SFI_OUT_OF_RANGE
0x5014	EMV_RESULT_CODE_AFL_INCORRECT
0x5015	EMV_RESULT_CODE_EXP_DATE_INCORRECT
0x5016	EMV_RESULT_CODE_EFF_DATE_INCORRECT
0x5018	EMV_RESULT_CODE_CRYPTOGRAM_TYPE_INCORRECT
0x5019	EMV_RESULT_CODE_PSE_BY_CARD_NOT_SUPPORTED
0x5020	EMV_RESULT_CODE_USER_LANGUAGE_SELECTED
0x5021	EMV_RESULT_CODE_SERVICE_NOT_ALLOWED
0x5022	EMV_RESULT_CODE_NO_TAG_FOUND
0x5023	EMV_RESULT_CODE_CARD_BLOCKED
0x5024	EMV_RESULT_CODE_LEN_INCORRECT

Code	Message
0x5025	EMV_RESULT_CODE_CARD_COM_ERROR
0x5028	EMV_RESULT_CODE_ARC_NOT_PRESENCED
0x5030	EMV_RESULT_CODE_COMM_NO_ONLINE
0x5031	EMV_RESULT_CODE_TRAN_TYPE_INCORRECT
0x5036	EMV_RESULT_CODE_APP_BLOCK_AID
0x5037	EMV_RESULT_CODE_PAN_INVALID
0x5038	EMV_RESULT_CODE_TRANS_TYPE_NO_SUPPORT
0x6003	EMV_RESULT_CODE_CVM_TAG_8E_MISSING
0x6004	EMV_RESULT_CODE_CVM_TAG_8E_FORMAT_ERROR

3.2. Note for Tag DFEF36

8	7	6	5	4	3	2	1	Notes:
_	-	1	1	-	-	-	Χ	-Disable Media Detection Reporting -Enable Media Detection Reporting
_	-	1	1	-	-	Х	1	-Disable Media Removal Reporting -Enable Media Removal Reporting
0	0	0	0	0	0	_	_	RFU

8	7	6	5	4	3	2	1	Notes:
-	_	_	_	-	-	-	Χ	0 - RF Field Deactivated 1 - RF Field
								Activated
-	-	-	-	_	_	Χ	-	0 - No CL Media Detected 1 - CL Media
								Detected
-	-	-	-	_	Χ	_	-	- CL Media Removed
								- CL Media Still Present
-	_	_	-	Χ	_	_	-	0 - No CT Media Detected 1 - CT Media
								Detected
-	-	-	Х	-	-	-	-	- CT Media Removed
								- CT Media Still Present
-	-	Χ	-	_	_	_	_	- No effect
								- PollForToken aborted
0	0	-	_	-	-	-	-	RFU

**Byte 3**: Status Byte 2 - RFU Byte 4: Status Byte 3 - RFU

## 4. Constructed Tags

Tag	Name	Focus	Description	Format	Comment
FFEE01	ViVOpay TLV Group		ViVOpay Proprietary Tag.		Encapsulating Tag: Contains
	Tag		Transaction (Cmd+Rsp)		TLVs returned by <b>Special Flow</b>
	3		, , , , , ,		apps invoked during Pre-PPSE
					Processing
FFEE02	ViVOpay Pre-	Special Flow	Transaction (response)	TLVs	Encapsulating Tag: Contains
	PPSE Special Flow		, and the second		TLVs returned by <b>Special Flow</b>
	Group Tag				apps invoked during Post-
					PPSE Processing
FFEE03	ViVOpay Post-	Special Flow	Transaction (response)	TLVs	This tag will hold any
	PPSE Special Flow				intermediate MSG signals
	Group Tag				issued by <b>Process K</b> during the
					transaction and included in the
					ACT response. If enabled, for L2
					verification of MSG signal data.
					It is also used to enable this
					functionality. If sent in the ACT
					command <b>Signal Data</b> capture
					will be enabled for that
					transaction and this tag will then be returned in the ACT
					response if any data was
					added to it during the
					transaction.
FFEE04	M/Chip3	MasterCard	M/Chip 3 specific	TLVs	This tag is used inside FFEE04
	Intermediate	l master ear a	in cinp 5 specific		to delineate the individual
	Message Data				signals (MSG or OUT) that are
	J				added.
FFEE05	M/Chip3	MasterCard	M/Chip 3 specific		This TLV is used to pass
	Intermediate				through ApplePay VAS
	Message Marker				proprietary TLV's. May be
					provided in the ACT and in the
			-		transaction response.
FFEE06	ApplePay VAS	Apple	ApplePayVAS	TLVs	Constructed tag with
	Container				individually encrypted sensitive
					tags. KSN DFEE12 needed for
FFEE07	Encrypted	Cloaring		TLVs	decryption  Constructed tag with individual
FFEEU/	Sensitive Tags	Clearing		ILVS	masked tags.
FFEE08	Masked Tags	Clearing		TLVs	Constructed tag that contains
					associated pairs <b>of Amount</b> ,
					Authorization. (9F02) and RIDs.
					Kernel uses <b>Amount</b> ,
					Authorization from a table
					when the related RID is
				<u>l</u>	detected.
FFEE09	Fixed Fare		TR3-FTP Phase 2	TLVs	No wild cards allowed.
	Amounts				
FFEEOA	BIN Range	White List	Contains two BIN's	TLVs	No wild cards allowed.
			(DFEF21). Any BIN		

Tag	Name	Focus	Description	Format	Comment
			including and between		
			the first BIN and second		
			BIN is a nonfinancial		
			regardless of content.		
FFEEOB	AID Range	White List	Contains two AID's	TLVs	
			(DFEF22). Any AID		
			including and between		
			the first AID and second		
			AID is a nonfinancial		
			regardless of content.		
FFEEOC	White List	White List	List of the BIN's and the	TLV's	
			AID's and ranges of BIN's		
			and AID's that will be		
			used to determine if		
			sensitive SRED data will		
			be evaluated.		
			<b>Example</b> : If in the white		
			list they are assumed		
			non-financial.	<u> </u>	
FFEEOD	Torn Temp Record	Mastercard	Temporary (List)	TLVs	
			construction tag used to		
			hold intermediate <b>Torn</b>		
			Transaction Log entries.		
			Mirrors the objects as		
			defined in the		
			specification.	<u> </u>	
FFEE10	ViVOpay MChip	MasterCard	Is this TLV exposed via	TLVs	
	Group Tag		the serial interface?		
			If yes then which		
			commands		
			Act Trans (Cmd or Resp)?		
			_		
CCCC 11	ViVOpay Discovor	Discover	•	TLVc	Discover DDAS
PPEEII		Discover	fff	ILVS	Discover DPA3
FFFF12		Visa	Holds the tags for cash	TI \/c	Replaces functionality of pow
		VIJU	_	1503	
	record				obsolete ou de command.
FFEE13	Cashback Reader	Visa	-	TLVs	Replaces functionality of now
					· ·
FFEE14	DRL Record 1	Visa	· ·	TLVs	One of four tags to replace
			risk record.		
					04-0E command.
FFEE15	DRL Record 2	Visa	Holds the tags for reader	TLVs	
			risk record.		functionality of now obsolete
					04-0E command.
FFEE16	DRL Record 3	Visa	Holds the tags for reader		One of four tags to replace
			risk record.		functionality of now obsolete
					04-0E command.
FFEE15	DRL Record 2	Visa	Holds the tags for reader risk record.  Holds the tags for reader		One of four tags to replace functionality of now obsolete 04-0E command.  One of four tags to replace functionality of now obsolete

FFEE 17 DRL Record 4 Visa Holds the tags for reader risk record.  FFEE 18 Tags to Write Yet Before GenAC  FFEE 19 Tags to Write Yet Mastercard Used in Data Exchange. (see CL25:C2)  FFEE 19 Tags to Write Yet Mastercard Used in Data Exchange.	
FFEE 18 Tags to Write Yet Before GenAC Wastercard Used in Data Exchange. (see CL25:C2)	
Before GenAC (see CL25:C2)	
(500 5115.01)	
FFEE19 Tags to Write Yet Mastercard Used in Data Exchange.	
After GenAC (see CL25:C2)	
FFEE 1ATerminal App DETMastercardUsed in Data Exchange.Each DET signal's dataData(see CL25:C2)be wrapped in this tag	
Data (see CL25:C2) be wrapped in this tag  Continue Transaction	III d
Command.	
FFEE20 Apple VAS KIII, This construct contains	
Merchant ID AppleVAS several Merchant ID	
Setting Container structures (FFEE21)	
FFEE21     Apple VAS     KIII,     This constructed tag	
Merchant ID AppleVAS contains Merchant ID	
Setting structure's content:	
9F25, 9F29.           FFEE69 ViVOpay         Amex         This construct         TLVs         Added for	
	0.2.and
Proprietary Tag Discover contains a list of Mastercard PayPass 3 List Interac proprietary tags that this TLV is a <b>Group TLV</b>	
Mastercard happen during the included in Group 1.	ana
Visa transaction. The user can set it with	1
'expected'	
TLV and the MC app ca	n
interact with and modi	fy the
TLV if	
encountered during the	ī
transaction.	
Unrecognized tags are expected and returned	
POS.	to the
For all other apps (Ame	·X.
Discover,	•
Interac, Visa), this is NO	)Ta
Group	
TLV. Instead, it is creat	
dynamically by the rea	der
during	., .,,
the transaction. This Ti	
only contain unrecognize that are found inside the	
Template Tag BFOC du	_
PPSE or Final Select.	р

## 5. Appendix A: Contact EMV Configuration Values (Tag DELETE)

Contact Terminal Configuration (**Default**: F0 DC 3C F0 C2 9E 94 00).

### Byte 1:

b8	b7	b6	b5	b4	Ь3	b2	b1	Meaning:
1	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Key Pad support
Χ	1	Χ	Χ	Χ	Χ	Χ	Χ	LCD support
Х	Χ	1	Χ	Χ	Χ	Χ	Χ	PIN Pad support
Χ	Χ	Χ	1	Χ	Χ	Χ	Χ	Print Support
Χ	Χ	Χ	Χ	0	Χ	Χ	Χ	RFU
Χ	Χ	Χ	Χ	Χ	0	Χ	Χ	RFU
Χ	Χ	Χ	Χ	Χ	Χ	0	Χ	RFU
Χ	Χ	Χ	Χ	Χ	Χ	Χ	0	RFU

#### Byte 2:

b8	b7	b6	b5	b4	b3	b2	b1	Meaning:
1	Χ	Χ	Χ	Χ	Χ	Χ	Χ	PSE support
Χ	1	Χ	Χ	Χ	Χ	Χ	Χ	Cardholder confirmation
Χ	Χ	1	Χ	Χ	Χ	Χ	Χ	PIN Pad support
Χ	Χ	Χ	1	Χ	Χ	Χ	Χ	Print Support
Χ	Χ	Χ	Χ	1	Χ	Χ	Χ	EMV language selection method
Χ	Χ	Χ	Χ	Χ	1	Χ	Χ	Default DDOL
Х	Χ	Χ	Χ	Χ	Х	0	Χ	RFU
Χ	Χ	Χ	Χ	Χ	Χ	Χ	0	RFU

#### Byte 3:

Dyce	5 y tc 5.							
b8	b7	b6	b5	b4	b3	b2	b1	Meaning:
0	Х	Х	Х	Х	Х	Х	Х	RFU (Revocation of Issuer Public Key Certificate (DF26))
37	1	37	3.7	37	3.7	37	3.7	, , ,
X	Τ.	Χ	X	X	Х	Χ	X	Manual action when CA PK loading
								fails
Χ	Χ	1	Χ	Χ	Χ	Χ	Χ	CA PK verified with check sum
Χ	Χ	Χ	1	Χ	Χ	Χ	Χ	Bypass PIN Entry
Χ	Χ	Χ	Χ	1	Χ	Χ	Χ	Subsequent bypass PIN Entry
Χ	Χ	Χ	Χ	Χ	1	Χ	Χ	Get data for pin try counter
Χ	Χ	Χ	Χ	Χ	Χ	0	Χ	RFU
Χ	Χ	Χ	Χ	Χ	Χ	Χ	0	RFU

## Byte 4:

b8	b7	b6	b5	b4	b3	b2	b1	Meaning:	
1	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Amount before CVM processing	
Χ	1	Χ	Χ	Χ	Χ	Χ	Χ	X Floor limit checking	
Χ	Χ	1	Χ	Χ	Χ	Χ	Χ	X Random transaction selection	
Х	Χ	Χ	1	Χ	Χ	Χ	Χ	Velocity checking	
Х	Χ	Χ	Χ	0	Χ	Χ	Χ	RFU (Transaction Log (DF11))	
Х	Χ	Χ	Χ	Χ	0	Χ	Χ	RFU (Exception File (DF27))	
Χ	Χ	Χ	Χ	Χ	Χ	0	Χ	RFU	
Χ	Χ	X	Χ	Χ	Χ	Χ	0	RFU	

### Byte 5:

B8	В7	В6	B5	В4	В3	B2	B1	Meaning:
1	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Terminal Action Code Support
Χ	1	Χ	Χ	Χ	Χ	Χ	Χ	Terminal Action Code Can Be Change
Χ	Χ	1	Χ	Χ	Χ	Χ	Χ	Terminal Action Code Can Be Deleted
								or Disable
Χ	Χ	Χ	1	Χ	Χ	Χ	Χ	Default Action Code Processing
								Before 1st Gac
Χ	Χ	Χ	Χ	1	Χ	Χ	Χ	Default Action Code Processing After
								1st Gac
Χ	Χ	Χ	Χ	Χ	1	Χ	Χ	Tac/Iac Default Process When Unable
								to Go Online (Skipped)
Χ	Χ	Χ	Χ	Χ	Χ	1	Χ	Tac/Iac Default Process When Unable
								to Go Online (Normal)
Χ	Χ	Χ	Χ	Χ	Χ	Χ	0	Rfu

#### Byte 6:

Dyte	<b>U</b> .								
b8	b7	b6	b5	b4	b3	b2	b1	Meaning:	
1	Χ	Χ	Χ	Χ	Х	Χ	Χ	Forced Online Support	
Χ	1	Χ	Χ	Χ	Х	Χ	Χ	Forced Acceptance Support	
Χ	Х	1	Χ	Χ	Χ	Χ	Χ	Advices Support	
Χ	Χ	Χ	1	Χ	Χ	Χ	Χ	Issuer Referrals Support	
Χ	Х	Χ	Χ	1	Χ	Χ	Χ	Batch Data Capture	
Χ	Χ	Χ	Χ	Χ	1	Χ	Χ	Online Data Capture	
Χ	Х	Χ	Χ	Χ	Х	1	Χ	Default TDOL	
Χ	Χ	Χ	Χ	Χ	Χ	Χ	0	0 RFU	

## Byte 7:

b8	b7	b6	b5	b4	b3	b2	b1	Meaning:
1	Χ	Χ	Х	Χ	Χ	Χ	Χ	Amount and Pin Entered on The Same
								Keypad
Χ	1	Χ	Х	Χ	Χ	Χ	Χ	ICC/Magstripe Reader Combined
Χ	Χ	1	Х	Χ	Χ	Χ	Χ	Magstripe Read First
Χ	Χ	Χ	1	Χ	Χ	Χ	Χ	Support Account Type Selection
X	Χ	Χ	Х	1	Χ	Χ	Χ	On Fly Script Processing
Χ	Χ	Χ	Х	Χ	1	Χ	Χ	Internal Date Management
Χ	Χ	Χ	Х	Χ	Χ	1	Χ	Reversal Mode
								(1)Unable Go Online
								(2) Arc Error
								0: (3) Online Approved but Reader
								Not Approved.
								1: (3) Online Approved but Card
								Response Aac.
X	Χ	Χ	Χ	Χ	Χ	Χ	0	RFU

### Byte 8:

•								
b8	<b>b</b> 7	b6	b5	<b>b4</b>	b3	b2	b1	Meaning:
Χ	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Amount and Pin Entered on The Same
								Keypad

## 6. Appendix B: Encrypted Track Data Status (Tag DFEF4B)

Byte 1:

b8	<b>b</b> 7	b6	b5	b4	b3	b2	b1	Meaning:	
1	Χ	Χ	Χ	Χ	Χ	Χ	Χ	Amount and Pin Entered on The Same	
							Keypad		
Χ	1	Χ	Χ	Χ	Χ	Χ	X ICC/Magstripe Reader Combined		
Х	Χ	1	Χ	Χ	Χ	Χ	Χ	Magstripe Read First	
Χ	Χ	Χ	1	Χ	Χ	Χ	Χ	Support Account Type Selection	
Χ	Χ	Χ	Χ	1	Χ	Χ	Χ	On Fly Script Processing	
Χ	Χ	Χ	Χ	Χ	1	Χ	X Internal Date Management		
Х	Χ	Χ	Χ	Χ	Χ	1	Χ	Reversal Mode	
								(1) Unable Go Online	
								(\\2) Arc Error	
								0:(3) Online Approved but Reader Not	
								Approved.	
								1:(3) Online Approved but Card	
								Response Aac.	
Χ	Χ	Χ	Χ	Χ	Χ	Χ	0	RFU	

Byte 1:

2710	te i.								
8	7	6	5	4	3	2	1	Notes:	
-	-	-	_	_	_	_	X 0- Disable Track 3 Sentinels		
								1- Enable Track 3 Sentinels	
-	-	-	-	-	-	Х	-	0- Disable Track 2 Sentinels	
								1- Enable Track 2 Sentinels	
-	-	-	-	-	Х	-	-	0- Disable Track 1 Sentinels	
								1- Enable Track 1 Sentinels	
-	-	-	-	Χ	_	_	0 - Disable Track 3		
								1- Enable Track 3	
-	-	-	Χ	-	-	-	- 0- Disable Track 2		
								1- Enable Track 2	
-	-	Χ	-	-	-	-	-	0- Disable Track 1	
								1- Enable Track 1	
-	Χ	-	-	-	-	-	-	0- Disable PAN	
								1- Enable PAN	
Χ	-	_	_	_	-	-	-	- 0- All Data Elements Found	
								1- Only First Element Found	

Byte 2: RFU Byte 3: RFU

If this tag does not exist in **Terminal Settings**, tags **DFEF4C** and **DFEF4D** will not be generated.

The default value of this tag is 0x12 = Track 2 enabled with **Sentinels**.

#### Data Search Order

The **Only First Element Found** (bit 8 = 1), Tag **DFEF4D** will be populated with a single data element:

- Track 2, Tag 57 (converted to alpha numeric format) Track 2, Tag 9F6B
- Track 2, Tag 5F22 Track 1, Tag 56 Track 1, Tag 5F21
- PAN, Tag 5A (converted to alpha numeric format) Track 3, Tag 58
- Track 3, Tag 5F23

The **All Data Elements Found** (BIT 8 = 0), Tag **DFEF4D** is populated with a single instance of each requested data element, according to the following order:

Track 1 requested (bit 6 = 1).

#### Include first instance:

Tag 56 = Track 1 Equivalent

Tag 5F21 = Track 1, identical to the data coded Track 2 requested (bit 5 = 1).

#### Include first instance:

Tag 57 = Track 2 Equivalent (converted to alpha numeric format)

Tag 9F6B = Track 2 Data

Tag 5F22 = Track 2, identical to the data coded

Track 3 requested (bit 4 = 1).

#### Include first instance:

Tag 58 = Track 3 Equivalent

Tag 5F23 = Track 3, identical to the data coded PAN requested (bit 7 = 1).

#### Include:

Tag 5A = PAN (converted to alpha numeric format)

#### Sentinels

Any found data element of Track 1, Track 2, or Track 3, start and add sentinels are added according to bits 1, 2, and 3.

## **6.1. Compressed Numeric Elements**

Any data element captured as compressed numeric have the following rules:

- Padding (0xf) is not included.
- Center separators 0xd is converted to 0x3d ("=").

Data is encoded as ASCII representation of binary data.

**Example**:  $0 \times 123 = 0 \times 313233 = "123"$ 

## 7. Appendix C: Contact Response Code (Tag DFEE25)

Certain commands produce **Response Code** messages to display on a host device. These codes are wrapped in the **DFEE25** tag and are shown below.

See the Appendix on tag **DFEF61** to review additional contact EMV status codes.

**Note**: The first response byte has bit flags in the lower nibble. (See explanation at end of table.)

Number	Response Code (2 Bytes)	Display on LCD
1	0x00,0x00	APPROVED (offline)
2	0x00,0x01	DECLINED (offline)
3	0x00,0x02	APPROVED
4	0x00,0x03	DECLINED (See also the note
		following this table.)
5	0x00,0x04	GO ONLINE
6	0x00,0x05	CALL YOUR BANK
7	0x00,0x06	NOT ACCEPTED
8	0x00,0x07	USE MAGSTRIPE
9	0x00,0x08	TIME OUT
10	0x00,0x10	(start transaction success)
11	0x00,0x11	MSR Success
	0x00, 0x12	Card In
12	0x10, 0x01	TERMINATE
	(FILE_ARG_INVALID)	
13	0x10,0x02	TERMINATE
	(FILE_OPEN_FAILED)	
14	0x10,0x03	TERMINATE
	(FILE_OPERATION_FAILED)	
15	0x20, 0x01	TERMINATE
	(MEMORY_NOT_ENOUGH)	
16	0x30, 0x01	TERMINATE
	(SMARTCARD_OK)	
17	0x30, 0x02	TERMINATE
	(SMARTCARD_FAIL)	
18	0x30, 0x03	TERMINATE
	(SMARTCARD_INIT_FAILED)	
19	0x30,0x04	TERMINATE
	(FALLBACK_SITUATION)	
20	0x30, 0x05	TERMINATE
	(SMARTCARD_ABSENT)	TEDAMMATE
21	0x30,0x06	TERMINATE
	(SMARTCARD_TIMEOUT)	TEDAMATE
22	0x30,0x07	TERMINATE
	(MSR_CARD_ERROR) 0x30, 0x10	FALLBACK TO MSR
	(SSL2 ICCMSR DATA FALLBACK)	FALLDACK TO IVISK
	0x30, 0x11	FALLBACK TO MSR
	(SSL2 ICCMSR DATA SERVICE)	FALLDACK TO WISK
	/JJLZ_ICCINIJK_DATA_JLKVICL/	I

1		
	0x30, 0x12	CHIP ERROR
	(SSL2_ICCMSR_CARD_ERROR)	TIME OUT AFTER FALL BACK
	0x30, 0x13	TIMEOUT AFTER FALLBACK
	(SSL2_ICCMSR_TIMEOUT)	
23	0x50, 0x01 (PARSING_TAGS_FAILED)	TERMINATE
24	0x50, 0x02	TERMINATE
24	(CARD_DATA_ELEMENT_DUPLICATE)	TERIVIIIVATE
25	0x50, 0x03	TERMINATE
	(DATA_FORMAT_INCORRECT)	TETRIVITION (TE
26	0x50,0x04	NOT ACCEPTED
	(APP_NO_TERM)	
27	0x50, 0x05	NOT_ACCEPTED
	(APP_NO_MATCHING)	
28	0x50,0x06	TERMINATE
	(MANDATORY_OBJECT_MISSING)	
29	0x50, 0x07	TERMINATE
	(APP_SELECTION_RETRY)	
30	0x50, 0x08	TERMINATE
	(AMOUNT_ERROR_GET)	
31	0x50, 0x09	TERMINATE
	(CARD_REJECTED)	
32	0x50, 0x10	TERMINATE
	(AIP_NOT_RECEIVED)	
33	0x50, 0x11	TERMINATE
	(AFL_NOT_RECEIVED)	
34	0x50, 0x12	TERMINATE
25	(AFL_LEN_OUT_OF_RANGE)	TEDMINISTE
35	0x50, 0x13 (SFI_OUT_OF_RANGE)	TERMINATE
36	0x50, 0x14	TERMINATE
30	(AFL_INCORRECT)	TERIVIIIVATE
37	0x50, 0x15	TERMINATE
· ·	(EXP_DATE_INCORRECT)	121111111111111111111111111111111111111
38	0x50, 0x16	TERMINATE
	(EFF_DATE_INCORRECT)	
39	0x50, 0x17	TERMINATE
	(ISS_COD_TBL_OUT_OF_RANGE)	
40	0x50, 0x18	TERMINATE
	(CRYPTOGRAM_TYPE_INCORRECT)	
41	0x50, 0x19	TERMINATE
	(PSE_BY_CARD_NOT_SUPPORTED)	
42	0x50, 0x20	TERMINATE
	(USER_LANGUAGE_SELECTED)	
43	0x50, 0x21	NOT_ACCEPTED
	(SERVICE_NOT_ALLOWED)	
44	0x50, 0x22	TERMINATE
	(NO_TAG_FOUND)	TEDMINISTE
45	0x50, 0x23	TERMINATE
,,	(CARD_BLOCKED)	TEDMINIATE
46	0x50, 0x24	TERMINATE

	(LEN_INCORRECT)	
47	0x50, 0x25	TERMINATE
	(CARD_COM_ERROR)	
48	0x50, 0x26	TERMINATE
	(TSC_NOT_INCREASED)	
49	0x50, 0x27	TERMINATE
	(HASH_INCORRECT)	
50	0x50, 0x28	TERMINATE
	(ARC_NOT_PRESENCED)	
51	0x50, 0x29	TERMINATE
	(ARC_INVALID)	
52	0x50, 0x30	TERMINATE
	(COMM_NO_ONLINE)	
53	0x50, 0x31	TERMINATE
	(TRAN_TYPE_INCORRECT)	
54	0x50, 0x32	TERMINATE
	(APP_NO_SUPPORT)	
55	0x50, 0x33	TERMINATE
	(APP_NOT_SELECT)	
56	0x50, 0x34	TERMINATE
	(LANG_NOT_SELECT)	
57	0x50, 0x35	TERMINATE
	(TERM_DATA_NOT_PRESENCED)	
	0x50, 0x36	TERMINATE
	(CARD_BLOCKED)	TEDAMATE
58	0x60, 0x01	TERMINATE
	(CVM_TYPE_UNKNOWN)	TEDMINIATE
59	0x60, 0x02	TERMINATE
	(CVM_AIP_NOT_SUPPORTED)	TEDMINIATE
60	0x60, 0x03	TERMINATE
61	(CVM_TAG_8E_MISSING) 0x60, 0x04	TERMINATE
01	(CVM_TAG_8E_FORMAT_ERROR)	ILMINAIL
62	0x60, 0x05	TERMINATE
02	(CVM_CODE_IS_NOT_SUPPORTED)	TEINVIIIVATE
63	0x60, 0x06	TERMINATE
	(CVM_COND_CODE_IS_NOT_SUPPORTED)	TEINVIII WATE
64	0x60, 0x07	TERMINATE
	(CVM NO MORE)	
65	0x60, 0x08	TERMINATE
	(PIN_BYPASSED_BEFORE)	
66	Error Result Code	TERMINATE
[		1

**Note**: First response byte has bit flags as follows:

Bit 0 --- if transaction has advice, this bit is 1. Bit 1 --- if transaction has reversal, this bit is 1.

#### Example:

DFEE25 02 02 03 
Reversal (02) + DECLINED (03)

# 8. Appendix D: DFEF61 (Contact EMV Status Codes)

Error Code	Definition
0x0400	Related Key Was Not Loaded
0x0410	Non-SRED Device Need Load Manufacture Key and Firmware Key
0x0500	Key Same / Duplicate Key Detected
0x0702	PAN Is Error
0x0F00	Encryption or Decryption Failed
0x1001	File Arg Invalid
0x1002	File Open Failed
0x1003	File Operation Failed
0x2001	Memory Not Enough
0x3001	Smartcard OK
0x3002	Smartcard Fail
0x3003	Smartcard Init Failed
0x3004	Fallback Situation
0x3005	Smartcard Absent
0x3006	Smartcard Timeout
0x3007	MSR Card Error
0x5001	Parsing Tags Failed
0x5002	Card Data Element Duplicate
0x5003 0x5004	Data Format Incorrect
0x5004 0x5005	App No Term  No Matching AID
0x5005	Mandatory Object Missing
0x5007	App Selection Retry
0x5008	Amount Error Get
0x5009	Card Rejected
0x5010	AIP Not Received
0x5011	AFL Not Received
0x5012	AFL Len Out of Range
0x5013	SFI Out of Range
0x5014	AFL Incorrect
0x5015	Exp Date Incorrect
0x5016	Eff Date Incorrect
0x5017	ISS Code Table Out of Range
0x5018	Cryptogram Type Incorrect
0x5019	PSE By Card Not Supported
0x5020	User Language Selected
0x5021	Service Not Allowed
0x5022	No Tag Found
0x5023	Card Blocked
0x5024 0x5025	Length Incorrect Card Communications Error
0x5025 0x5026	TSC Not Increased
0x5026	Hash Incorrect
0x5027	Arc Not Present
0x5029	ARC Invalid
0x5030	Comm No Online
	22

0x5031     Tran Type Incorrect       0x5032     App Not Supported       0x5033     App Not Selected       0x5034     Language Not Selected       0x5035     Term Data Not Present       0x5036     Card Blocked       0x5501     No RKI-KEK       0x5504     Validate Authentication Code Error       0x5505     Encrypt or Decrypt Data Failed       0x5506     Not Support the New Key Type       0x5507     New Key Index Is Error       0x5508     Step Error       0x5509     Remote Key Injection Timeout (Latest Command Is Timeout)       0x5509     Remote Key Isage Error       0x5500     Mode of Use Error       0x5501     Over Use Error       0x5502     Mode of Use Error       0x5503     Mode of Use Error       0x5504     Over Use Error       0x5505     Over Configuration Failed / Or Read Configuration Error, Flash Error       0x6000     Save Or Configuration Failed / Or Read Configuration Error, Flash Error       0x6001     CVM Type Unknown       0x6002     CVM Aip Not Supported       0x6003     CVM Tag 8E Format Error       0x6004     CVM Tag 8E Format Error       0x6005     CVM Cond Code Is Not Supported       0x6006     CVM Cond Code Is Not Supported       0x6007     Vok Mon
Ox5033 App Not Selected Ox5034 Language Not Selected Ox5035 Term Data Not Present Ox5036 Card Blocked Ox5500 No RKI-KEK Ox5501 Rki-Kek Stop Ox5504 Validate Authentication Code Error Ox5505 Encrypt or Decrypt Data Failed Ox5506 Not Support the New Key Type Ox5507 New Key Index Is Error Ox5508 Step Error Ox5509 Remote Key Injection Timeout (Latest Command Is Timeout) Ox5500 Mac Error Ox5500 Mode of Use Error Ox5500 Mode of Use Error Ox5500 Tother Error Ox5500 Mode of Use Error Ox5500 Note Fror Ox5500 Mode of Use Error Ox5500 Mode of Use Error Ox5500 Mode of Use Error Ox6000 Save Or Configuration Failed / Or Read Configuration Error, Flash Error Ox6001 CVM Type Unknown Ox6002 CVM Aip Not Supported Ox6003 CVM Tag 8E Missing Ox6004 CVM Tag 8E Format Error Ox6005 CVM Code Is Not Supported Ox6006 CVM Code Is Not Supported Ox6007 CVM No More Ox6008 PIN Bypassed Before Ox6000 No Serial Number Ox6000 Invalid Command – Protocol Is Right, But Task Id Is Invalid Ox6000 Invalid Command – Protocol Is Right, But Task Id Is Invalid
0x5034         Language Not Selected           0x5035         Term Data Not Present           0x5036         Card Blocked           0x5500         No RKI-KEK           0x5501         Rki-Kek Stop           0x5504         Validate Authentication Code Error           0x5505         Encrypt or Decrypt Data Failed           0x5506         Not Support the New Key Type           0x5507         New Key Index Is Error           0x5508         Step Error           0x5509         Remote Key Injection Timeout (Latest Command Is Timeout)           0x5500         Mac Error           0x5501         Mode of Use Error           0x5502         Mode of Use Error           0x5503         Key Usage Error           0x5504         Mode of Use Error           0x5505         Other Error           0x5000         Save Or Configuration Failed / Or Read Configuration Error, Flash Error           0x6000         Save Or Configuration Failed / Or Read Configuration Error, Flash Error           0x6001         CVM Type Unknown           0x6002         CVM Aip Not Supported           0x6003         CVM Tag 8E Missing           0x6004         CVM Tag 8E Format Error           0x6005         CVM Code Is Not Supported
Ox5035 Term Data Not Present Ox5036 Card Blocked Ox5500 No RKI-KEK Ox5501 Rki-Kek Stop Ox5504 Validate Authentication Code Error Ox5505 Encrypt or Decrypt Data Failed Ox5506 Not Support the New Key Type Ox5507 New Key Index Is Error Ox5508 Step Error Ox5508 Step Error Ox5509 Remote Key Injection Timeout (Latest Command Is Timeout) Ox5500 Mac Error Ox5500 Mac Error Ox5500 Mac Error Ox5500 Mode of Use Error Ox5500 Mode of Use Error Ox5500 Ox5500 Other Error Ox5500 Ox6000 Save Or Configuration Failed / Or Read Configuration Error, Flash Error Ox6001 CVM Type Unknown Ox6002 CVM Aip Not Supported Ox6003 CVM Tag 8E Missing Ox6004 CVM Tag 8E Format Error Ox6005 CVM Code Is Not Supported Ox6006 CVM Code Is Not Supported Ox6007 CVM No More Ox6000 No Serial Number Ox6000 No Serial Number Ox6001 No White List Ox6000 Invalid Command – Protocol Is Right, But Task Id Is Invalid Ox6000 Unsupported Command – Protocol and Task Id Is Invalid
0x5036     Card Blocked       0x5500     No RKI-KEK       0x5501     Rki-Kek Stop       0x5504     Validate Authentication Code Error       0x5505     Encrypt or Decrypt Data Failed       0x5506     Not Support the New Key Type       0x5507     New Key Index Is Error       0x5508     Step Error       0x5509     Remote Key Injection Timeout (Latest Command Is Timeout)       0x550A     Mac Error       0x550B     Key Usage Error       0x550F     Other Error       0x550F     Other Error       0x6000     Save Or Configuration Failed / Or Read Configuration Error, Flash Error       0x6001     CVM Type Unknown       0x6002     CVM Aip Not Supported       0x6003     CVM Tag 8E Missing       0x6004     CVM Tag 8E Format Error       0x6005     CVM Code Is Not Supported       0x6006     CVM Code Is Not Supported       0x6007     CVM No More       0x6008     PIN Bypassed Before       0x6200     No Serial Number       0x6201     No White List       0x6900     Invalid Command – Protocol Is Right, But Task Id Is Invalid       0x6001     Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x5500         No RRI-KEK           0x5501         Rki-Kek Stop           0x5504         Validate Authentication Code Error           0x5505         Encrypt or Decrypt Data Failed           0x5506         Not Support the New Key Type           0x5507         New Key Index Is Error           0x5508         Step Error           0x5509         Remote Key Injection Timeout (Latest Command Is Timeout)           0x550A         Mac Error           0x550B         Key Usage Error           0x550C         Mode of Use Error           0x550F         Other Error           0x6000         Save Or Configuration Failed / Or Read Configuration Error, Flash Error           0x6001         CVM Type Unknown           0x6002         CVM Aip Not Supported           0x6003         CVM Tag 8E Missing           0x6004         CVM Tag 8E Format Error           0x6005         CVM Code Is Not Supported           0x6006         CVM Code Is Not Supported           0x6007         CVM No More           0x6008         PIN Bypassed Before           0x6200         No Serial Number           0x6201         No White List           0x6900         Invalid Command – Protocol Is Right, But Task Id Is Invalid
0x5501       Rki-Kek Stop         0x5504       Validate Authentication Code Error         0x5505       Encrypt or Decrypt Data Failed         0x5506       Not Support the New Key Type         0x5507       New Key Index Is Error         0x5508       Step Error         0x5509       Remote Key Injection Timeout (Latest Command Is Timeout)         0x550A       Mac Error         0x550B       Key Usage Error         0x550C       Mode of Use Error         0x550F       Other Error         0x6000       Save Or Configuration Failed / Or Read Configuration Error, Flash Error         0x6001       CVM Type Unknown         0x6002       CVM Aip Not Supported         0x6003       CVM Tag 8E Missing         0x6004       CVM Tag 8E Format Error         0x6005       CVM Code Is Not Supported         0x6006       CVM Cond Code Is Not Supported         0x6007       CVM No More         0x6008       PIN Bypassed Before         0x6200       No Serial Number         0x6201       No White List         0x6900       Invalid Command – Protocol Is Right, But Task Id Is Invalid         0x6400       Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x5504     Validate Authentication Code Error       0x5505     Encrypt or Decrypt Data Failed       0x5506     Not Support the New Key Type       0x5507     New Key Index Is Error       0x5508     Step Error       0x5509     Remote Key Injection Timeout (Latest Command Is Timeout)       0x550A     Mac Error       0x550B     Key Usage Error       0x550C     Mode of Use Error       0x550F     Other Error       0x6000     Save Or Configuration Failed / Or Read Configuration Error, Flash Error       0x6001     CVM Type Unknown       0x6002     CVM Aip Not Supported       0x6003     CVM Tag 8E Missing       0x6004     CVM Tag 8E Format Error       0x6005     CVM Code Is Not Supported       0x6006     CVM Cond Code Is Not Supported       0x6007     CVM No More       0x6008     PIN Bypassed Before       0x6200     No Serial Number       0x6201     No White List       0x6900     Invalid Command – Protocol Is Right, But Task Id Is Invalid       0x6400     Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x5505       Encrypt or Decrypt Data Failed         0x5506       Not Support the New Key Type         0x5507       New Key Index Is Error         0x5508       Step Error         0x5509       Remote Key Injection Timeout (Latest Command Is Timeout)         0x550A       Mac Error         0x550B       Key Usage Error         0x550C       Mode of Use Error         0x550F       Other Error         0x6000       Save Or Configuration Failed / Or Read Configuration Error, Flash Error         0x6001       CVM Type Unknown         0x6002       CVM Alp Not Supported         0x6003       CVM Tag BE Missing         0x6004       CVM Tag BE Format Error         0x6005       CVM Code Is Not Supported         0x6006       CVM Code Is Not Supported         0x6007       CVM No More         0x6008       PIN Bypassed Before         0x6200       No Serial Number         0x6201       No White List         0x6900       Invalid Command – Protocol Is Right, But Task Id Is Invalid         0x6400       Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x5506     Not Support the New Key Type       0x5507     New Key Index Is Error       0x5508     Step Error       0x5509     Remote Key Injection Timeout (Latest Command Is Timeout)       0x550A     Mac Error       0x550B     Key Usage Error       0x550C     Mode of Use Error       0x550F     Other Error       0x6000     Save Or Configuration Failed / Or Read Configuration Error, Flash Error       0x6001     CVM Type Unknown       0x6002     CVM Aip Not Supported       0x6003     CVM Tag 8E Missing       0x6004     CVM Tag 8E Format Error       0x6005     CVM Code Is Not Supported       0x6006     CVM Code Is Not Supported       0x6007     CVM No More       0x6008     PIN Bypassed Before       0x6200     No Serial Number       0x6201     No White List       0x6900     Invalid Command – Protocol Is Right, But Task Id Is Invalid       0x6400     Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x5507New Key Index Is Error0x5508Step Error0x5509Remote Key Injection Timeout (Latest Command Is Timeout)0x550AMac Error0x550BKey Usage Error0x550CMode of Use Error0x550FOther Error0x6000Save Or Configuration Failed / Or Read Configuration Error, Flash Error0x6001CVM Type Unknown0x6002CVM Aip Not Supported0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command - Protocol Is Right, But Task Id Is Invalid0x6400Unsupported Command - Protocol and Task Id Are Right, But Command Is Invalid
0x5508     Step Error       0x5509     Remote Key Injection Timeout (Latest Command Is Timeout)       0x550A     Mac Error       0x550B     Key Usage Error       0x550C     Mode of Use Error       0x550F     Other Error       0x6000     Save Or Configuration Failed / Or Read Configuration Error, Flash Error       0x6001     CVM Type Unknown       0x6002     CVM Aip Not Supported       0x6003     CVM Tag 8E Missing       0x6004     CVM Tag 8E Format Error       0x6005     CVM Code Is Not Supported       0x6006     CVM Cond Code Is Not Supported       0x6007     CVM No More       0x6008     PIN Bypassed Before       0x6200     No Serial Number       0x6201     No White List       0x6900     Invalid Command – Protocol Is Right, But Task Id Is Invalid       0x6A00     Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
Ox5509 Remote Key Injection Timeout (Latest Command Is Timeout)  Ox550A Mac Error  Ox550B Key Usage Error  Ox550C Mode of Use Error  Ox6000 Save Or Configuration Failed / Or Read Configuration Error, Flash Error  Ox6001 CVM Type Unknown  Ox6002 CVM Aip Not Supported  Ox6003 CVM Tag 8E Missing  Ox6004 CVM Tag 8E Format Error  Ox6005 CVM Code Is Not Supported  Ox6006 CVM Cond Code Is Not Supported  Ox6007 CVM No More  Ox6008 PIN Bypassed Before  Ox6200 No Serial Number  Ox6201 No White List  Ox6900 Invalid Command – Protocol Is Right, But Task Id Is Invalid  Ox6A00 Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x550AMac Error0x550BKey Usage Error0x550CMode of Use Error0x6000Save Or Configuration Failed / Or Read Configuration Error, Flash Error0x6001CVM Type Unknown0x6002CVM Aip Not Supported0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command - Protocol Is Right, But Task Id Is Invalid0x6A00Unsupported Command - Protocol and Task Id Are Right, But Command Is Invalid
0x550BKey Usage Error0x550CMode of Use Error0x550FOther Error0x6000Save Or Configuration Failed / Or Read Configuration Error, Flash Error0x6001CVM Type Unknown0x6002CVM Aip Not Supported0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command – Protocol Is Right, But Task Id Is Invalid0x6400Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x550CMode of Use Error0x550FOther Error0x6000Save Or Configuration Failed / Or Read Configuration Error, Flash Error0x6001CVM Type Unknown0x6002CVM Aip Not Supported0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command – Protocol Is Right, But Task Id Is Invalid0x6400Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x550FOther Error0x6000Save Or Configuration Failed / Or Read Configuration Error, Flash Error0x6001CVM Type Unknown0x6002CVM Aip Not Supported0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command - Protocol Is Right, But Task Id Is Invalid0x6400Unsupported Command - Protocol and Task Id Are Right, But Command Is Invalid
0x6000Save Or Configuration Failed / Or Read Configuration Error, Flash Error0x6001CVM Type Unknown0x6002CVM Aip Not Supported0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command – Protocol Is Right, But Task Id Is Invalid0x6A00Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6001CVM Type Unknown0x6002CVM Aip Not Supported0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command – Protocol Is Right, But Task Id Is Invalid0x6A00Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
Ox6002 CVM Aip Not Supported Ox6003 CVM Tag 8E Missing Ox6004 CVM Tag 8E Format Error Ox6005 CVM Code Is Not Supported Ox6006 CVM Cond Code Is Not Supported Ox6007 CVM No More Ox6008 PIN Bypassed Before Ox6200 No Serial Number Ox6201 No White List Ox6900 Invalid Command – Protocol Is Right, But Task Id Is Invalid Ox6A00 Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6003CVM Tag 8E Missing0x6004CVM Tag 8E Format Error0x6005CVM Code Is Not Supported0x6006CVM Cond Code Is Not Supported0x6007CVM No More0x6008PIN Bypassed Before0x6200No Serial Number0x6201No White List0x6900Invalid Command – Protocol Is Right, But Task Id Is Invalid0x6A00Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6004       CVM Tag 8E Format Error         0x6005       CVM Code Is Not Supported         0x6006       CVM Cond Code Is Not Supported         0x6007       CVM No More         0x6008       PIN Bypassed Before         0x6200       No Serial Number         0x6201       No White List         0x6900       Invalid Command – Protocol Is Right, But Task Id Is Invalid         0x6A00       Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6005       CVM Code Is Not Supported         0x6006       CVM Cond Code Is Not Supported         0x6007       CVM No More         0x6008       PIN Bypassed Before         0x6200       No Serial Number         0x6201       No White List         0x6900       Invalid Command – Protocol Is Right, But Task Id Is Invalid         0x6A00       Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6006       CVM Cond Code Is Not Supported         0x6007       CVM No More         0x6008       PIN Bypassed Before         0x6200       No Serial Number         0x6201       No White List         0x6900       Invalid Command – Protocol Is Right, But Task Id Is Invalid         0x6A00       Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
Ox6007 CVM No More Ox6008 PIN Bypassed Before Ox6200 No Serial Number Ox6201 No White List Ox6900 Invalid Command – Protocol Is Right, But Task Id Is Invalid Ox6400 Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6008     PIN Bypassed Before       0x6200     No Serial Number       0x6201     No White List       0x6900     Invalid Command – Protocol Is Right, But Task Id Is Invalid       0x6A00     Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
Ox6200 No Serial Number Ox6201 No White List Ox6900 Invalid Command – Protocol Is Right, But Task Id Is Invalid Ox6A00 Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6201       No White List         0x6900       Invalid Command – Protocol Is Right, But Task Id Is Invalid         0x6A00       Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
0x6900       Invalid Command – Protocol Is Right, But Task Id Is Invalid         0x6A00       Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
Ox6A00 Unsupported Command – Protocol and Task Id Are Right, But Command Is Invalid
and appeared a second and a second a second and a second
Ox6A01 Unsupported Command – Protocol and Task ID Are Right, But Command Is Invalid – In this State
0x6B00 Unknown Parameter in Command – Protocol Task ID and Command Are Right, But Parameter Is
Invalid  Ox6B10 ASN.1 Data Error
Ox6C00 Unknown Parameter in Command – Protocol Task ID and Command Are Right, but Length is Out of
the Requirement.
Ox7300 DUKPT is STOP (21 bit 1)
0x8100 Timeout
0x8200 Wrong Operate Step
0x8300 Decode MSR Error
0x8500 No Swipe MSR Card
0x2C02 No Microprocessor ICC seated
0x2C06 No Card Seated to Request ATR
0x8B10 ICC Error on Power-Up
0xE313 IO Line Low Card Error After Session Start
0x9042 Invalid LCL-KEK
0x9046 Invalid Data Encryption Key

Error Code	Definition
0x9047	Do Not Support This Key
0x9052	Invalid RKI-KEK
0x9054	TR31 Checks Failed
0x9055	DOMAC Verification Failed
0x9057	LCL-KEK Exists
0xF002	ICC Communication Timeout
0xF003	ICC Communication Error
0xF005	ICC Encrypted C-APDU Data Structure Length Error or Format Error.
0xF200	AID List / Application Data Does Not Exist
0xF201	Terminal Data Does Not Exist
0xF202	TLV Format Is Error
0xF203	AID List Is Full
0xF204	Any CA Key Does Not Exist
0xF205	CA Key RID Does Not Exist
0xF206	CA Key Index Does Not Exist
0xF207	CA Key is Full
0xF208	CA Key Hash Value is Error
0xF209	Transaction Format Error
0xF20A	The Command Will Not Be Processing
0xF20B	CRL Does Not Exist
0xF20C	CRL Number Exceed Max Number
0xF20D	Amount, Other Amount, and Transaction Type Are Missing
0xF20E	The Identification of Algorithm Is Mistake
0xF20F	No Financial Card
0xF210	In Encrypt Result State, TLV total Length Is Greater Than Max Length
0xF211	ICC L2 Is Not in Idle State

### 9. Appendix E: Tag DFEE1B

Tag **DFEE1B** can be supplied in **Complete Transaction** to enforce specifics surrounding approvals, declines, or referrals.

The approving processor or gateway Host will provide Tag 8A as part of its response. The two-byte value in 8A needs to be a value the kernel understands, or the kernel will change it to 'Z3' (0x5A33) in the **Completion** step.

Sending a **Result** code to a reader that is not recognized by the kernel will change it to 'Z3' (0x5A33).

**Example**: The kernel may not recognize result code 3035 and instead may change it to to 5A33 ('Z3').

**Solution**: Use tag **DFEE1B** to define the three response codes: **Approved**, **Referral**, or **Decline**.

DFEE1B is defined as 8 bytes long:

- Bytes 0/1 are for **Approved Code**
- Bytes 2/3 are for **Referral Code**
- Bytes 4/5 are for **Declined Code**
- Bytes 6/7 are **Reserved for Future Use** (RFU).

**Example**: If the online host uses 3030 as **APPROVED**, 3031 as **REFERRA**L, and 3035 as **DECLINED**, included the following TLV in the terminal settings:

DFEE1B 08 3030 3031 3035 0000

The kernel will recognize and properly process the transaction when **DFEE1B** is defined with the DECLINE = 3035.

**Note**: You can set DFEE1B on a per-transaction basis. To set the tag on a per-transaction basis send DFEE1B to the **emv\_completeTransaction()** method of the Universal SDK, or provide DFEE1B in the "extra tags" of the **Complete Transaction** parameters in the Universal Demo app.