



Product Datasheet

www.1-light.eu

New 2025 Edition 2>Office & Kitchen

38150A/B/V



CCT and Power variable 40W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with power variable driver

Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions




Gallery



Accessories



050170



050170C/B



Related items



050170D/B/V



38150E/B

Physical Specification

Item Group	New 2025 Edition 2
Family	Office & Kitchen
Order Code	38150A/B/V
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	1200mm
Width	35mm
Height	70mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W-30W-40W
IP Rating	IP20

Light Source
Dimmable
Cable Length
F Mark

LED built in
No
300cm


Fitting

Input Type
IP Rating
Light Source
LED Type

Constant Current
IP20
LED built in
SMD

Gear

Gear Type
Input Voltage
50 Hz
60 Hz
IP Rating
Dimmable
Protection

Led Driver
220-240V
Yes
Yes
IP20
No
0

Illumination Data

Colour Temperature
Lumen Output
Light Efficiency
CRI
Illumination Diagram
UGR

3000K-4000K-5000K
3400lm (40W)
85lm/W
90

19

Packing Info

Pcs/Carton

12



Warranty

3 Years

Weee Directive

Yes

switch to
one light!

