

K	技术要求： 1. 尺寸:展开640*120mm，折后80*120mm 2. 材质:105g铜版纸 3. 颜色:四色印刷 4. 工艺:手风琴8折页 5. 环保要求：所有材料及工艺需满足欧盟WEEE和RoHS指令要求				原材料		PC，松诺白色		指定公差等级			制图日期	黎业军 2024/11/10	物料编码：		单位	比例	图框																																													
					测试项		测试要求		测试项		测试要求			尺寸	等级				A	B	C	00.00.07.0402																																									
					☒	RoHS检测		第三方认证报告 (有效期一年)	☐	低温存储(-40℃)				0<L≤3					±0.05	±0.10	±0.15																																										
					☐	球压试验(125℃/70℃)			☐	冷热冲击(-40~70℃)				3<L≤6					±0.10	±0.15	±0.20																																										
					☐	灼热丝试验(850℃/650℃)			☐	百格测试				6<L≤16					±0.15	±0.25	±0.35																																										
					☐	UV老化测试(72H/48H)			☐	RCA试验(100圈/150圈..)				16<L≤30					±0.20	±0.30	±0.45																																										
					☐	冰醋酸测试(3min/5min)			☐	铅笔硬度测试(3H/4H..)				30<L≤120					±0.25	±0.35	±0.50																																										
					☐	盐雾试验(24/36/48H..)			☐	酒精耐摩擦测试				120<L≤315					±0.30	±0.50	±0.80																																										
					☐	高温存储(70℃)			☐	镭雕/丝印附着力测试				0<L≤10					±1°	50<L≤120	±0.5°																																										
					☐				☐					10<L≤50					±0.3°	120<L≤400	±0.15°																																										
L													审核日期		物料名称：		快速指南 BMT01																																														
1				2				3				4				5				6				7				8				9				10				11				12				13				14				15				16			