Products

Assemble kit

Tech specs

Holder

Fastener for fixing the button on the surface




Devices compatibility

Button Jeweller

Button S Jeweller

DoubleButton Jeweller



Key features

Button fixing

Fix Holder in a place where the button is easy to access.

Quick installation and removal of the button

The button is attached to Holder and detached from it in one movement. There is no need to use tools or waste time.

Enclosure

Material

Plastic

Holder More ~

1.85" × 1.49" × 0.56"

1.49"

Weight

0.12 oz

Operating temperature range

from 14 °F to 104 °F



Operating humidity

up to 75%

Colors

Black



White



Complete set

Holder

Installation kit

Quick start guide

Additional information

Compliance with standards

Learn more

Warranty

24 months

Learn more

Subscribe

Subscribe to our emails about secure life. No spam.



Request extra help

- +18334294824
- support@ajax.systems
- @AjaxSystemsSupport_Bot



Rating 4.7

2,500,000

people worldwide under Ajax protection











Products

Intrusion protection

Video surveillance

Fire and life safety

Comfort and automation

All products

Services

Software

For users

Ajax PRO: Tool for Engineers

Ajax Desktop

Ajax PRO Desktop

Ajax Translator

Scenarios

System integrations

Ajax Ready products

Available on App Store



Solutions

Customer stories

Solutions by facility type

Upgrades and retrofits

How it works

Support

Manuals and articles

Maintenance and repair

Compliance with standards

Tools

Ajax device compatibility

Video storage calculator

Battery life calculator

Radio communication range calculator

Switches and outlets configurator

Fibra power supply calculator

All web tools

Company

Blog

About us

Press page

Events

Career

Reviews and feedback

For partners

For partners

Ajax Academy

Partner Portal

United States Privacy policy Report a vulnerability GDPR White Paper NDAA Statement

Do Not Sell My Personal Information Anti-Spam Policy End user agreement Warranty

© 2025 AJAX SYSTEMS CH. All rights reserved