60cm Stainless Steel Canopy

RANGEHOOD

PRODUCT CODE: **EA60SX2**



FEATURES:

- Stainless steel finish
- 3 speed motor
- 700m3/hr extraction capacity
- 2 x 1.5w LED lights

- Separate light function
- Electronic button front controls
- Dishwasher safe cassette filters
- 150mm air flow outlet

DISHWASHER SAFE CASSETTE FILTERS

The cassette filters can be placed in a dishwasher for easy cleaning and can easily be removed, re-connected from the rangehood.

DECIBEL RATING

58 - 62 dBA

3 SPEED MOTOR

This rangehood provides the option of 3 different speed levels ensuring you have the option to use your rangehood at a low, medium or high level of operation.

HIGH EXTRACTION CAPACITY

The extraction capacity of 700m3/hr provides strength and power to this stylish rangehood.

Electrical Requirements Rangehood is supplied with 10amp cord & plug. 58 - 62 dBA **Decibel Rating**

Available Ventilation Kits

Wall – Eave vent kit RHKE65EU Universal metal roof kit (includes flashing) RHKMR65EU Universal tile roof kit (includes flashing) RHKTR65EU

Flue Extension 1m Code: ERCEXT **Rangehood Extension**

CF110 (requires 2) Carbon Filter

8.5kg (net) 10.5kg (gross) Weight

9347726027876 Barcode

eurø cooking



HELPFUL TIPS

- Leave your rangehood on for 15 minutes after the cooking of the food to remove all odors,
- The dishwasher-safe cassette filters need to be cleaned after approximately 2 months of standard operation
- It is recommended that the rangehood be installed between 650mm and 750mm above the cooktop
- It is also recommended that fumes from the rangehood be ducted out into the atmosphere.
- Turn off the rangehood before attempting to

INSTALLATION

Installation is recommended by a qualified installer, please refer to the product manual for full installation instructions

FILTER CLEANING INFORMATION

Cassette mesh filter: Requires cleaning monthly. This will ensure no interruptions with airflow operation.

