## Hisense





- · Low Noise Cooling System
- Long Distance and Centralized Air Flow
- · Cool, Dehumidify, and Fan Functions
- Remote Control is Included
- 2-year Warranty



3 Modes - Cool, Dehumidify, and Fan



**Quiet Operation** 



**Drain-free Operation (Cooling mode)** 



**Easy Snap-Together Window Kit** 

### Cool Comfort – Quiet, Convenient, and Quick Installation

The Hisense AP0721CR1W Portable Air Conditioner provides convenient performance. Long-distance airflow is strong, cool, and quiet because of the new air flow design. Additionally, the air louver automatically opens to a preset position after the unit is powered on and can be adjusted with the included remote. The easy-to-install snap-together window kit fits windows 18" to 50" wide, helping preserve the external appearance of your home.

# Hisense



Model AP0721CR1W

Model #	AP0721CR1W
Performance	
Maximum Cooling space	300 sq.ft.
Cooling Capacity-SACC (BTU)	7.000
CEER	6.9
Dehumidification Pint / 24 hr	67.2
(at 26.7 / 19.4' C)	
Refrigerant	R·32
Airflow (CFM)	222 – 241
Noise Level in dB(A)	49 - 52
Electrical	
Voltage / Freq / Amps	115V / 60Hz, 12A* / 10.6A
Plug Type / NEMA#	A / 5-15P
Power Cord Length (feet)	4.9
Control Features	
Unit Control Type	Electronic
Fan Control	Button
Thermostat Control	61 - 86°F
Display Type	Dimmable LED
Sleep Mode	Yes (on remote)
DehumidifierMode	Yes
Cooling Speeds	3 Speeds
Temp Display Units	∘ c/∘ <b>F</b>
Timer	1 Hr - 24Hr On/Off
Auto Restart	Yes (after power is restored)
General Features	
Removable Filter	Yes
Washable PP Filter	Yes
Oscillating Air Vent Louvers	Yes (on remote)
Vent System	Single Hose, 5, 9"0 x 59"L
Accessories	
Remote Control	Yes
AAA Batteries	Yes
Air Hose	Yes
Window Kit	Yes
Approvals	
Safety	ETL
Energy Star	No


Product Dimensions		
Unit Dimension W x H x D (mm)	433 x 708 x 320	
Net Weight (Kg)	26.5	
Unit Dimension WxHxD (inch)	16.9 x 27.4 x 12.8	
Net Weight (lbs)	58.4	
Product		
Parts & Labor	2 years	
UPC	819130027302	

#### Note:

#### **Control Panel**



#### Window Size



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise.

©2021HisenseUSA, All rights reserved

Hisense USA Corporation 731o McGinnis Ferry Road. Suwanee, GA, 30024 I ·877-465-3566 www.hisense-usa.com

<sup>\*:</sup> Rated Amps(A) / accorded UL 60335 Safety