

Unitronics

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Unitronics Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Unitronics Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Vision V430-J-T2	
V120-22-UN2	V120-22 OPLC,12/12IO,2 UNIV
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
450.72.UNT.10	USL-070-B05 HMI 7"
450.71.UNT.10	USC-B5-TR22 PLS 2 AI-10DI , 12 TO- 8 RO
1X2X0,34MM2 BUS CAN UNITRO.2170263	Cable
V570-57-T20B-J	Vision V570 COLOR OPLC, WL,5.7", TOUCH, no Frame
V1210-T20B-J	V1210 COLOR OPLC,12.1", TOUCH, NoB
V570-57-T20-B	V570 COLOR OPLC, WL,5.7", TOUCH
EX-A2X	Expansion adapter, isolated
IO-AI8	8 Analog Input module
IO-TO16	16 digital outputs module
SM35-J-R20	SM35-R20,3.5",12/8 I/O,2A,1HS
SM35-J-T20	SM35-T20,3.5",12/8 I/O,2A,3HS
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS

V200-18-E1B	IO MODULE,16/10 IN/RELAY OUT,ISO
V200-18-E1B	IO MODULE,16/10 IN/RELAY OUT,ISO
V130-33-RA22	V130-RA22 OPLC,WL DIS,12/8 IO
V100-17-CAN	MODULE,CANbusINTERFACE FORV130
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
UIA-0800N	UniStream IO, 8AI,NO ISO
UID-0808T	UniStream IO 8DI,8TO,24V
V570-57-T20B-J	V570 COLOR OPLC,WL,5.7",TOUCH - NO LCD FRAME
EXL-CAB1000	CABLE,XL-EXP-PLC,RJ45-RJ45,10m
BUS PB FD P A - : 2170822	
V130-33-T38	V130-T38 OPLC,WL DIS,22I,16O,2A
EX-RC1	REMOTE I/O ADAPTER
UNITRONICS V200-18-E3/4XB	
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
V200-18-E4XB	IO MODULE,18/17IN/TOUT,4UN/AN,IS
IO-D16A3-TO16	XL-EXP,16I,3AI,16TO
IO-TO16	16 digital outputs module
EX-D16A3-TO16	XL-EXP,ADPTER,16I,3AI,16O
IO-AI4-AO2	4 in / 2 out analog module
EX-A2X	Expansion adapter,Isolated
V200-18-E3XB	IO MODULE,18/17IN/OUT,4UNI/AN,IS
V200-18-E4XB	IO MODULE,18/17IN/TOUT,4UN/AN,IS
USP-070-B08	UniStream 7" HMI PANEL B08
UIS-04PTN	UniStream IO, 4PT100
UID-0808R	UniStream IO 8DI,8RO,24V
UIA-0006	UniStream IO, 6AO,NO ISO, 24V
V700	
V570 TOUCH SCREEN	
X-A2X I/O EXPANSION MODULE	
EX-D16A3-TO16-	XL-EXP,ADPTER,16I,3AI,16O
EX-A2X - Expansion adapter,Isolated	
V200-18-E46B - IO MODULE,ISO 18/17I/O,9ANA,2AO	
V200-18-E4XB - IO MODULE,18/17IN/TOUT,4UN/AN,IS	
V200-18-E5B	IO MODULE,18/17IN/TOUT,4AIN,IS
Io-T016 I/O	

Ex-D16a3-To16 I/O.	
280-18-B20b Plc	
280-18-B20b	
M90-R1-Can	Operator Panel
V290-19-B20b	5.7" Monochrome Touchscreen
Eu210154 Ex-A2x	
Vision120-22-R34	PLC, Vision, 2.4 "b / w LCD, 20DI, 12RO, 2AI 11.04.19 Item No .: 111473 µ-PLC with graphic display and keyboard: - Display: FSTN LCD (128x64) 8x20 characters Keyboard: 16 membrane keys - Program size: 448 kWord, real-time clock - 1 RS-232 (RJ11), 1 RS-485 (RJ11) - I / O extension (RJ45), MODBUS and GSM support Zung - Panel or DIN rail mounting, front IP65 - Including programming software and serial cable - 20 digital inputs (24VDC), of which 3 as counter (10kHz, 32 bit) - 12 relay outputs (230VAC / 5A, 10Hz) - 2 inputs as analog inputs (10Bit; 0-10V, 0 / 4-20mA) or as 2 additional digital inputs (24VDC) - Power supply 24 VDC - incl. programming software and cable, assembly instructions erial
Io-Ao6x	
Jz10-11-R16 - Obsolete , Alternative Is Jz20-J-R16	
I0-Di16 I/O	
V130-33-R34	
V280-18-B20b	Product: Unitronics Vision V280-18-B20B
Io-Di8-Ro8	
V130-33-T2	10 DIGITAL INPUTS
111625	
112270 Jz-Prg	
109564	
107881	
Acs355-03e-12a5-4.3f/3f	DRIVER
V200-18-E2b	PLC I / O module, 16DI, 10RO, 4TO, 2AI, 2AO Item No .: 106929 Snap-in I / O Module: - 16 digital inputs (24VDC) of which 2 as Counter (10kHz, 16 bit) isolated in groups of 8 inputs. Isolation 1KV - 4 digital outputs (24VDC / 0.5A) thereof 2 as high speed output (max. 50kHz) isolated in a group of 4 outputs , Isolation 1KV - 10 relay outputs (230VAC / 5A, 10Hz) - 2 analog inputs 10bit (0-10V, 0 (4) -20mA) - 2 analog outputs 12bit (0-10V, 0 (4) -20mA)
M91-2-R2c	
2170334	
V120-22-R1	
Eu210068 Io-Pt400	
Io-Lc1	
Io-Ro16	PLC remote I / O, 16RO (24VDC) Item No .: 106948 - Relay outputs (230VAC / 24VDC, 10Hz): 16 outputs - Relay type: SPST-NO - 5A resistive load, 1A inductive load - DIN rail mounting - Dimensions:

80mm x 93mm x 60mm, 125g - only in conjunction with EX-A1, EX-2AX u. EX-Maxi Modules - Supply voltage 24VDC	
117824 Vision130-33-Ta24	
121358	
101262	
V200-18-E3xb I/O	
120336 Jz10-11-Un20	
Jz-Rs4	
Sm35-J-R20	
Io-Di16	PLC remote I / O, 16DI (24VDC) Item No .: 101262 - Digital inputs (24VDC): 16; - counter (10kHz, 16 bit): 1; - DIN rail mounting - only in conjunction with EX-A1, EX-2AX u. EX-Maxi Modules - Supply voltage 24VDC - Dimensions: 80mm x 93mm x 60mm, 141g
M91-2-R1	
126642	
101264	
107882	
Eu210045 , V200-18-E3xb	
V130	PLC Operator Panel
01 M91-2-R34 Serie Oplc	
Io-Ai8	
Io-Atc8	
Li2ycy Pimf 3x2x0,Lapp0034041	
Ex-A2x (Successor To Ex-A1)	PLC expansion adapter, for PLC I / O module, insulated Art. No .: 126453 - Extension adapter for M90 / 91 / Vision series - incl. cable (1,0m) - supports up to 8 extensions - Connect using the supplied cable proprietary bus - Supply voltage 12 / 24VDC - Dimensions: 80mm x 93mm x 60mm, 125g
114157 Jz-Rs4	
Jz10-11-T40	
V1040-T20b	10.4" COLOR TOUCH SCREEN, TFT, USB PROGRAMMING PORT, MICRO SD CARD SLOT, 800 X 600 RESOLUTION (SVGA), 65K COLORS, WHITE LED-ILLUMINATED BACKLIGHT,9 PROGRAMMABLE FUNCTION KEYS, UP TO 1024 I/OS
121354	