



HYDROFRESH 24 CL

COMPONENTS INCLUDED

- ※ Single-phase pump
- ※ Expansion tank
- ※ PSG-1 pressure switch
- ※ Pressure Gauge
- ※ Flexible hose
- ※ Brass fitting
- ※ 1.5 metres cable with Schuko plug

INSTALLATION AND USE

The **HYDROFRESH** group is designed for residential water supply or irrigation purposes and is available with a **24 litres** or a **60 litres** horizontal expansion tank. This cost-effective, ready-to-use system improves pressurization through two key features:

- an **expansion tank** designed to reduce the number of times the pump needs to turn on and counteract any loss of water pressure that occurs when you open a faucet
- a **pressure switch** that automatically controls the pump operation

TYPE	POWER (P ₂)		CAPACITY litres	FLOW RATE (1) litres/min	CALIBRATION (2) bar
	kW	HP			
HYDROFRESH 24 CL					
FUTURE JETm 1A - 24 CL	0.55	0.75	24	90	1.2 – 3.2
FUTURE JETm 2C - 24 CL	0.75	1	24	110	1.2 – 3.2
FUTURE JETm 1A-ST - 24 CL	0.55	0.75	24	90	1.2 – 3.2
FUTURE JETm 2C-ST - 24 CL	0.75	1	24	110	1.2 – 3.2

HYDROFRESH 60 CL

FUTURE JETm 1A - 60 CL	0.55	0.75	60	90	1.2 – 3.2
FUTURE JETm 2C - 60 CL	0.75	1	60	110	1.2 – 3.2
FUTURE JETm 1A-ST - 60 CL	0.55	0.75	60	90	1.2 – 3.2
FUTURE JETm 2C-ST - 60 CL	0.75	1	60	110	1.2 – 3.2

(1) Maximum flow rate corresponding to the minimum set pressure of the pressure switch

(2) Pressure switch calibration (recommended)

DIMENSIONS AND WEIGHT

HYDROFRESH 24 CL	DIMENSIONS mm			WEIGHT kg
	l	a	h	
FUTURE JETm 1A - 24 CL	535	255	520	18.7
FUTURE JETm 2C - 24 CL			530	22.0
FUTURE JETm 1A-ST - 24 CL			560	15.8
FUTURE JETm 2C-ST - 24 CL			570	19.2

HYDROFRESH 60 CL

FUTURE JETm 1A - 60 CL	730	340	657	23.7
FUTURE JETm 2C - 60 CL			675	27.0
FUTURE JETm 1A-ST - 60 CL	730	340	678	20.8
FUTURE JETm 2C-ST - 60 CL			703	24.2

