

VAR TECH®

Quality • Reliability • Economy

DIGITAL MULTIMETER

Model : V 92 S

3 5/6 Digits (6000 Counts)

Auto Ranging

TRUE RMS SMART

Primary & secondary display
Auto Ranging Cap., Freq., Test.,
& Temperature Measurement

A.P.O., NCV, D/H, B/L

& Torch

A/V Continuity & Diode Test

WITH HOLSTER



SPECIFICATIONS		
DC Voltage	Range	600 mV, 6 V, 60 V, 600 V
	Basic Accuracy	± (0.5 % rdg + 3 digits)
AC Voltage (True RMS)	Range	6 V, 60 V, 600 V
	Basic Accuracy	± (1 % rdg + 3 digits).
DC Current	Range	600 mA, 6 A, 10 A
	Basic Accuracy	± (1.2 % rdg + 3 digits)
AC Current (True RMS)	Range	600 mA, 6 A, 10 A
	Basic Accuracy	± (1.2 % rdg + 3 digits).
Resistance	Range	600 Ω, 6 K Ω, 60 K Ω, 600 K Ω, 6 M Ω, 60 M Ω
	Basic Accuracy	± (1 % rdg + 5 digits)
Capacitance	Range	6 nF, 60 nF, 600 nF, 6 μF, 60 μF, 600 μF, 6 mF, 60 mF
	Accuracy	± (3.5 % rdg + 20 digits)
Frequency	Range	6 Hz, 60 Hz, 600 Hz, 6 KHz, 60 KHz, 600 KHz, 6 MHz, 10 MHz
	Basic Accuracy	± (1 % rdg + 3 digits)
Temperature	Range	- 40 °C ~ 1000 °C (-40 °F ~ 1832 °F)
Other Facilities / Features		NCV, Torch, ACV Freq., Measurement, A/V Continuity Test, Diode Test, LCD Back Light, Data Hold, Auto Power Off, Low Batt., Ind., Jack & Burnt Fuse Prompt, Intelligent Mode.
Accessories Supplied		Holster (Installed), Test Leads, User Manual, Battery - 4 x AAA (Installed / Kept Aside) - Optional & Temperature Probe.
Dimension & Weight		146 x 72 x 50 mm & Approx. 235 gms. (With Batt. & Holster)

* All Specifications & appearances are subject to change without prior notice.