



BlueTooth Amp BTA-AC30-2C



Installation

- 1) Find a suitable location not subject to water immersion.
- 2) Make all speaker connections prior to plugging Blue Tooth Amp into AC Power Source.
- 3) Assure Positive (+) & Negative (-) amp outputs are connected properly to (+) & (-) Speaker Terminals. See Product Label. Failure to connect speakers properly can cause amp/speaker failure.
Note: It is recommended to use fully insulated crimp terminals (FISO) on speaker tabs.
- 4) It is recommended to plug into a switchable power plug , or , plug/unplug unit manually after each use. Unit does not have an on/off button.
- 5) Secure amp to a firm surface .

Amp Pairing

- 1) Connect Speakers, turn on Amp.
- 2) Listen for pairing tone.
- 3) Search device (phone/laptop/pad) for BAMP0240.
- 4) If device asks for PIN Code enter 8888. Allow device to pair.
- 5) Amp is now connected. Volume is controlled by user device .

Technical

Model: BTA-AC30-2C
Input: AC 100-240V , 50/60 Hz, 1A
Output: 2 Channel
Waterproof: IPX6
Bluetooth: Qualcomm 5.0
Power: 30W Channel @ 4 Ohms / 20W Channel @ 6 Ohms
Freq. Resp: 20Hz - 20KHz
Dimen: 8" x 4.5" x 2"
Weight: 12.3 Oz

Warnings

No Serviceable Parts. DO NOT Open.
Risk of Shock.
Handle with care to avoid damage. Do Not Drop.



Listen To PQN Innovation

PQN Enterprises, Inc.
Morro Bay, CA 93442
sales@pqnaudio.com
www.pqnaudio.com

Warranty Policy

PQN Audio products are warranted to be free of manufacturing defects for a period of one (1) year. Warranty is subject to proper installation & application. Warranty does not cover exposure to excessive chemical usage or operational abuse. Return defective product prepaid to point of purchase for replacement or refund as determined by PQN. Warranty is not transferable. Proof of Purchase must be included.

PQN Audio Products are tested to the highest standards. User assumes all responsibility for misuse of product.