

Water Spot Sprinkler
Asperseur d'Eau Static
Aspersor de Agua
MOD: 400003



1. IMPORTANT SAFEGUARDS

Read these instructions before use. If this product is passed to a third party, these instructions must be included.

When using the product, safety precautions should be followed to reduce the risk of injury, including:

- For outdoor use with cold water only.
- Do not use near electrical components.
- Check all parts before using the product. Do not use if parts are damaged.
- Operate in an upright position only.
- Do not modify the product.
- Turn the water off after each use.
- Do not use the product for any other purpose for which it was not intended.
- Do not operate at high water pressure, see Section 7.
- Do not leave water running or unsupervised.
- Do not expose the product to freezing temperatures with water remaining in the product.
- This product is not intended to handle drinking water.



DANGER Risk of suffocation! Please remove and keep packaging materials away from children and pets.

2. Intended Use

- * This product is intended to water a lawn or garden patch.

3. Product Description

- A** Fixing nut to hose
- B** Sprinkler body



- C** Intake filter

4. Product Usage and Function

CAUTION

Risk of damage! Please ensure the water supply does not exceed the maximum pressure.

- * Position the sprinkler on the surface, making sure the Base is level and upright. Do not operate the sprinkler with a tilted Base.
- * Attach the garden hose to the Fixing nut.



- * Turn the water tap on. Water comes out the selected nozzles on the wheel.
- * After use, turn off the water supply and disconnect the sprinkler from the hose.

4.1 Operating tips:

- * Remove any obstructions which can interfere with the water spray.
- * Water at cooler temperatures to minimize loss to evaporation, e.g. mornings.
- * Water for a period of at least 30 minutes to obtain deep root moisture.
- * Install a sediment filter to the garden hose to minimize clogging of the nozzles.
- * Coverage is very important to maximize the use of the water and minimize loss of water on other surfaces, e.g. paved roads.
- * We suggest some initial observation of the working sprinkler to ensure coverage is satisfactory.
- * After use, drain water from the product.

4. Cleaning and Storage

4.1 General cleaning.

- * To clean, wipe with a soft, damp cloth. Microfiber preferred.
- * Never use gasoline, acetone, or any other corrosive chemicals. Never use metal brushes or sharp utensils to clean the sprinkler.

4.2 Storage.

- * Drain water out of the product before storage.
- * Avoid storing the product at conditions below 32°F.

4.3 Unclogging the nozzle.

- * Use any fine metal pin or paper clip.



5. Frequently Asked Questions

Problem:	Solution:
The Sprinkler Wheel has single spray pattern	When the water pressure is too low, the spray is very weak <ul style="list-style-type: none">* Check for a partially open tap.* Check for an obstruction in the hose, e.g. kink.* Clean the Intake filter.
The Sprinkler does not water	Remove any obstructions which could interfere with the operation of the tube <ul style="list-style-type: none">* Check for water flow.
The spray patter is irregular	Remove any obstructions in the nozzles <ul style="list-style-type: none">* Unclog the nozzle.* Rinse the product.
The nozzle clogs frequently	<ul style="list-style-type: none">* Install a sediment filter to the water supply.* Replace the hose.* Change water supply.

6. Specifications

Working pressure	20 – 60 psi	Storage temperature	33°F – 105°F
Flow rate	2.0 – 4.0 gal/min	Weight	4 oz
Operating temperature	33°F – 105°F	Dimensions (in)	4" x 3" x 2"