

Alphacool ES quick release connector kit G1/4 IG/IG - PushIn Industry Version

Alphacool article number: 17569

Aquatuning article number: 1020306

The Alphacool ES Quick Disconnect Fittings Industry IG/IG are taken from the Alphacool Enterprise Solutions product range. The connections are G1/4" male threads. Special emphasis has been placed longevity and safety.

ES quick release connector



- G1/4" female connectors
- Space-saving design
- Made of durable nylon

Compatibility

Compatibility	G1/4" male connectors
---------------	-----------------------

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Scope of delivery

1 x Alphacool ES quick release connector kit G1/4 IG/IG - PushIn Industry Version

1 x Locking tool

1 x Unlocking tool

Data

L x D	75 x 20 mm
Net weight	23 g
Material	Nylon
Threads	2 x G1/4" female
Thread length	8,5 mm
Type of quick release connector	Push In
Bore diameter	8 mm

Download Links

Product pics	https://www.alphacool.com/download/1020306_ES_QDC_pics.zip
--------------	---

Packaging dimensions 1 unit

L x W x H	8,8 x 3,5 x 3,5 cm
Total weight	34 g

Other data

Certification	CE, FC, RoHS
EAN	4250197175962
Customs number	39174000990

We assume no responsibility for any typing errors.

Alphacool International GmbH, Marienberger Strasse 1, 38122 Braunschweig Tel: (+49)0531 288 740 Supportmail: info@alphacool.com

Article text

The Alphacool ES Quick Disconnect Fittings Industry IG/IG are taken from the Alphacool Enterprise Solutions product range. The connections are G1/4" female threads. Special emphasis has been placed on high tensile strength and safety.

Enterprise Solution?

Alphacool offers specialised water cooling products for servers and workstations in the B2B and Enterprise Solution area. When used for these applications, water cooling must be secure and safe. To ensure these criteria is met, Alphacool has concentrated on 3 main targets for the quick release fittings: a secure leak proof link, high tensile strength and a particularly low weight.

Compact Quick Connector?

Common quick connectors can have a diameter of over 24mm. This Alphacool quick release connectors has a diameter of only 20 mm. This makes it probably one of the sleekest quick release connectors for water cooling systems on the market. To close the quick-release fastener, it only needs to be pushed together. To open it again, a small ring is pulled back. This makes the quick-release fastener pop open. The water loss is minimal and consists of only 1-2 small drops which can easily be halted with a towel or cloth.

Nylon as material?

Instead of the usual brass, the fittings for the Enterprise Solutions product range are usually made of nylon. In water-cooled servers and workstations, all components must be easily and quickly replaceable and keeping the weight down is important. That is why all components are fitted with quick release fasteners. Due to the high packing density in modern servers, the quick release fastener is made of highly stable nylon. They are therefore non-conductive and cannot cause any short circuits. Nylon is also an ultra-light material, which makes it extremely easy to use.

Flow and sealing

In servers and workstations with multiple processors and graphics cards, many components must be equipped with quick connectors. With conventional quick-connectors, narrow water channels will restrict the flow. With the Alphacool quick release connectors, which were developed especially for such solutions, the water flow is optimised to keep the resistance as low as possible. As with all Alphacool quick-release fasteners, this version also uses a double seal to ensure maximum tightness and therefore maximum safety. To further increase safety, a locking clip is also included to prevent accidental opening of the quick release fastener. An unlocking clip makes it easier to open the quick-release fastener if required.

Lightweight, extremely thin, high security and the non-conductive material are the basic characteristics of this quick release connector which has been developed especially for industry and servers.