

Nova series LED high bay light

 Wattage	150W; 200w	 Beam Angle	110°	 Waterproof Rating	Waterproof (IP65)
 Color Temperature	5000K	 PF	>0.9	 Light Decay	<5%
 Efficacy	130LM/W	 DIMMABLE Dimming	No	 Certification	UL Listed
 Input Voltage	120V	 Lumens	19500LM; 26000LM	 Operating Temperature	-22° F - 122° F
 Lifespan	50,000 hours	 CRI	>80	 Warranty	5 Years
 Housing Materials	Aluminum	 Housing Color	Black	SPECIFICATIONS	



US Hook



5.9FT Cable with
3- prong plug



Ultra-thin Design

Advantages

1. UL cUL certificate.
2. Lumileds or Bridgelux Chip, high CRI.
3. Input voltage 120VAC.
4. No UV or IR in the beam.
5. Easy to install and operate.
6. Energy saving, long lifespan.
7. Light is soft and uniform, safe to eyes.
8. Instant start, NO flickering, NO humming.
9. Green and eco-friendly without mercury.

LED High Bay Light Installation Instruction

Cautions:

1. Can not use the electric generator to test the LED light.
2. Please abide by related country, regional and local law and regulations when install this fixture.
3. Please turn off the power before installation or maintenance.
4. Proper earth grounding is required to ensure safety.

Notice:


1. To avoid possibility of electrical shock or fire, the installation personnel must have professional electric knowledge.
2. Please wear gloves to avoid injury before installation.
3. If any smoke or spark of the wire happened, please turn off the power immediately and notify relevant personnel.
4. The luminaire shall be mounted directly below an outlet or junction box.
5. The cord shall be visible over entire length and cannot be concealed.

Attention:

1. Please check if there is any damage during shipping. If so, please contact manufacturer timely.
2. Please read the installation instruction carefully to check whether all the accessories are complete. After confirmation, then install the fixture according to installation steps.

Wiring Diagram & Instruction:

1. The length of the plug wire is 1.8m(5.9ft)
2. The input voltage is 120V



3 Installation Methods: Hook Mount

(Please choose the most suitable installation method for the purchased product as per your needs.)

A. Hook Mount:

1. Please screw the lifting ring into the high bay light fixture, then tighten firmly. (Figure 1)
2. Please hang the fixture into the lifting hook or chain and protect it from falling. (Figure 2)
3. After installation, please wire in accordance with local connection standard, and make sure there is a good joint protective measures.



Figure 1




Figure 2