

Cloud

NO MORE Eye4 Security Center
SECURITY VULNERABILITY
WORRIES!

- ✓ Account remote login reminder
- ✓ Weak password prompt
- ✓ Mobile phone and email address
- ✓ Gesture password

You Are Here: [Home](#) > [Video Surveillance](#) > [Home IP Camera](#) > [C93 IP Camera](#)

Video Surveillance

Home IP Camera

Professional IP Camera

HD Network Video Server

Security System

Alarm Camera

Alarm Detector

Alarm Center Solutions

Smart Shop Solutions

Baby Monitor

C81

Smart Home/Smart Shop

WiFi Smart Unit

Smart Host

Accessory

C93 IP Camera



Product Name: C93 IP Camera

Model No.: C93

Product Abstract:

C93 IP Camera Dual IR-CUT Filter auto switch, 1pcs 850nm
42Mil LED,5m IR distance



Product Description

Model : C93		
System	OS	Embedded Linux OS
	System security	Three level user authority management
	Online visitor	Support 4 online visitors simultaneously
	Free DDNS	Support ONVIF 2.4,Universal agreement, enhanced product interoperability.
	Processor	Hisilicon processor, built in ARM926 @Max. 440MHz and high-speed video co-process
Collection	Sensor	1/4 720p progressive CMOS sensor
	CMOS	support AWB, AGC, AE
	Sensor size	3.84mm×2.16mm
	SNR	≥39dB
	Minimum illumination	0.8Lux/F1.4（colourful model）,0.3Lux/F1.（B&W mode）
	Lens/viewing angle	3.6mm@F1.4 /56.14°
	Night vision	Dual IR-CUT Filter auto switch, 1pcs 850nm 42Mil LED,5m IR distance
	IR control	IR turned on: night vision view enabled, infrared Ray, ICR auto detect. R turned off: night vision disabled, infrared ray off, ICR stay in day view mode.
Video	Compression format	H.264 Main Profile/H.264 Baseline Profile/MJPEG/JPEG Baseline
	Video coding	Multi stream: 720P@30fps+VGA@30fps+QVGA@30fps+720P @1fsJPEG capture
	Resolution	720p/VGA/QVGA
	Bit rate	CBR/VBR, output bit rate range: 128~4096kbps
	Frame rate	30fps/24fps（720p）
	Picture adjustment	Contrast, Brightness, Saturation are adjustable.

Sales

Support

Support

Audio	Input	1 Channel Internal -48dB Microphone
	Output	Internal speaker(8Ω0.8W)
	Sampling frequency /width	8KHz/16bit
	Compression format	ADPCM/32kbps
Network	Protocol	TCP/IP,HTTP,TCP,UDP,SMTP,FTP,DHCP,DNS,DDNS,NTP,UPnP,RTSP,4EP2P,and so
	WIFI	WiFi802.11b/g/n
	Security	WPS encryption
Alarm	Detection	motion detection
	Action	Image E-mail/FTP image upload
Features	Rated Voltage	DC5±0.3V
	Power supply interface	Micro USB
	Power consumption	Rated power: 3.2W (IR opening)
	Working environment	Working temperature: -10 to 50 °C, working humidity <90%
	Weight	Gross weight: (note: in kind prevail)
	Package size	(L×W×H)
		Note:Only for reference

请您留言

VStarcam
sales@vstarcam.com

请在此输入留言内容，我们会尽快与您联系。（必填）

Email（必填）

Tel（必填）

发送


Related Products




C7838WIP HD



C7837WIP Home
monitoring IP
Camera




C7835WIP HD




C93 IP Camera



C7823WIP Mini



C7824WIP HD




Eye4 C42 IP



C37A
1.3MegaPixel
IP ip camera



C38A 960p IP
Camera



Eye4 C25 IP
Camera

C37A

C38A 960p IP

Eye4 C25 IP

Inquiry Information

* Subject:

* Content:

* Telephone Number:

* Your E-Mail:

* Confirm Text:

GSLP

Send

Reset

[Return Home] [Print] [Go Back]

About Us

Profile
Certificate
R & D Team
Innovation
Contact Us

Innovation

Innovations
R & D Center

Products

Video Surveillance
Security System
Baby Monitor
Smart Home/Shop

Services

Online CD
Video Center
BBS
Support & Help

Partner

Join Us
VStarcam Agent
Announcement

News

Coming Exhibition
Company News

Sales Tel:

+86(755) 33953177

Email:

sales@vstarcam.com

Follow:



Follow Us WeChat



Sales

Support

请您留言

VStarcam
sales@vstarcam.com

请在此输入留言内容，我们会尽快与您联系。（必填）

Email（必填）

Tel（必填）

发送