



INSTRUCTION GUIDE

Commercial Wall Washer

Model No. SLDWW-3W

FEATURES

- 1 x Light fixture



FEATURES

1. Automatic Day/Night Operation
2. Adjustable LED Tube and Bracket
3. 2 Lighting Modes;
Mode 1 - 100% brightness for 6 hours then 15% brightness until dawn
Mode 2 - 100% brightness for 5 hours then 15% brightness for 6 hours
4. Surface Mounted Base

INSTALLATION METHOD

1. Remove contents from packaging and if applicable remove film from solar panel.
2. Switch your light fitting **"ON"** by pressing the **"ON/OFF"** button for 3 seconds, to turn **"OFF"** repeat this 3 second press and your light will switch off.

NOTE: Before continuing, we recommend you put your light in direct sunlight (with the switch in the **"OFF"** position) for 2 days before installation.

3. Decide where to mount your light fitting (**Please remember to choose a location where your light will be exposed to a minimum of 6hrs direct sunlight each day**)
4. Using 4 screws, fix the surface mounted bases in your desired location.
5. To adjust the direction of the lamp, simply unscrew the Torx screws on each side of the fitting and adjust the light within 90 degree in your desired direction. Once you have chosen your light angle, re-tighten the Torx screws.

LIGHT MODES

- **Mode 1** - 100% Brightness for 6 Hours, then 15% Brightness until dawn
- **Mode 2** - 100% Brightness for 5 Hours, then 15% Brightness for 6 Hours

To choose your desired mode, press the **"ON/OFF"** button once, when in **Mode 1** a **RED** indicator light will flash, press again for **Mode 2** and a **GREEN** indicator light will flash.

IMPORTANT NOTES

- **Please ensure you place your Solar Panel in a location where it can achieve a minimum of 6HRS DIRECT SUNLIGHT**
- Be aware that on overcast/cloudy days, the solar panel will still charge. However, not as efficiently as a sunny day, so the battery may not reach full capacity. Therefore, your light may turn off earlier than specified.
- It's best not to install these lights underneath a street light, porch light etc. because this may stop the automatic day/night operation triggering and result in your lights not turning on.

TROUBLE SHOOTING

Phenomenon	Cause	Inspection Method	Solution
Light won't turn on	Switch hasn't been turned on	Determine what position the switch is in	Turn the switch on
	Battery has run flat	Period of rainy or cloudy weather or installation site doesn't provide enough direct sunlight	Charge the light in direct sunlight for 1-2 days then check again
The light only stays on for a short amount of time	Low Battery	1. Bad installation site for the solar panel 2. Dust or leaves are covering the panel 3. Long period of overcast weather	1. Charge the battery in direct sunlight for 1-2 days with the switch off, then check again 2. Clean the solar panel
	Battery Failure	1. Access the light and & replace battery 2. Battery has matured	Contact SLD Customer Service to buy new batteries

