

Standard

Standard

Professional Displays

SQ2H

4K intel

*Actual Resolution: 3840 x 2160p

• DisplayPort(Ver. 1.2)

*1: Some functions are limited.

AG G *only applies for 43-65"

TH-98SQ2H 700cd/m² 24/7 Operation USB Media Player Portrait

TH-86SQ2H 700cd/m² 24/7 Operation USB Media Player Portrait

TH-75SQ2H 700cd/m² 24/7 Operation USB Media Player Portrait

TH-65SQ2H 700cd/m² 24/7 Operation USB Media Player Portrait

TH-55SQ2H 700cd/m² 24/7 Operation USB Media Player Portrait

TH-50SQ2H 700cd/m² 24/7 Operation USB Media Player Portrait

TH-43SQ2H 700cd/m² 24/7 Operation USB Media Player Portrait

SQE2

4K intel

*Actual Resolution: 3840 x 2160p

• DisplayPort(Ver. 1.2)

*1: Some functions are limited.

AG G *only applies for 43-65"

TH-98SQE2 500cd/m² 24/7 Operation USB Media Player Portrait

TH-86SQE2 500cd/m² 24/7 Operation USB Media Player Portrait

TH-75SQE2 500cd/m² 24/7 Operation USB Media Player Portrait

TH-65SQE2 500cd/m² 24/7 Operation USB Media Player Portrait

TH-55SQE2 500cd/m² 24/7 Operation USB Media Player Portrait

TH-50SQE2 500cd/m² 24/7 Operation USB Media Player Portrait

TH-43SQE2 500cd/m² 24/7 Operation USB Media Player Portrait

Entry

CQE2

4K

*Actual Resolution: 3840 x 2160p

A 1 G *only applies for 43-65"

TH-98CQE2 500cd/m² 24/7 Operation USB Media Player Portrait

TH-86CQE2 400cd/m² 16h Operation USB Media Player Portrait

TH-75CQE2 400cd/m² 16h Operation USB Media Player Portrait

TH-65CQE2 500cd/m² 16h Operation USB Media Player Portrait

TH-55CQE2 500cd/m² 16h Operation USB Media Player Portrait

TH-50CQE2 500cd/m² 16h Operation USB Media Player Portrait

TH-43CQE2 500cd/m² 16h Operation USB Media Player Portrait

Multi-Touch Screen

CQE2-IR

4K Multi Touch

*Actual Resolution: 3840 x 2160p

TH-86CQE2-IR 400cd/m² 16h Operation USB Media Player Portrait

TH-75CQE2-IR 400cd/m² 16h Operation USB Media Player Portrait

TH-65CQE2-IR 500cd/m² 16h Operation USB Media Player Portrait

TH-55CQE2-IR 500cd/m² 16h Operation USB Media Player Portrait

LED

AD

LED

*Specifications subject to confirmation

NEW

TL-165AD19A* 700cd/m² 24/7 Operation intel Portrait

TL-137AD15A 700cd/m² 24/7 Operation intel Portrait

TL-110AD12A 700cd/m² 24/7 Operation intel Portrait

Entry

Multi-Touch Screen

LED

Model Number Legend

TH-86SQ2H

Display body Screen size Display category F Full HD Q 4K UHD

Pitch for wall hanging is VESA compliant

NOTE: The availability varies depending on model.
The specifications are subject to change without notice.



For more information about Panasonic Professional Displays,
please visit Display Global Website:
<https://eu.connect.panasonic.com/gb/en/professional-displays>

Pict Descriptions



Wireless Presentation System

PressIT WPS2 Series **NEW**



Note: The transmitter and receiver are also available separately.

Basic set		Transmitter	
TY-WPS2	TY-WPSC2	TY-WPB2	TY-WPBC2
   X 2	  X 2	 X 1	 X 1

360 Degree Camera Speakerphone



PressIT360

Equipped with various video modes



PressIT

Plug & Play Wireless Presentation System
Dongle based wireless presentation system
for fast and simple screen sharing

Lineup



	Basic Set		Receiver (Box)	Receiver (Board)	Transmitter (HDMI™/USB-A)	Transmitter (USB-C)
Model	TY-WPS2	TY-WPSC2	TY-WPR2	TY-SB01WP	TY-WPB2	TY-WPBC2
Applicable product	Flat Panel Display /Projector (Panasonic and others)			*Attachable to a display compatible with Intel® SDM specification slot.	PC/Tablet/Smartphone	
What's included?	1 Receiver (Box) x1 3 Transmitter (HDMI™/USB-A) x2 5 Transmitter case x1	1 Receiver (Box) x1 4 Transmitter (USB-C) x2 5 Transmitter case x1	1 Receiver (Box) x1	2 Receiver x1 *Supports only communication in the 5GHz band.	3 Transmitter (HDMI™/USB-A) x1	4 Transmitter (USB-C) x1

Connects to mobile devices
Genuine Digital AV adaptor by Apple is required.

6GHz Wireless LAN adopted

Presents 4 screens in Full HD [supports 4K]

24 channels available

4K UHD video
max. resolution: 3840 x 2160 pixels, 30p transmission

Low latency image

Connects up to 32 transmitters at once

Lock mode prevents interrupts

HDMI™-CEC command compatible

Supports audio transmission

Share screen without transmitter¹

Shared Supports "Multicast" without a router

¹ Firmware update is required. For details, please contact your dealer

PressIT360

Providing a more realistic meeting with the 360-degree camera speakerphone



High-quality images from a high-performance 360-degree camera
Four high-performance cameras provide 360-degree immersive images.

360-degree orientation microphone and speaker
Covers a 360-degree radius up to 5m/16.4ft for clear sound collection.

Easy to carry and operate meeting
Video and audio data can be sent to your PC with a single USB-C. Diameter 64 mm, height 285 mm, weight approx. 950 g.